

Chapter 69

A Knowledge-Based Approach for Microwire Casting Plant Control

S. Zaporojan

*Technical University of Moldova, Republic of
Moldova*

I. Calmicov

*Technical University of Moldova, Republic of
Moldova*

C. Plotnic

*Technical University of Moldova, Republic of
Moldova*

V. Larin

*Microfir Tehnologii Industriale Ltd, Republic of
Moldova*

ABSTRACT

This chapter presents the main ideas and preliminary results of an applied research project concerning the development of an intelligent plant for microwire casting. The properties of glass-coated microwires are useful for a variety of sensor applications. On the other hand, the process of casting can be one of the methods of nanotechnology and advanced materials. In microwire continuous casting, the main control problem is to maintain the optimum thermal and flow conditions of the process, in order to fabricate the microwire of a given stable diameter. Unlike a conventional casting plant, we propose to use a video camera to take the picture of the molten drop and to control the casting process by means of a knowledge based system. For this reason, a model, that is capable of taking into account the current features of the process and of describing the shape of the drop at each time, is developed. The model presented here should allow us to estimate the geometry of the metal-filled capillary and predict the diameter of microwire at each time during the casting process.

INTRODUCTION

The chapter provides the first results of an ongoing applied research which deals with the development of a knowledge based plant for the fabrication of glass-coated microwires. Glass-

coated microwires are manufactured by means of the Taylor-Ulitovsky technique (Larin et al., 2002). Such microwires show magnetic properties of great technological interest, like magnetic bistability, giant magnetoimpedance effect, soft magnetic and memory shape properties. The above properties are quite useful for a variety of sensor applications. The investigation into technology

DOI: 10.4018/978-1-4666-5125-8.ch069

and physical properties of glass-coated microwires is presently attracting much attention because of their use in sensor devices (Coben et al., 2001) and fiber-based products. For example, the new generation of multi-functional ternary composite materials will be made of microwires, the bio-based polymers and paper.

Glass-coated microwires consist of an inner metallic nucleus covered by a Pyrex-like coating. The typical limits for the metallic core diameter are between 1 and 50 microns. In microwire continuous casting, the main control problem is to maintain the optimum thermal and flow conditions of the process, in order to fabricate the microwire of a given stable diameter. To control the process, the human operator uses indications of a microwire resistance meter. The typical accuracy of the resistance meter is of the order of 5% to 10% within quite narrow limits. On the one hand, it is too difficult to improve and expand the capabilities of the meter. Because of this, the operator cannot use the information from that meter in a wide range of diameters. In other words, an acceptable control of the casting process based on the measured resistance is only possible within some limits. On the other hand, a highly qualified and experienced human operator is capable of maintaining the casting process under control only by using the information captured by his eyes. That information is with respect to color, position, and shape of the molten drop during the casting. However, the quality of such a control is poor (and hence, the quality of microwire).

According to reasons stated above, in this chapter, an approach for microwire casting plant control is suggested. In order to construct a knowledge-based system for the casting plant control, we consider the concepts of machine vision and fuzzy logic control. Our goal is to develop and exploit human operator knowledge. At a first stage, the proposed approach must help (assist) the operator to cast high quality microwire of different diameters. At the same time, the operator's experience and knowledge will be accumulated

on the system during continuous casting. At the second stage, we intend to provide an experimental plant capable to cast almost automatically high quality microwires in a wide range of diameters.

BACKGROUND

The aim of modeling is capturing the essence of phenomena behavior. When complete knowledge of a process eludes us, we build models in order to obtain some measure of control over that process. A model is never entirely correct but it is useful if it explains and predicts the behavior of the process within the limits of precision required for the task. It is essential that the users of the model understand well the conditions over which the model has been developed and consequently the regimes of its validity. If the phenomenon to be modeled is understood well enough to construct a model and if its mathematical formulation is suitable to be analytically or numerically solved, then the resulting model is a powerful tool as it enables us to explain and predict system behavior within the bounds of the validity of model.

The process of microwire casting is qualified with a highly elevated level of complexity. It represents a joining of interactions, such as mechanical, thermal, electrodynamical, physical, and chemical. More than that, those interactions are not just multiple but are overlapped during the time of casting. It can be supposed that a model of casting might be derived from the underlying properties of the process. However, even under various approximations, the final model will be too difficult, of high order, nonlinear and so on.

Having a high degree of complexity, the creation of a mathematical complete and proper model for the automation and optimization of the process of microwire casting represents a highly difficult problem (Berman, 1972). We believe that pure physical and mathematical evaluation of the discussed process doesn't represent a practical solution.

17 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/a-knowledge-based-approach-for-microwire-casting-plant-control/102079

Related Content

Spin Relaxation Mechanisms in the Organic Semiconductor Alq3

Sridhar Patibandla, Bhargava Kanchibotla, Sandipan Pramanik, Supriyo Bandyopadhyay and Marc Cahay (2009). *International Journal of Nanotechnology and Molecular Computation* (pp. 20-38).

www.irma-international.org/article/spin-relaxation-mechanisms-organic-semiconductor/40363

The Crystal Computer - Computing with Inorganic Cellular Frameworks and Nets

Mark D. Symes and Leroy Cronin (2011). *International Journal of Nanotechnology and Molecular Computation* (pp. 24-34).

www.irma-international.org/article/crystal-computer-computing-inorganic-cellular/54342

Influence of Nano-Particle Additives on Bio-Diesel-Fuelled CI Engines: A Review

Tamilvanan A., K. Balamurugan, T. Mohanraj, P. Selvakumar, B. Ashok and R. Sakthivel (2021). *Research Anthology on Synthesis, Characterization, and Applications of Nanomaterials* (pp. 1424-1443).

www.irma-international.org/chapter/influence-of-nano-particle-additives-on-bio-diesel-fuelled-ci-engines/279201

Possibilities of the Quantitative Comparison of Catalytic Capacity in Autocatalytic Processes of Palladium-Containing Nanocatalysts

Zulayho A. Smanova, Tokhir Kh. Rakhimov, Muxtarjan Mukhamediev, Dilfuza A. Gafurova and Dilbar A. Shaxidova (2020). *International Journal of Applied Nanotechnology Research* (pp. 35-46).

www.irma-international.org/article/possibilities-of-the-quantitative-comparison-of-catalytic-capacity-in-autocatalytic-processes-of-palladium-containing-nanocatalysts/273616

Nanorobots: Miniature Machines With Mighty Potential – Exploring the Building Blocks, Crafting Techniques, and Transformative Real-World Implementation

Shruti Awasthi, Archana Nalinan, Lahar Niraj Khandelwal and Disha Maheshwari (2024). *Artificial Intelligence in the Age of Nanotechnology* (pp. 136-174).

www.irma-international.org/chapter/nanorobots/334938