Chapter 10 Coverage Path Planning Using Mobile Robot Team Formations

Prithviraj Dasgupta

University of Nebraska - Omaha, USA

ABSTRACT

The multi-robot coverage path-planning problem involves finding collision-free paths for a set of robots so that they can completely cover the surface of an environment. This problem is non-trivial as the geometry and location of obstacles in the environment is usually not known a priori by the robots, and they have to adapt their coverage path as they discover obstacles while moving in the environment. Additionally, the robots have to avoid repeated coverage of the same region by each other to reduce the coverage time and energy expended. This chapter discusses the research results in developing multi-robot coverage path planning techniques using mini-robots that are coordinated to move in formation. The authors present theoretical and experimental results of the proposed approach using e-puck mini-robots. Finally, they discuss some preliminary results to lay the foundation of future research for improved coverage path planning using coalition game-based, structured, robot team reconfiguration techniques.

INTRODUCTION

Automated exploration of an unknown environment using a multi-robot system is an important topic within robotics that is relevant in several applications of robotic systems. These applications include automated reconnaissance and surveillance operations, automated inspection of engineering structures, and even domestic applications such as automated lawn mowing and vacuum cleaning. An integral part of robotic exploration is coverage path planning - how to enable robots to cover an initially unknown environment using a distributed terrain or area coverage algorithm. The coverage algorithm should ensure that every portion of the environment is covered by the coverage sensor or tool of at least one robot. Simultaneously, to ensure that the coverage is efficient, the coverage algorithm should prevent robots from repeatedly covering the same regions that have already been covered by themselves or by other robots. In most of the current multi-robot area coverage techniques, each robot performs and coordinates its motion individually. While individual coverage has shown promising results in many domains, there are a significant number of scenarios for multi-robot exploration such as

extra-terrestrial exploration, robotic demining, unmanned search and rescue, etc., where the system can perform more efficiently if multiple robots with different types of sensors or redundant arrays of sensors can remain together as single or multiple cohesive teams (Cassinis, 2000; Chien et al., 2005; De Mot, 2005). For example, in the domain of robotic demining (Bloch, Milisavljevc & Acheroy, 2007), where autonomous robots are used to detect buried landmines, the incidence of false positive readings from underground landmines can be significantly reduced if robots with different types of sensors such as ground penetrating radar (GPR), IR (infra-red) sensors and metal detectors are able to simultaneously analyze the signals from potential landmines. In such a scenario, it would benefit if robots, each provided with one of these sensors, are able to explore the environment while maneuvering themselves together as a team. Multi-robot formation control techniques provide a suitable mechanism to build teams of robots that maintain and dynamically reconfigure their formation, while avoiding obstacles along their path (Mastellone, Stipanovic, Graunke, Intlekofer & Spong, 2008; Olfati Saber, 2006; Smith, Egerstedt & Howard, 2009). However, these techniques are not principally concerned with issues related to area coverage and coverage efficiency. To address this deficit, in this paper, we investigate whether multi-robot formation control techniques and multi-robot area coverage techniques can be integrated effectively to improve the efficiency of the area coverage operation in an unknown environment by maintaining teams of multiple robots.

Recently, miniature robots that have a small footprint size are being used for applications such as automated exploration of engineering structures (Rutishauser, Corell & Martinoli, 2009; Tache *et al.*, 2009). Similarly, unmanned aerial vehicles (UAVs) and micro-helicopters that have memory and computation capabilities comparable to these mini-robots are being widely used in several domains such as aerial reconnaissance

for homeland security, search and rescue following natural disasters, monitoring forest fires, wildlife monitoring, etc (Boccalate et al., 2013). Mini-robots are attractive because they are relatively inexpensive to field and a swarm of several mini-robots can be fielded at a cost comparable to fielding one or a few large robots. A multi-robot system that consists of several mini-robots also improves the robustness of the system. However, coordinating the actions of mini-robots to make them work cooperatively (e.g., move in formation) in a distributed manner becomes a challenging problem. We have approached this problem using a flocking-based technique (Gokce & Sahin, 2009; Balch & Arkin, 1998) to control the movement of robots so that they can move in formation. We have theoretically analyzed our team-formation techniques and identified certain conditions under which team formation improves the efficiency of distributed area coverage. We have also verified our techniques through extensive experiments on the Webots robotic simulation platform as well as using physical robots within an indoor environment. Our analytical and experimental results show that our team-based coverage techniques for distributed area coverage can perform comparably with other coverage strategies where the robots are coordinated individually. We also show that various parameters of the system such as the size of the robot teams, the presence of localization noise and wheel slip noise (error in the wheel's encoder readings caused by the slippage of the wheels on the floor), as well as environmentrelated features like the size of the environment and the presence of obstacles and walls significantly affect the performance of the area coverage operation. Finally, we discuss a promising future direction to improve the quality of coverage by multi-robot teams by using a coalition game-based technique for systematically restructuring robots teams through splitting and merging, based on the geometry of obstacles perceived by the robots while moving in the environment.

32 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/coverage-path-planning-using-mobile-robot-team-formations/115306

Related Content

On the Value of Aspiration Criteria in Tabu Search

Lars Magnus Hvattum (2016). *International Journal of Applied Metaheuristic Computing (pp. 39-49)*. www.irma-international.org/article/on-the-value-of-aspiration-criteria-in-tabu-search/165026

Advancing Malware Classification With an Evolving Clustering Method

Chia-Mei Chenand Shi-Hao Wang (2018). International Journal of Applied Metaheuristic Computing (pp. 1-12).

www.irma-international.org/article/advancing-malware-classification-with-an-evolving-clustering-method/204491

Evolving Concepts

(2018). Concept Parsing Algorithms (CPA) for Textual Analysis and Discovery: Emerging Research and Opportunities (pp. 49-57).

www.irma-international.org/chapter/evolving-concepts/186507

Multi-Objective Big Data View Materialization Using MOGA

Akshay Kumarand T. V. Vijay Kumar (2022). International Journal of Applied Metaheuristic Computing (pp. 1-28).

www.irma-international.org/article/multi-objective-big-data-view-materialization-using-moga/292499

A Multiobjective Genetic-Algorithm-Based Optimization of Micro-Electrical Discharge Drilling: Enhanced Quality Micro-Hole Fabrication in Inconel 718

Deepak Rajendra Ununeand Amit Aherwar (2018). Handbook of Research on Emergent Applications of Optimization Algorithms (pp. 728-749).

www.irma-international.org/chapter/a-multiobjective-genetic-algorithm-based-optimization-of-micro-electrical-dischargedrilling/190183