# Chapter 55 Theoretical Analyses of the Universal Approximation Capability of a Class of Higher Order Neural Networks Based on Approximate Identity

Saeed Panahian Fard Universiti Sains, Malaysia

Zarita Zainuddin Universiti Sains, Malaysia

## ABSTRACT

One of the most important problems in the theory of approximation functions by means of neural networks is universal approximation capability of neural networks. In this study, we investigate the theoretical analyses of the universal approximation capability of a special class of three layer feedforward higher order neural networks based on the concept of approximate identity in the space of continuous multivariate functions. Moreover, we present theoretical analyses of the universal approximation capability of the networks in the spaces of Lebesgue integrable multivariate functions. The methods used in proving our results are based on the concepts of convolution and epsilon-net. The obtained results can be seen as an attempt towards the development of approximation theory by means of neural networks.

## **1. INTRODUCTION**

The function approximation can be explained as follows: Let be a continuous function on a compact set. We intend to find a simple function *g* such that  $||f-g|| < \varepsilon$ . This problem has attracted many researchers' attentions in the last century. According to Tikk et al. (2003), in 1900, Hilbert presented his 23 conjectures at the second international congress of mathematicians in Paris. Based on the 13th conjecture, there exist continuous functions with multi variables which cannot be represented as the finite superposition

DOI: 10.4018/978-1-5225-0788-8.ch055

#### Theoretical Analyses of the Universal Approximation Capability

of continuous functions with fewer variables. In 1957, Arnold rejected this conjecture. In the same year, Kolmogorov proved his representation theorem with a constructive proof. This theorem shows that a continuous function with multi variables can be decomposed as the finite superposition of continuous functions with one variable. In 1965, Sprecher improved the Kolmogorov's representation theorem. In 1966, Lorentz further improved this theorem.

In the approximation theory of artificial neural networks (ANNs) that problem reduces to find an artificial neural network such that approximate f, i.e. *IIf*–ANNs*II*<e. In 1980, De Figueriedo generalized this theorem for multilayer feedforward artificial neural networks. In 1989, Poggio and Girosi showed that this theorem is irrelevant for artificial neural networks because in a Kolmogorov networks, nodes have wild and complex functions. Then, many researchers have been tried to solve the problem of approximation function by artificial neural networks such as Cybenko (1989), Funuhashi (1989), Park and Sandberg, (1991, 1993), Mhaskar, (1993), Leshno (1993), Suzuki (1998), Hahm and Hong, (2004), Li (2008), Ismailov (2012), Wang et al. (2012), Lin et al. (2013), and Arteaga and Marrero (2013).

The standard form of universal approximation capability of feedforward neural networks states that under what kind of conditions an arbitrary continuous function can be approximated by a single-hiddenlayer feedforward neural networks to any degree of accuracy. Comprehensive surveys of the universal approximation capability of feedforward neural networks can be found in Nong (2013); Bouaziz et al. (2014); Wang (2010); Ismailov (2014); Arteaga and Marrero (2014), Costarelli (2014). Recently, the history of the development of universal approximation by artificial neural networks has been presented by Pricipe and Chen (2015).

In the present chapter, we are motivated to extend the scheme of the univariate universal approximation capability to the scheme of the multivariate universal approximation capability. In other words, the motivation of this chapter is to develop the theory of the universal approximation capability of a class of feedforward higher order neural networks based on approximate identity in multivariate functions spaces. We should address what we can expect from higher order neural networks based on approximate identity. In fact, higher order neural networks based on approximate identity are merging higher order neural networks and approximate identity neural networks.

Higher order neural networks extend standard feedforward neural networks by using a higher correlation of input neurons for better fitting properties. Higher order neural networks was first studied by Giles and Maxwell (1987) and further analysed by Pao (1989). The above networks have also been used in pattern recognition (Schmit & Davis, 1993), financial data simulation (Zhang et al., 2002). In recent years, universal approximation capability of different models of higher order neural networks have been investigated (Long et al., 2007; Long et al., 2007a).

Approximate identity neural networks are neural networks models which employ approximate identity as neuron activation functions. We briefly review the literature of this field of research. Turchetti et al. published the first paper on approximate identity neural networks (Turchetti, 1998). In recent years, universal approximation capability of several different types of approximate identity neural networks models have been investigated (Panahian & Zainuddin, 2013, 2014, 2012, 2014a, 2013a, 2014b, 2015, 2014c, 2014d).

The objective of this study is to describe an approximate representation of multivariate functions by a class of three layer feedforward higher order neural networks based on approximate identity in the space of continuous multivariate functions and in the spaces of Lebesgue integrable multivariate functions. In other words, we aim to provide an answer to the question that what kind of three layer feedforward

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/theoretical-analyses-of-the-universalapproximation-capability-of-a-class-of-higher-order-neural-networks-basedon-approximate-identity/161078

## **Related Content**

Algorithms and Methods Inspired from Nature for Solving Supply Chain and Logistics Optimization Problems: A Survey

Georgios Douniasand Vassilios Vassiliadis (2014). *International Journal of Natural Computing Research* (pp. 26-51).

www.irma-international.org/article/algorithms-and-methods-inspired-from-nature-for-solving-supply-chain-and-logisticsoptimization-problems/118156

## Data Analysis Tools for Neural Data Cognitive Computing: Neural-Inspired Algorithms

Shiddarth Srivastavaand Rashmi Sharma (2023). Exploring Future Opportunities of Brain-Inspired Artificial Intelligence (pp. 139-156).

www.irma-international.org/chapter/data-analysis-tools-for-neural-data-cognitive-computing/320614

## Solving Uncapacitated Facility Location Problem Using Heuristic Algorithms

Soumen Atta, Priya Ranjan Sinha Mahapatraand Anirban Mukhopadhyay (2019). International Journal of Natural Computing Research (pp. 18-50).

www.irma-international.org/article/solving-uncapacitated-facility-location-problem-using-heuristic-algorithms/225822

## Automatic Test Data Generation Using Bio-Inspired Algorithms: A Travelogue

Madhumita Pandaand Sujata Dash (2018). *Handbook of Research on Modeling, Analysis, and Application of Nature-Inspired Metaheuristic Algorithms (pp. 140-159).* www.irma-international.org/chapter/automatic-test-data-generation-using-bio-inspired-algorithms/187685

## Materialized View Selection using Marriage in Honey Bees Optimization

Biri Arunand T.V. Vijay Kumar (2015). International Journal of Natural Computing Research (pp. 1-25). www.irma-international.org/article/materialized-view-selection-using-marriage-in-honey-bees-optimization/146882