

Chapter 4

Multi-Thresholded Histogram Equalization Based on Parameterless Artificial Bee Colony

Krishna Gopal Dhal

Midnapore College (Autonomous), India

Mandira Sen

Tata Consultancy Services, India

Swarnajit Ray

JBMatrix Technology Pvt. Ltd., India

Sanjoy Das

University of Kalyani, India

ABSTRACT

This chapter presents a novel variant of histogram equalization (HE) method called multi-thresholded histogram equalization (MTHE), depending on entropy-based multi-level thresholding-based segmentation. It is reported that proper segmentation of the histogram significantly assists the HE variants to maintain the original brightness of the image, which is one of the main criterion of the consumer electronics field. Multi-separation-based HE variants are also very effective for multi-modal histogram-based images. But, proper multi-separation of the histogram increases the computational time of the corresponding HE variants. In order to overcome that problem, one novel parameterless artificial bee colony (ABC) algorithm is employed to solve the multi-level thresholding problem. Experimental results prove that proposed parameterless ABC helps to reduce the computational time significantly and the proposed MTHE outperforms several existing HE variants in brightness preserving histopathological image enhancement domain.

DOI: 10.4018/978-1-5225-5020-4.ch004

INTRODUCTION

Contrast enhancement methods have been applied for better visual interpretation. Histogram Equalization (HE) is one of the most simple and widely used method for contrast enhancement (Gonzalez, R.C., Woods, R.E. (2002)). Basically HE computes linear cumulative histogram of the original image and dispenses intensity values over its dynamic intensity range. HE based techniques have been used in medical image processing, satellite image processing etc. The method of Traditional Histogram Equalization (Gonzalez, R.C., Woods, R.E. (2002)) is described below:

The method of Traditional Histogram Equalization (Chen, S. D., Ramli, A. R. (2004)) has the following steps:

If the original image $f(i, j)$ has total W number of pixels within the dynamic range $[X_0, X_{L-1}]$, where L is the number of discrete gray levels, then the probability density function $H1(X_k)$ of intensity level X_k of the image is given by:

$$H1(X_k) = \frac{n_k}{W} \text{ for } 0 \leq k \leq L - 1 \quad (1)$$

Where, n_k is the total number of pixels with intensity level X_k . The plot of X_k vs. n_k is the histogram of image f . the cumulative density function is defined as (Chen, S. D., Ramli, A. R. (2004)):

$$CDF(X_k) = \sum_{i=0}^k H1(X_i) \quad (2)$$

Traditional HE maps the corresponding image into the total dynamic range $[X_0, X_{L-1}]$ with the help of the CDF as given below:

$$f(X) = X_0 + (X_{L-1} - X_0).CDF(X) \quad (3)$$

In the HE procedure the entire gray levels are distributed uniformly, HE improves the image contrast and maximizes the image entropy and also change the mean brightness of the output image to the middle of the gray level regardless of the input image's mean (Chen, S. D., Ramli, A. R. (2004), Kim, Y.T. (1997)). The equation of mean or statistical expectation $E(\cdot)$ of the output image G is given below:

17 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/multi-thresholded-histogram-equalization-based-on-parameterless-artificial-bee-colony/202193

Related Content

Towards a Methodology for Monitoring and Analyzing the Supply Chain Behavior

Reinaldo Moraga, Luis Rabelo and Alfonso Sarmiento (2008). *Handbook of Computational Intelligence in Manufacturing and Production Management* (pp. 186-208).

www.irma-international.org/chapter/towards-methodology-monitoring-analyzing-supply/19359

Granular Computing and Human-Centricity in Computational Intelligence

Witold Pedrycz (2012). *Machine Learning: Concepts, Methodologies, Tools and Applications* (pp. 1721-1735).

www.irma-international.org/chapter/granular-computing-human-centricity-computational/56222

Machine Learning Approach for Multi-Layered Detection of Chemical Named Entities in Text

Usha B. Biradar, Harsha Gurulingappa, Lokanath Khamari and Shashikala Giriyan (2016). *International Journal of Software Science and Computational Intelligence* (pp. 1-15).

www.irma-international.org/article/machine-learning-approach-for-multi-layered-detection-of-chemical-named-entities-in-text/161709

Relevant and Non-Redundant Amino Acid Sequence Selection for Protein Functional Site Identification

Chandra Das and Pradipta Maji (2010). *International Journal of Software Science and Computational Intelligence* (pp. 19-43).

www.irma-international.org/article/relevant-non-redundant-amino-acid/43896

An Innovative Model for Detecting Brain Tumors and Glioblastoma Multiforme Disease Patterns

Peifang Guo and Prabir Bhattacharya (2017). *International Journal of Software Science and Computational Intelligence* (pp. 34-45).

www.irma-international.org/article/an-innovative-model-for-detecting-brain-tumors-and-glioblastoma-multiforme-disease-patterns/197784