Chapter 4 Multi-Thresholded Histogram Equalization Based on Parameterless Artificial Bee Colony

Krishna Gopal Dhal Midnapore College (Autonomous), India

Mandira Sen Tata Consultancy Services, India

Swarnajit Ray JBMatrix Technology Pvt. Ltd., India

> **Sanjoy Das** University of Kalyani, India

ABSTRACT

This chapter presents a novel variant of histogram equalization (HE) method called multi-thresholded histogram equalization (MTHE), depending on entropy-based multi-level thresholding-based segmentation. It is reported that proper segmentation of the histogram significantly assists the HE variants to maintain the original brightness of the image, which is one of the main criterion of the consumer electronics field. Multi-separation-based HE variants are also very effective for multi-modal histogram-based images. But, proper multi-seaparation of the histogram increases the computational time of the corresponding HE variants. In order to overcome that problem, one novel parameterless artifical bee colony (ABC) algorithm is employed to solve the multi-level thresholding problem. Experimental results prove that proposed parameterless ABC helps to reduce the computational time significantly and the proposed MTHE outperforms several existing HE variants in brightness preserving histopathological image enhancement domain.

DOI: 10.4018/978-1-5225-5020-4.ch004

INTRODUCTION

Contrast enhancement methods have been applied for better visual interpretation. Histogram Equalization (HE) is one of the most simple and widely used method for contrast enhancement (Gonzalez, R.C., Woods, R.E. (2002)). Basically HE computes linear cumulative histogram of the original image and dispenses intensity values over its dynamic intensity range. HE based techniques have been used in medical image processing, satellite image processing etc. The method of Traditional Histogram Equalization (Gonzalez, R.C., Woods, R.E. (2002)) is described below:

The method of Traditional Histogram Equalization (Chen, S. D., Ramli, A. R. (2004)) has the following steps:

If the original image f(i, j) has total W number of pixels within the dynamic range $[X_0, X_{L-1}]$, where L is the number of discrete gray levels, then the probability density function $H1(X_k)$ of intensity level X_k of the image is given by:

$$H1(X_{k}) = \frac{n_{k}}{W} \text{ for } 0 \le k \le L - 1$$

$$\tag{1}$$

Where, n_k is the total number of pixels with intensity level X_k . The plot of X_k vs. n_k is the histogram of image f. the cumulative density function is defined as (Chen, S. D., Ramli, A. R. (2004)):

$$CDF(X_{k}) = \sum_{i=0}^{k} H1(X_{i})$$
(2)

Traditional HE maps the corresponding image into the total dynamic range $[X_0, X_{L-1}]$ with the help of the CDF as given below:

$$f(X) = X_0 + (X_{L-1} - X_0).CDF(X)$$
(3)

In the HE procedure the entire gray levels are distributed uniformly, HE improves the image contrast and maximizes the image entropy and also change the mean brightness of the output image to the middle of the gray level regardless of the input image's mean (Chen, S. D., Ramli, A. R. (2004), Kim, Y.T. (1997)). The equation of mean or statistical expectation E(.) of the output image G is given below: 17 more pages are available in the full version of this document, which may be purchased using the "Add to Cart"

button on the publisher's webpage: www.igi-

global.com/chapter/multi-thresholded-histogram-equalization-

based-on-parameterless-artificial-bee-colony/202193

Related Content

Users' Consumption Behavior Recognition Based on SMOTE and Improved AdaBoost

(2022). International Journal of Software Science and Computational Intelligence (pp. 0-0).

www.irma-international.org/article//309424

A Preparation Framework for EHR Data to Construct CBR Case-Base

Shaker El-Sappagh, Mohammed Mahfouz Elmogy, Alaa M. Riad, Hosam Zaghlouland Farid A. Badria (2017). *Handbook of Research on Machine Learning Innovations and Trends (pp. 345-378).*

www.irma-international.org/chapter/a-preparation-framework-for-ehr-data-to-construct-cbr-casebase/180953

A Feature Selection Approach in the Study of Azorean Proverbs

Luís Cavique, Armando B. Mendes, Matthias Funkand Jorge M. A. Santos (2014). *Exploring Innovative and Successful Applications of Soft Computing (pp. 38-58).* www.irma-international.org/chapter/a-feature-selection-approach-in-the-study-of-azoreanproverbs/91873

Chaotic Tornadogenesis Optimization Algorithm for Data Clustering Problems

Ravi Kumar Saidalaand Nagaraju Devarakonda (2018). *International Journal of Software Science and Computational Intelligence (pp. 38-64).* www.irma-international.org/article/chaotic-tornadogenesis-optimization-algorithm-for-dataclustering-problems/199016

EEG Feature Extraction and Pattern Classification Based on Motor Imagery in Brain-Computer Interface

Ling Zou, Xinguang Wang, Guodong Shiand Zhenghua Ma (2011). *International Journal of Software Science and Computational Intelligence (pp. 43-56).* www.irma-international.org/article/eeg-feature-extraction-pattern-classification/60748