Chapter 31 Neighborhood Rough-Sets-Based Spatial Data Analytics

Sharmila Banu K VIT University, India

B. K. Tripathy *VIT University, India*

ABSTRACT

Rough set theory partitions a universe using single-layered granulation. The equivalence classes induced by rough sets are based on discretized values. Considering the fact that the spatial data are continuous at large, discretizing them may cause loss of data. Neighborhood approximations can lead to closely related coverings using continuous values. Besides, the spatial attributes also need to be given due consideration and should be handled unlike non-spatial attributes in the process of dimensionality reduction. This chapter analyzes the use of neighborhood rough sets for continuous data and handling spatially correlated attributes using rough sets.

INTRODUCTION

With the huge amount of data generated every day, governments, corporates and scientists look at mining useful information from them. Considering the storage and organization costs of these data, the useful trade-off is to discover useful patterns in them. Transactional, telecommunication, spatial, satellite, remote sensing, medical informatics etc., are some of the domains dealing with *Big Data*. Discovering patterns and inferring predictions are vital to the well-being of man-kind at large. Analysis of spatial data usually includes construction of information system, dimensionality reduction, decision rule extraction based on a computational model and error analysis. This chapter focuses on the construction decision systems, proposes a hybrid method by substantiating the advantages and challenges involved with spatial data.

Spatial Data upholds an important perspective that it can be analysed only with respect to specific spatial reference (or a geographic area). Spatial data include spatial attributes like temperature, rainfall, humidity, slope, land cover etc., These features will be with respect to a spatial reference and encompass spatial auto correlation. Spatial auto correlation is the property of spatial data where the values of a

DOI: 10.4018/978-1-5225-7598-6.ch031

feature will tend to be similar in a neighborhood and vary with increasing distance from the neighborhood. Figure 1 illustrates a sample region identified with latitudes and longitudes. A number of spatial features can be measured and some of them are shown in Table 1.

BACKGROUND

Mining spatial data is useful in fields like weather forecasting, natural calamity prediction, crime management, transmission and spread of infectious diseases and others. This calls for expertise in these areas and the nature of spatial data. For example, representing topology in spatial data modelling is inherent to dealing with uncertainties. And, Rough Sets have been used to deal with uncertainty in spatial data mining. Pawlak's (1982) Rough Set Theory (RST) has been used to model spatial regions with unclear boundaries. Beaubouef and Petry (1994) have demonstrated the use of rough sets have been used to query crisp data in relational databases. The Region Connection Calculus (RCC) proposed by Randell & Cohn (1992) and Egg-Yolk models by Cohn and Gotts (1996) have been blended with the approximation concepts of RST to identify vague region boundaries. Rough sets have been used by Bai et. al (2010) to identify villages with birth defects, Ahlqvist (2005) for spatial classification and analysis, Leung et. al. (2007) for discovering classification rules in remote sensor data, Øhrn A (1999) for disease diagnosis and outcome prediction and Thangavel and Pethalakshmi (2006) for dimensionality reduction.

Spatial Data Analysis presents a myriad of challenges in modelling due to the uncertainty intrinsic to it. Spatial auto correlation is yet another feature which presents the reference with core and periphery. And clearly RST can handle this with its approximation concepts.



Figure 1. A sample geographic region

10 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/neighborhood-rough-sets-based-spatial-dataanalytics/214632

Related Content

A Case for Leveraging Mobile Learning in Action Learning Teams

Shawn McCann (2019). Advancing Mobile Learning in Contemporary Educational Spaces (pp. 1-23). www.irma-international.org/chapter/a-case-for-leveraging-mobile-learning-in-action-learning-teams/234046

Enterprise Network Packet Filtering for Mobile Cryptographic Identities

Janne Lindqvist, Essi Vehmersalo, Miika Komuand Jukka Manner (2010). *International Journal of Handheld Computing Research (pp. 79-94).* www.irma-international.org/article/enterprise-network-packet-filtering-mobile/39054

Adaptive Dynamic Path Planning Algorithm for Interception of a Moving Target

H. H. Triharminto, A.S. Prabuwono, T. B. Adjiand N. A. Setiawan (2013). *International Journal of Mobile Computing and Multimedia Communications (pp. 19-33).* www.irma-international.org/article/adaptive-dynamic-path-planning-algorithm/80425

B-POS Secure Mobile Payment System

Antonio Grillo, Alessandro Lentiniand Gianluigi Me (2009). *Mobile Computing: Concepts, Methodologies, Tools, and Applications (pp. 1237-1245).* www.irma-international.org/chapter/pos-secure-mobile-payment-system/26584

Term Ordering-Based Query Expansion Technique for Hindi-English CLIR System

Ganesh Chandraand Sanjay K. Dwivedi (2020). Handling Priority Inversion in Time-Constrained Distributed Databases (pp. 283-302).

www.irma-international.org/chapter/term-ordering-based-query-expansion-technique-for-hindi-english-clir-system/249436