

Chapter 2.10

Question Answering from Procedural Semantics to Model Discovery

John Kontos

National and Kapodistrian University of Athens, Greece

Ioanna Malagardi

National and Kapodistrian University of Athens, Greece

INTRODUCTION

Question Answering (QA) is one of the branches of Artificial Intelligence (AI) that involves the processing of human language by computer. QA systems accept questions in natural language and generate answers often in natural language. The answers are derived from databases, text collections, and knowledge bases. The main aim of QA systems is to generate a short answer to a question rather than a list of possibly relevant documents. As it becomes more and more difficult to find answers on the World Wide Web (WWW) using standard search engines, the technology of QA systems will become increasingly important. A series of systems that can answer questions from various data or knowledge sources are briefly described. These systems provide a friendly in-

terface to the user of information systems that is particularly important for users who are not computer experts. The line of development of ideas starts with procedural semantics and leads to interfaces that support researchers for the discovery of parameter values of causal models of systems under scientific study. QA systems historically developed roughly during the 1960-1970 decade (Simmons, 1970). A few of the QA systems that were implemented during this decade are:

- The BASEBALL system (Green et al., 1961)
- The FACT RETRIEVAL System (Cooper, 1964)
- The DELFI systems (Kontos & Kossidas, 1971; Kontos & Papakontantinou, 1970)

The BASEBALL System

This system was implemented in the Lincoln Laboratory and was the first QA system reported in the literature according to the references cited in the first book with a collection of AI papers (Feigenbaum & Feldman, 1963). The inputs were questions in English about games played by baseball teams. The system transformed the sentences to a form that permitted search of a systematically organized memory store for the answers. Both the data and the dictionary were list structures, and questions were limited to a single clause.

The FACT RETRIEVAL System

The system was implemented using the COMIT compiler-interpreter system as programming language. A translation algorithm was incorporated into the input routines. This algorithm generated the translation of all information sentences and all question sentences into their logical equivalents.


The DELFI System

The DELFI system answers natural language questions about the space relations between a set of objects. These are questions with unlimited nesting of relative clauses that were automatically translated into retrieval procedures consisting of general-purpose procedural components that retrieved information from the database that contained data about the properties of the objects and their space relations. The system was a QA system based on procedural semantics. The following is an example of a question put to the DELFI system:

“Is an object that has dotted contour below the object number 2?”

The answer is, “Yes, object no. 4,” given the objects with numbers 1, 2, 3, 4, and 5 as shown

Figure 1. The objects of the DELFI I example application database



in Figure 1 (Kontos, 2004; Kontos & Papakonstantinou, 1970).

The DELFI II System

The DELFI II system (Kontos & Kossidas, 1971) was an implementation of the second edition of the system DELFI augmented by deductive capabilities. In this system, the procedural semantics of the questions are expressed using macro-instructions that are submitted to a macro-processor that expands them with a set of macro-definitions into full programs. Every macro-instruction corresponded to a procedural semantic component. In this way, a program was generated that corresponded to the question and could be compiled and executed in order to generate the answer. DELFI II was used in two new applications. These applications concerned the processing of the database of the personnel of an organization and the answering of questions by deduction from a database with airline flight schedules using the following rules:

- If flight F1 flies to city C1, and flight F2 departs from city C1, then F2 follows F1.

7 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/question-answering-procedural-semantics-model/24300

Related Content

Traffic Congestion Reduction and Accident Circumvention System via Incorporation of CAV and VANET

Mohsin Khan and Bhavna Arora (2021). *International Journal of Ambient Computing and Intelligence* (pp. 53-72).

www.irma-international.org/article/traffic-congestion-reduction-and-accident-circumvention-system-via-incorporation-of-cav-and-vanet/272039

Quantum Computing AI: Application of Artificial Intelligence in the Era of Quantum Computing

Ankita Nayak, Atmika Patnaik, Ipseeta Satpathy, Alex Khang and B. C. M. Patnaik (2024). *Applications and Principles of Quantum Computing* (pp. 113-128).

www.irma-international.org/chapter/quantum-computing-ai/338286

Towards a Possibilistic Information Retrieval System Using Semantic Query Expansion

Bilel Elayeb, Ibrahim Bounhas, Oussama Ben Khiroun, Fabrice Evrard and Narjès Bellamine-BenSaoud (2011). *International Journal of Intelligent Information Technologies* (pp. 1-25).

www.irma-international.org/article/towards-possibilistic-information-retrieval-system/60655

Approximate Fuzzy Continuity of Functions

Mark Burgin and Oktay Duman (2011). *International Journal of Fuzzy System Applications* (pp. 37-46).

www.irma-international.org/article/approximate-fuzzy-continuity-functions/60379

ANN-Based Defects' Diagnosis of Industrial Optical Devices

Matthieu Voiry, Véronique Amarger, Joel Bernier and Kurosh Madani (2009). *Encyclopedia of Artificial Intelligence* (pp. 131-137).

www.irma-international.org/chapter/ann-based-defects-diagnosis-industrial/10237