

Chapter XVI

MMIR: An Advanced Content-Based Image Retrieval System Using a Hierarchical Learning Framework

Min Chen

Florida International University, USA

Shu-Ching Chen

Florida International University, USA

ABSTRACT

This chapter introduces an advanced content-based image retrieval (CBIR) system, MMIR, where Markov model mediator (MMM) and multiple instance learning (MIL) techniques are integrated seamlessly and act coherently as a hierarchical learning engine to boost both the retrieval accuracy and efficiency. It is well-understood that the major bottleneck of CBIR systems is the large semantic gap between the low-level image features and the high-level semantic concepts. In addition, the perception subjectivity problem also challenges a CBIR system. To address these issues and challenges, the proposed MMIR system utilizes the MMM mechanism to direct the focus on the image level analysis together with the MIL technique (with the neural network technique as its core) to real-time capture and learn the object-level semantic concepts with some help of the user feedbacks. In addition, from a long-term learning perspective, the user feedback logs are explored by MMM to speed up the learning process and to increase the retrieval accuracy for a query. The comparative studies on a large set of real-world images demonstrate the promising performance of our proposed MMIR system.

INTRODUCTION

Content-based image retrieval (CBIR), which was proposed in the early 1990s, has attracted a broad range of research interests from many computer communities in the past decade. Generally speaking, in a CBIR system, each image is first mapped to a point in a certain feature space, where the features

can be categorized into color (Stehling, Nascimento, & Falcao, 2000), texture (Kaplan et al., 1998), shape (Zhang & Lu, 2002), and so forth. Next, given a query in terms of image examples, the system retrieves images with regard to their features (He, Li, Zhang, Tong, & Zhang, 2004). Though extensive research efforts have been directed into this area, it still remains a big challenge and an open issue in terms of retrieving the desired images from the large image repositories effectively and efficiently. In short, some of the major obstacles can be summarized as follows.

- First, it is widely accepted that the major bottleneck of CBIR systems is the large semantic gap between the low-level image features and high-level semantic concepts, which prevents the systems from being applied to real applications (Hoi & Lyu, 2004).
- Second, the perception subjectivity problem poses additional challenges for CBIR systems. In other words, in viewing the same image (e.g., Figure 1a), different users might possess various interests in either a certain object (e.g., the house, the tree, etc.) or the entire image (e.g., a landscape during the autumn season). In this case, Figure 1b, Figure 1c, or Figure 1d, respectively, might be considered as the relevant image with regard to Figure 1a. In addition, even a same user can have different perceptions toward the same image at various situations and with different purposes.

To address the earlier-mentioned challenges and issues, a certain form of adaptive (i.e., data-driven) description is required to capture the salient meaning of each image. In addition, the system should be able to expedite the navigation process through a large image database with the facilitation of users' relevance feedbacks. In other words, the search engine should be equipped with an inference engine to observe and learn from user interactions. To this extent, we believe that there are both a need and an opportunity to systematically incorporate machine learning techniques into an integrated approach for content-based image retrieval. In this chapter, we introduce an advanced content-based image retrieval system called MMIR, where Markov model mediator (MMM) and multiple instance learning (MIL)

Figure 1. Example images



(a)



(b)



(c)



(d)

15 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:
www.igi-global.com/chapter/mmir-advanced-content-based-image/4164

Related Content

Analysis of Different Feature Description Algorithm in object Recognition

Sirshendu Hore, Sankhadeep Chatterjee, Shouvik Chakraborty and Rahul Kumar Shaw (2017). *Feature Detectors and Motion Detection in Video Processing* (pp. 66-99).

www.irma-international.org/chapter/analysis-of-different-feature-description-algorithm-in-object-recognition/170213

Techniques for Skin, Face, Eye and Lip Detection using Skin Segmentation in Color Images

Mohammadreza Hajiarbabian and Arvin Agah (2015). *International Journal of Computer Vision and Image Processing* (pp. 35-57).

www.irma-international.org/article/techniques-for-skin-face-eye-and-lip-detection-using-skin-segmentation-in-color-images/159806

Adapted Approach for Omnidirectional Egomotion Estimation

A. Radgui, C. Demonceaux, E. Mouaddib, M. Rziza and D. Aboutajdine (2013). *Intelligent Computer Vision and Image Processing: Innovation, Application, and Design* (pp. 1-13).

www.irma-international.org/chapter/adapted-approach-omnidirectional-egomotion-estimation/77028

Brain Tumor Detection Using Multipath Convolution Neural Network (CNN)

Mukesh Kumar Chandrakar and Anup Mishra (2020). *International Journal of Computer Vision and Image Processing* (pp. 43-53).

www.irma-international.org/article/brain-tumor-detection-using-multipath-convolution-neural-network-cnn/264220

Multi Orientation Text Detection in Natural Imagery: A Comparative Survey

Deepak Kumar and Ramandeep Singh (2018). *International Journal of Computer Vision and Image Processing* (pp. 41-56).

www.irma-international.org/article/multi-orientation-text-detection-in-natural-imagery/214073