

Chapter 11

Game Theory and Femtocell Communications: Making Network Deployment Feasible

Mehdi Bennis

University of Oulu, Finland

Samir Medina Perlaza

Orange Labs, France

Merouane Debbah

SUPELEC, France

ABSTRACT

Game Theory (GT) is a natural paradigm to study and analyze wireless networks where players compete for the same resources. The importance of studying the coexistence between macro- and femtocells from a game theoretical perspective is multi-fold: First, by modeling the dynamic spectrum sharing among network players as games, the behaviors and actions of players can be analyzed in a formalized structure, by which the theoretical achievements in GT can be fully utilized. Second, GT equips us with various optimality criteria for the spectrum sharing problems, which are of key importance when it comes to analyzing the equilibrium of the game. Third, the application of GT enables us to derive efficient distributed algorithms for femtocell networks relying only on partial information. Without a doubt, the theory of learning in games is instrumental in allowing players to choose the right strategies and gradually learn from their environment until convergence.

1. INTRODUCTION

The provision of high data rate services imposes stringent requirements on cellular communication systems. Particularly, indoor users or those trying to communicate at cell border are severely affected by poor coverage and uneven guarantee of Quality

of Service (QoS). In this context, the femtocell concept constitutes an inexpensive alternative to increase capacity, while coping with the scarcity of resources, providing better spectral efficiency and improving spatial reuse. However, the deployment of femtocell sites faces challenging obstacles: resource allocation, timing and synchronization, reliable IP backhaul, interference management,

DOI: 10.4018/978-1-4666-0092-8.ch012

mobility control, self-organization and security issues. Among all the technical challenges, the Co-Channel Interference (CCI) arising from uncoordinated transmissions generated by other femtocells and the overlay macrocell is the most demanding (Chandrasekhar 2009; Claussen 2008 among others).

The expected contribution of this chapter is as follows: In the first section of the chapter, we show that the deployment of femtocell networks is cast into a dynamic spectrum sharing (Bennis 2009; Bennis 2010; Perlaza 2008) problem with different interference scenarios such as femtocell-to-femtocell and femtocell-to-macrocell interference. Femto Base Stations (FBSs) and their associated Femtocell User Equipments (FUEs) need to autonomously determine their transmission strategies in order to maximize their own performance metrics. Often, this configuration is described by the power allocation scheme, channel/carrier selection, modulation scheme, etc. However, the transmission configuration of one femto-base station affects the performance of other FBS and all their associated FUEs. Hence, this scenario is clearly a competition of selfish autonomous devices for radio resources. Under these conditions, GT appears as one of the paradigms to study these types of networks. Finally, in this section, we provide the fundamental concepts of game theory required to understand the results presented in the rest of this chapter. The second section tackles one of the most important issues in self organized networks, namely learning. Due to their non-coordinated nature, femtocells opportunistically share the spectrum with the macrocell network while mitigating interference among each others. In order to do so, femtocells need to self-organize and optimize their strategies/actions (power level, carrier allocation etc) taking into account their side information. Learning is an inherent part of self-organization paradigms and is crucial for developing and adapting multi-agent strategies based on their perceived reward. The problem boils down as to how femtocells

gradually learn from their environment (through trials-and-errors) while at the same time not interfering with the overlay macrocell network. Furthermore, learning is adamantly driven by the type of information available at every agent where the possibility of exchanging their local information drives the learning efficiency (and convergence) and thereby their respective pay-offs. For this purpose, we will investigate both private and public information exchange among femtocells. The third section looks into the QoS provisioning of femtocell networks, in which femtocells mitigate their interference towards the overlay macrocell network. Tools from game theory and Stochastic geometry are used to come up with decentralized algorithms to achieve the equilibrium (Lasaulce 2009) of the game. The fourth section investigates the spectral efficiency of femtocell networks using the framework of potential games. Here, typical problems such as power allocation and channel selection are tackled in detail. Finally, we discuss several decentralized algorithms which allow self-configuring femtocell networks to achieve the equilibrium.

Finally, all possible interference scenarios related to femtocell communications coexisting with one overlay macrocell network are outlined in Figure 1 where (1) refers to FUE-MBS UL interference, (2) refers to MBS- FUE DL interference, (3) refers to FUE-FAP UL interference, (4) refers to FBS-FUE DL interference, (5) refers to FBS-MUE DL interference and finally (6) refers to MUE-FBS UL interference.

1.1 System Model

We assume that there exists a set $N = \{1, \dots, N\}$ of N frequency bands over which a Macrocell Base Station (MBS) can operate. Let $\Gamma_0^{(m)}, m \in M$, denote the minimum time-average SINR offered by MBS m over its corresponding fixed frequency band. Consider now a set $K = \{1, \dots, K\}$ of K femtocells under-laying the M -cell N -frequency band macrocell system. Each femtocell can use

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/game-theory-femtocell-communications/61957

Related Content

Distributed Computation in Wireless Sensor Networks: Efficient Network Architectures and Applications in WSNs

Tejaswini Devanaboyina, Balakrishna Pillalamarriand Rama Murthy Garimella (2015). *International Journal of Wireless Networks and Broadband Technologies* (pp. 14-32).

www.irma-international.org/article/distributed-computation-in-wireless-sensor-networks/154479

Configurable and Scalable Turbo Decoder for 4G Wireless Receivers

Yang Sun, Joseph R. Cavallaro, Yuming Zhuand Manish Goel (2010). *Fourth-Generation Wireless Networks: Applications and Innovations* (pp. 622-643).

www.irma-international.org/chapter/configurable-scalable-turbo-decoder-wireless/40720

Cooperative Communication System Architectures for Cellular Networks

Mischa Dohler, Djamel-Eddine Meddour, Sidi-Mohammed Senouciand Hassnaa Moustafa (2010). *Cooperative Communications for Improved Wireless Network Transmission: Framework for Virtual Antenna Array Applications* (pp. 522-547).

www.irma-international.org/chapter/cooperative-communication-system-architectures-cellular/36562

On the Selection of Optimum Threshold Bound of Body Surface to External Communication in Body Area Network

Sukhraj Kaurand Jyoteesh Malhotra (2018). *International Journal of Wireless Networks and Broadband Technologies* (pp. 15-24).

www.irma-international.org/article/on-the-selection-of-optimum-threshold-bound-of-body-surface-to-external-communication-in-body-area-network/209432

Impact of Frame Duration and Modulation Coding Schemes With WiMAX Bandwidth Asymmetry in Transmission Control Protocol Variants

Kailash Chandra Bandhuand Ashok Bhansali (2019). *International Journal of Wireless Networks and Broadband Technologies* (pp. 35-45).

www.irma-international.org/article/impact-of-frame-duration-and-modulation-coding-schemes-with-wimax-bandwidth-asymmetry-in-transmission-control-protocol-variants/237190