

# Chapter 104

## A State-of-the-Art in Spatio-Temporal Data Warehousing, OLAP and Mining

**Leticia Gómez**

*Instituto Tecnológico de Buenos Aires, Argentina*

**Bart Kuijpers**

*Hasselt University and Transnational University of Limburg, Belgium*

**Bart Moelans**

*Hasselt University and Transnational University of Limburg, Belgium*

**Alejandro Vaisman**

*Universidad de la Republica, Uruguay*

### ABSTRACT

*Geographic Information Systems (GIS) have been extensively used in various application domains, ranging from economical, ecological and demographic analysis, to city and route planning. Nowadays, organizations need sophisticated GIS-based Decision Support System (DSS) to analyze their data with respect to geographic information, represented not only as attribute data, but also in maps. Thus, vendors are increasingly integrating their products, leading to the concept of SOLAP (Spatial OLAP). Also, in the last years, and motivated by the explosive growth in the use of PDA devices, the field of moving object data has been receiving attention from the GIS community, although not much work has been done to provide moving object databases with OLAP capabilities. In the first part of this paper we survey the SOLAP literature. We then address the problem of trajectory analysis, and review recent efforts regarding trajectory data warehousing and mining. We also provide an in-depth comparative study between two proposals: the GeoPKDD project (that makes use of the Hermes system), and Piet, a proposal for SOLAP and moving objects, developed at the University of Buenos Aires, Argentina. Finally, we discuss future directions in the field, including SOLAP analysis over raster data.*

DOI: 10.4018/978-1-4666-2455-9.ch104

## INTRODUCTION

Geographic Information Systems (GIS) have been extensively used in various application domains, ranging from economical, ecological and demographic analysis, to city and route planning (Rigaux, Scholl, & Voisard, 2001; Worboys, 1995). Spatial information in a GIS is typically stored in different so-called *thematic layers* (also called *themes*). Information in themes can be stored in data structures according to different data models, the most usual ones being the *raster model* and the *vector model*. In a thematic layer, spatial data is annotated with classical relational attribute information, of (in general) numeric or string type. While spatial data is stored in data structures suitable for these kinds of data, associated attributes are usually stored in conventional relational databases. Spatial data in the different thematic layers of a GIS system can be mapped univocally to each other using a common frame of reference, like a coordinate system. These layers can be overlapped or overlayed to obtain an integrated spatial view.

On the other hand, OLAP (On Line Analytical Processing) (Kimball, 1996; Kimball & Ross, 2002) comprises a set of tools and algorithms that allow efficiently querying multidimensional databases containing large amounts of data, usually called data warehouses. In OLAP, data is organized as a set of *dimensions* and *fact tables*. In the multidimensional model, data can be perceived as a *data cube*, where each cell contains a measure or set of (probably aggregated) measures of interest. As we discuss later, OLAP dimensions are further organized in hierarchies that favor data aggregation (Cabibbo & Torlone, 1997). Several techniques and algorithms have been developed for multidimensional query processing, most of them involving some kind of aggregate precomputation (Harinarayan, Rajaraman, & Ullman, 1996).

## The need for OLAP in GIS

Different data models have been proposed for representing objects in a GIS. ESRI (<http://www.esri.com>) first introduced the *Coverage* data model to bind geometric objects to non-spatial attributes that describe them. Later, they extended this model with object-oriented support, in a way that behavior can be defined for geographic features (Zeiler, 1999). The idea of the Coverage data model is also supported by the Reference Model proposed by the Open Geospatial Consortium (<http://www.opengeospatial.org>). Thus, in spite of the model of choice, there is always the underlying idea of binding geometric objects to objects or attributes stored in (mostly) object-relational databases (Stonebraker & Moore, 1996). In addition, query tools in commercial GIS allow users to overlap several thematic layers in order to locate objects of interest within an area, like schools or fire stations. For this, they use indexing structures based on R-trees (Gutman, 1984). GIS query support sometimes includes aggregation of geographic measures, for example, distances or areas (e.g., representing different geological zones). However, these aggregations are not the only ones that are required, as we discuss below.

Nowadays, organizations need sophisticated GIS-based Decision Support System (DSS) to analyze their data with respect to geographic information, represented not only as attribute data, but also in maps, probably in different thematic layers. In this sense, OLAP and GIS vendors are increasingly integrating their products (see, for instance, Microstrategy and MapInfo integration in <http://www.microstrategy.com/>, and <http://www.mapinfo.com/>). Thus, aggregate queries are central to DSSs. Classical aggregate OLAP queries (like “Total sales of cars in California”), and aggregation combined with complex queries involving geometric components (“Total sales in all villages crossed by the Mississippi river and within a radius of 100 km around New Orleans”) must be efficiently supported. Moreover, naviga-

34 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/state-art-spatio-temporal-data/73533](http://www.igi-global.com/chapter/state-art-spatio-temporal-data/73533)

## Related Content

---

### Detecting Trends in Social Bookmarking Systems: A del.icio.us Endeavor

Robert Wetzker, Carsten Zimmermann and Christian Bauckhage (2010). *International Journal of Data Warehousing and Mining* (pp. 38-57).

[www.irma-international.org/article/detecting-trends-social-bookmarking-systems/38953](http://www.irma-international.org/article/detecting-trends-social-bookmarking-systems/38953)

### Density-Based Spatial Anomalous Window Discovery

Prerna Mohod and Vandana P. Janeja (2022). *International Journal of Data Warehousing and Mining* (pp. 1-23).

[www.irma-international.org/article/density-based-spatial-anomalous-window-discovery/299015](http://www.irma-international.org/article/density-based-spatial-anomalous-window-discovery/299015)

### A Query Language for Mobility Data Mining

Roberto Trasarti, Fosca Giannotti, Mirco Nanni, Dino Pedreschi and Chiara Renzo (2011). *International Journal of Data Warehousing and Mining* (pp. 24-45).

[www.irma-international.org/article/query-language-mobility-data-mining/49639](http://www.irma-international.org/article/query-language-mobility-data-mining/49639)

### Filter-Wrapper Incremental Algorithms for Finding Reduct in Incomplete Decision Systems When Adding and Deleting an Attribute Set

Nguyen Long Giang, Le Hoang Son, Nguyen Anh Tuan, Tran Thi Ngan, Nguyen Nhu Son and Nguyen Truong Thang (2021). *International Journal of Data Warehousing and Mining* (pp. 39-62).

[www.irma-international.org/article/filter-wrapper-incremental-algorithms-for-finding-reduct-in-incomplete-decision-systems-when-adding-and-deleting-an-attribute-set/276764](http://www.irma-international.org/article/filter-wrapper-incremental-algorithms-for-finding-reduct-in-incomplete-decision-systems-when-adding-and-deleting-an-attribute-set/276764)

### Object-Oriented Features in Oracle

Johanna Wenny Rahayu, David Tanier and Eric Pardede (2006). *Object-Oriented Oracle* (pp. 31-50).

[www.irma-international.org/chapter/object-oriented-features-oracle/27337](http://www.irma-international.org/chapter/object-oriented-features-oracle/27337)