Chapter 16 Quantum Dot Solar Cells

Yoshitaka Okada The University of Tokyo, Japan

Katsuhisa Yoshida The University of Tokyo, Japan

Yasushi Shoji University of Tsukuba, Japan

ABSTRACT

Advanced concepts for high efficiency solar cells such as hot carrier effects, Multi-Exciton Generation (MEG), and Intermediate-Band (IB) absorption in low-dimensional nanostructures are under focused research topics in recent years. Among various potential approaches, this chapter is devoted to the device physics and development of the state-of-the-art technologies for quantum dot-based IB solar cells.

INTRODUCTION

By avoiding all the nonradiative recombination processes within the solar cell, the theoretical maximum efficiency to a thermodynamic upper limit becomes ~ 85% for a fully concentrated black-body radiation of 5,800K (Green, 2003; Würfel, 2009). On the other, the maximum efficiency of a single-junction solar cell is limited to the Shockley-Queisser (1961) limit of ~ 31% for AM1.5 spectrum. The main physical processes that limit the efficiency of a solar cell are the losses by thermal dissipation or thermalization, and nonabsorption of low-energy below-bandgap photons. Thus improving the efficiency means developing the methods to reduce these losses. One of the concepts is to split the solar spectrum among multiple bandgap absorbers or sub-cells, e.g. tandem or multijunction cells. The others employ more advanced techniques such as hot carrier effects, Multi-Exciton Generation (MEG), and Intermediate-Band (IB) absorption in low-dimensional nanostructures such as semiconductor quantum dots (Nozik, 2002, 2008; Green, 2003; Luque, 1997). Among various approaches available, this Chapter is devoted to the device physics and development of the state-of-the-art technologies for quantum dot-based IB solar cells.

Quantum Dot (QD) superlattice incorporated in the active region of a *p-i-n* single-junction solar cell has attracted significant interest as a potential means of utilizing the sub-bandgap infra-red photons to generate additional photocurrents, through absorption via superlattice miniband states, beyond that corresponding to the valenceto-conduction band transitions (Luque, 1997). The QDs also offer the possibility for reducing thermal dissipation loss. If such a nanostructure solar cell were realized, the conversion efficiency could not only exceed the Shockley-Queisser (1961) limit of a conventional single-junction solar cell, which is ~ 31% for AM1.5 spectrum, but further provides a pathway to increase the efficiency up to the thermodynamic limit of $> \sim 60\%$ under full concentration.

In a QD solar cell, QDs are required to be homogeneous and small in size, and are regularly and tightly placed in all three dimensions. This configuration then leads to formation of an Intermediate-Band(IB) or a superlattice miniband that is well separated in energy from the higherorder states (Tomić, 2008). Secondly, IB states should ideally be half-filled with electrons in order to ensure an efficient pumping of electrons by providing both the empty states to receive electrons being photo-excited from the Valence Band (VB), and filled states to promote electrons to the Conduction Band (CB) via absorption of second sub-bandgap photons (Martí, 2001). This implies that its own quasi-Fermi level is defined within IB, as schematically shown in Figure 1.

Proposed implementation of QD-IB solar cells must accompany two-step carrier generation via IB states and it has been difficult to clearly verify this concept at room temperature. The demonstration of OD-IB solar cells is presently undergoing two research stages. The first is to develop the technologies to realize a high-density QD array or superlattice of low defect density, which is placed in the central active region of the cell. The fabrication of QD arrays is most commonly achieved by taking advantage of spontaneous self-assembly of coherent three-dimensional (3D) islands in lattice-mismatched epitaxy long known as Stranski-Krastanov (S-K) growth in Molecular Beam Epitaxy (MBE). However, the number of QDs is severely limited by the lattice strain accumulation in the crystalline material as the

Figure 1. Schematic energy band diagram of QD-IB solar cell shown with possible photo-absorption processes involved. The energy bandgap of host material and quasi-Fermi level of IB are given by E_{g} *and* E_{IP} *respectively.*



22 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/quantum-dot-solar-cells/102022

Related Content

Machine Learning Applications in Nanomedicine and Nanotoxicology: An Overview

Gerardo M. Casañola-Martinand Hai Pham-The (2019). *International Journal of Applied Nanotechnology Research (pp. 1-7).*

www.irma-international.org/article/machine-learning-applications-in-nanomedicine-and-nanotoxicology/241273

Electrophoretical Deposition of Nanotube TiO2 Conglomerates Detached During Ti Anodizing Used for Decomposing Methyl Orange in Water

C. Y. Torres López, J. J. Pérez Bueno, I. Zamudio Torres, M. L. Mendoza-López, J. E. Urbina Álvarezand A. Hurtado Macías (2015). *Handbook of Research on Diverse Applications of Nanotechnology in Biomedicine, Chemistry, and Engineering (pp. 477-495).*

www.irma-international.org/chapter/electrophoretical-deposition-of-nanotube-tio2-conglomerates-detached-during-tianodizing-used-for-decomposing-methyl-orange-in-water/116859

Robust Computation through Percolation: Synthesizing Logic with Percolation in Nanoscale Lattices

Mustafa Altunand Marc D. Riedel (2011). International Journal of Nanotechnology and Molecular Computation (pp. 12-30).

www.irma-international.org/article/robust-computation-through-percolation/66395

Quantum Computation Perspectives in Medical Image Processing

Pedro Rodrigues, Manuel João Ferreiraand João Luís Monteiro (2010). International Journal of Nanotechnology and Molecular Computation (pp. 16-46).

www.irma-international.org/article/quantum-computation-perspectives-medical-image/48527

Nanopriming-Based Management of Biotic Stresses for Sustainable Agriculture

Muhammad Majeed, Murad Muhammad, Tanveer Hussain, Muqarrab Ali, Tayyaba Naz, Sehar Nawaz, Muhammad Mazhar Iqbaland Ghulam Abbas (2023). *Nanopriming Approach to Sustainable Agriculture (pp. 263-289).*

www.irma-international.org/chapter/nanopriming-based-management-of-biotic-stresses-for-sustainableagriculture/328184