Chapter 21 Linguistic Multi-Attribute Decision Making with a Prioritization Relationship

Cuiping Wei Yangzhou University, China

Xijin Tang CAS Academy of Mathematics and Systems Science, China

> Xiaojie Wang Qufu Normal University, China

ABSTRACT

In this paper we consider linguistic information aggregation problems where a prioritization relationship exists over attributes. The authors define a prioritized 2-tuple ordered weighted averaging (PTOWA) operator to aggregate satisfactions of alternatives under attributes with a linear prioritized ordering. The authors then use the PTOWA and a TOWA operator to aggregate linguistic information where attributes are partitioned into some categories of which prioritization between categories exists. Finally, two illustrative examples are employed to show the feasibility of the proposed method.

1. INTRODUCTION

Due to the complexity and uncertainty of the objective world, as well as the fuzziness of the human mind, some attributes are more suitable to be evaluated in the form of language (Herrera & Verdegay, 1993; Herrera & Herrera-Viedma, 1997; Torra, 1997; Herrera & Martínez, 2000; Herrera & Martínez, 2001; Xu, 2007; Wei, Feng & Zhang, 2009). For example, when evaluating the comprehensive qualities of the students or

the performance of cars, the decision makers prefer to use "excellent," "good" and "poor" for judgment. For linguistic information aggregation, various linguistic aggregation operators have been proposed, including linguistic OWA operator (Herrera & Verdegay, 1993), induced-linguistic OWA operator (Herrera & Herrera-Viedma, 1997), linguistic WOWA operator (Torra, 1997), etc. In the aggregation process using these operators, the results do not exactly match any of the initial linguistic terms. Therefore, an approximation

DOI: 10.4018/978-1-4666-6042-7.ch021

process is developed to express the results in the initial expression domain, but leads to the loss of information and lack of precision. Herrera and Martínez (2000) presented an analytical method based upon 2-tuple for linguistic aggregation. They proposed both 2-tuple weighted average (TWA) operator and 2-tuple ordered weighted averaging (TOWA) operator (Herrera & Martínez, 2000), and then successfully applied the TOWA operator to multigranular hierarchical linguistic contexts in a multi-expert decision making problem (Herrera & Martínez, 2001). Many achievements have been taken in multi-attribute decision making (MADM) with these linguistic aggregation operators.

It is important to see that the above linguistic aggregation operators have the ability to trade off between attributes. While in some situations where a prioritization relationship over the attributes exists, we do not expect this kind of compensation. Yager (2004) studied this kind of problem where decision information is described by real numbers. He pointed out that the importance weights of lower priority attributes were based on the satisfaction of alternative to the higher priority attributes. Based on this idea, Yager proposed the prioritized average (PA) operator (Yager, 2008) and the prioritized ordered weighted averaging (POWA) operator (Yager, 2009). Later Wei and Tang (2012) proposed two averaging operators, a generalized PA operator and a generalized POWA operator. In the case with one attribute in each priority category, both operators reduce to the PA operator and the POWA operator proposed by Yager.

Motivated by the above-mentioned studies, we consider linguistic aggregation problems where a prioritization relationship exists over the attributes. This paper is structured as follows. In Section 2, we make a brief review of 2-tuple and its related operators. In Section 3, we propose a prioritized 2-tuple ordered weighted averaging (PTOWA) operator and discuss its properties. We then use this operator and a TOWA operator to aggregate satisfactions of attributes by alternatives. The paper is concluded in Section 4.

2. 2-TUPLE LINGUISTIC REPRESENTATION MODEL AND TOWA OPERATORS

For MADM problems with some qualitative attributes, we need to use a linguistic term set to describe the decision information. Herrera and Martínez (2000) introduced a finite and totally ordered discrete linguistic term set: $S = \{s_{\alpha} | \alpha = 0, 1, \dots, \tau\}$, whose cardinality value is odd. For example, a set of seven linguistic terms *s* could be:

$$S = \begin{cases} s_0 = \text{extremely poor, } s_1 = \text{very poor,} \\ s_2 = \text{poor, } s_3 = \text{fair, } s_4 = \text{good,} \\ s_5 = \text{very good, } s_6 = \text{extremely good} \end{cases}$$

Furthermore, Herrera defined 2-tuple to aggregate linguistic information:

Definition 1: (Herrera & Martínez, 2001) Let $S = \{s_0, s_1, \dots, s_{\tau}\}$ be a linguistic term set, then the 2-tuple can be obtained by the translation function θ :

$$\theta: S \to S \times \left[-0.5, 0.5\right), \theta\left(s_{i}\right) = \left(s_{i}, 0\right), \text{for any } s_{i} \in S$$

$$\tag{1}$$

Definition 2: (Herrera & Martínez, 2001) Let $S = \{s_0, s_1, \dots, s_{\tau}\}$ be a linguistic term set, $s_i = S$ and $\beta \in [0, \tau]$, a value representing the result of a symbolic aggregation operation, then the 2-tuple can be obtained with the following function:

$$\Delta : [0, \tau] \to S \times [-0.5, 0.5),$$

$$\Delta (\beta) = (s_i, \alpha) = \begin{cases} s_i, i = round(\beta) \\ \alpha = \beta - i, i \in [-0.5, 0.5) \end{cases}$$
(2)

where round (\bullet) is the usual round operation.

6 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/linguistic-multi-attribute-decision-making-with-a-

prioritization-relationship/108733

Related Content

Adaptive Digital Filtering and Its Algorithms for Acoustic Echo Canceling

Mohammad Reza Asharifand Rui Chen (2007). Advances in Audio and Speech Signal Processing: Technologies and Applications (pp. 225-285). www.irma-international.org/chapter/adaptive-digital-filtering-its-algorithms/4688

An Overview and Technological Background of Semantic Technologies

Reinaldo Padilha França, Ana Carolina Borges Monteiro, Rangel Arthurand Yuzo Iano (2021). *Advanced Concepts, Methods, and Applications in Semantic Computing (pp. 1-21).* www.irma-international.org/chapter/an-overview-and-technological-background-of-semantic-technologies/271118

Systematic Review of Speech Generating Devices for Aphasia

Rajinder Koul, Diana Petroiand Ralf Schlosser (2010). *Computer Synthesized Speech Technologies: Tools for Aiding Impairment (pp. 148-160).* www.irma-international.org/chapter/systematic-review-speech-generating-devices/40863

Finding the Semantic Relationship Between Wikipedia Articles Based on a Useful Entry Relationship

Lin-Chih Chen (2020). Natural Language Processing: Concepts, Methodologies, Tools, and Applications (pp. 838-859).

www.irma-international.org/chapter/finding-the-semantic-relationship-between-wikipedia-articles-based-on-a-usefulentry-relationship/239969

Newness and Givenness of Information : Automated Identification in Written Discourse

Philip M. McCarthy, David Dufty, Christian F. Hempelmann, Zhiqiang Cai, Danielle S. McNamaraand Arthur C. Graesser (2012). *Applied Natural Language Processing: Identification, Investigation and Resolution (pp. 457-478).*

www.irma-international.org/chapter/newness-givenness-information/61065