

Assistive Navigation Systems for the Visually Impaired

A

Kai Li Lim

Sunway University, Malaysia

Lee Seng Yeong

Sunway University, Malaysia

Kah Phooi Seng

Edith Cowan University, Australia

Li-Minn Ang

Edith Cowan University, Australia

INTRODUCTION

Navigation systems consist of three main components, 1. positioning and tracking, 2. pathfinding, and 3. guidance. (See Figure 1)


The positioning and tracking block determines the position of the user through the use of triangulation or trilateration techniques and tracking is achieved by continuously updating the position of the user. Locating is similar to positioning except that it does not include information on the orientation and direction of the user. This becomes important when working indoors whereby most systems provide location detection rather than the position. The pathfinding block determines routes from between two locations optimised based on traveling time, cost and/or distance. Once the path is

determined, the guidance block provides guidance such as turn-by-turn instructions to the user. More advanced systems can determine in real-time the surrounding conditions and guide the user around obstacles.

The most commonly known navigation system currently in use is based on the Global Positioning System (GPS), which rely on a constellation of satellites orbiting Earth for trilateration based positioning. These systems typically provide audio-visual based guidance for the user to traverse the path. Such guidance is not well suited for the visually impaired whose guidance is primarily in the form of audio and tactile feedback (touch).

The next section will describe the technologies commonly used in components of the navigation system used for the visually impaired. Next, the article

Figure 1. General components of a navigation system



DOI: 10.4018/978-1-4666-5888-2.ch030

describe what assistive technologies are available for the visually impaired and compares five different assistive navigation systems for the visually impaired (ANSVI). Then, this article discusses about pathfinding, and reviews two more pathfinding-focused systems. Finally, future research directions are presented before this article concludes.

BACKGROUND

This section will describe technologies and methods that are commonly used in each of the three navigation system components for ANSVI.

Positioning and Tracking

There are three common methods for positioning (or locating) in ANSVI,

1. Global Positioning System (GPS)

The GPS is a satellite based positioning system that while it works well outdoors (to an accuracy of $\pm 3\text{m}$), does poorly indoors or not at all. This is due to the signals from the satellite not being able to penetrate buildings. One method of overcoming this is to use in-door GPS repeaters. However, these are an additional cost

2. Radio Signal Strength Indicator (RSSI)

The RSSI is a measurement of power present in a received radio signal and it is this signal strength that is used to estimate the user's location. One common source of RSSI data is the 802.11 protocols. Locations with large-scale deployments of wireless access points can benefit from the ease of using the RSSI method for positioning. While this method is highly suited for use indoors, it is inaccurate as the RSSI is highly dependent on factors such as the antenna gain patterns and polarisations, multipath fading and interference from devices in the same frequency. More recent advances in using RSSI is to implement it on a micro-location basis such as those implemented by Bluetooth Low Energy (BLE) beacons.

3. Radio Frequency Identification Devices (RFID)

This method relies on a network of RFID tags or transponders in the area where the user's location is to be determined, forming a grid of checkpoint markers. It is an absolute locating method and the location is determined based on which checkpoint is activated. Accuracy of such systems are dependent on the density of the grid and the sensitivity/range of the transponders. To increase the location detection accuracy:

- A more tightly coupled grid can be used, but the cost will increase
- Transponders with a smaller area of detection can be used, but the person must be standing very close to the transponder. This can be overcome by having a more tightly coupled grid but same cost trade-off applies.

Pathfinding

Pathfinding is the process of finding the optimal route (in terms of distance, time to travel etc.) between two points. Pathfinding can be classified into:

1. Informed (Directed)

In this search, the general direction of the destination from the current position is known. The search is then weighted towards that direction.

2. Uninformed (Undirected)

Unlike the informed search, the direction of the destination is unknown from the current position. This leads to an exhaustive search from the current position until the destination is found.

Algorithms such as the A* search algorithm (Hart, Nilsson, & Raphael, 1968) and the Dijkstra's shortest path algorithm (Dijkstra, 1959) are often used interchangeably in situations, depending on the requirements that the current situation holds, as both algorithms, along with other unmentioned algorithms are made to cater for different pathfinding scenarios.

11 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/assistive-navigation-systems-for-the-visually-impaired/112340

Related Content

Resource Allocation in OFDMA as an Optimization Problem

Álvaro Pachón, Ubaldo García-Palomares and Juan Manuel Madrid (2015). *Encyclopedia of Information Science and Technology, Third Edition* (pp. 5730-5740).

www.irma-international.org/chapter/resource-allocation-in-ofdma-as-an-optimization-problem/113028

Gender Differences in ICT Studies: A Study of Selected Public Secondary Schools in Ogun State, Nigeria

Tayo O. George, Anthony C. Onwumah, Michael O. Fagbohun, Mercy E. Adebayo and Olawale Yinusa Olonade (2019). *Gender Gaps and the Social Inclusion Movement in ICT* (pp. 147-169).

www.irma-international.org/chapter/gender-differences-in-ict-studies/218443

A Work System Front End for Object-Oriented Analysis and Design

Steven Alter and Narasimha Bolloju (2016). *International Journal of Information Technologies and Systems Approach* (pp. 1-18).

www.irma-international.org/article/a-work-system-front-end-for-object-oriented-analysis-and-design/144304

Fuzzy Decision Support System for Coronary Artery Disease Diagnosis Based on Rough Set Theory

Noor Akhmad Setiawan (2014). *International Journal of Rough Sets and Data Analysis* (pp. 65-80).

www.irma-international.org/article/fuzzy-decision-support-system-for-coronary-artery-disease-diagnosis-based-on-rough-set-theory/111313

Hybrid TRS-FA Clustering Approach for Web2.0 Social Tagging System

Hannah Inbarani Hand Selva Kumar S (2015). *International Journal of Rough Sets and Data Analysis* (pp. 70-87).

www.irma-international.org/article/hybrid-trs-fa-clustering-approach-for-web20-social-tagging-system/122780