

Chapter 12

Image Segmentation Based on Bio-Inspired Optimization Algorithms

Hongwei Mo

Harbin Engineering University, China

Lifang Xu

Harbin Engineering University, China

Mengjiao Geng

Harbin Engineering University, China

ABSTRACT

This chapter addresses the issue of image segmentation by clustering in the domain of image processing. Fuzzy C-Means is a widely adopted clustering algorithm. Bio-inspired optimization algorithms are optimal methods inspired by the principles or behaviors of biology. For the purpose of reinforcing the global search capability of FCM, five Bio-Inspired Optimization Algorithms (BIOA) including Biogeography-Based Optimization (BBO), Artificial Fish School Algorithm (AFSA), Artificial Bees Colony (ABC), Particle Swarm Optimization (PSO), and Bacterial Foraging Algorithm (BFA) are used to optimize the objective criterion function, which is interrelated to centroids in FCM. The optimized FCMs by the five algorithms are used for image segmentation, respectively. They have different effects on the results.

INTRODUCTION

Image segmentation is one of the central problems in computer vision and pattern recognition. It refers to the process of assigning a label to every pixel in an image such that pixels with the same label share certain visual characteristics. The result of image segmentation is a set of segments (sets of

pixels) that collectively cover the entire image. Pixels in the same region are similar with respect to some characteristics or computed properties, such as color, intensity, and texture. Adjacent regions are significantly different with respect to the same characteristics. The goal of segmentation is to simplify and/or change the representation of

DOI: 10.4018/978-1-4666-6328-2.ch012

an image into something that is more meaningful and easier to analyze (Shapiro & Stockman, 2001).

There are many general-purpose approaches available for image segmentation such as threshold methods (Mardia & Hainsworth, 1988), edge-based methods (Perona & Malik, 1990), region-based methods (Hijjatoleslami & Kitter, 1998), and graph-based methods (Felzenszwalb & Huttenlocher, 2004). In contrast to the heuristic nature of these methods, one would formalize an objective criterion for evaluating a given segmentation. This would allow us to formulate the segmentation problem as an optimization problem. The objective function that one would seek to optimize is the interclass variance that is used in cluster analysis. An optimizer can lead to efficient solutions for optimal segmentation. But the objective function is usually not a monotone chain, therefore the problem is general NP-hard. Following this way, some clustering methods have been applied to solve image segmentation problems.

Clustering techniques represent the non-supervised pattern classification in groups (Jain et al., 1999). Considering the image context, the clusters correspond to some semantic meaning in the image, which is, objects. Among the many methods for data analysis through clustering and unsupervised image segmentation is: Nearest Neighbor Clustering, Fuzzy C-Means (FCM) clustering and Artificial Neural Networks for Clustering (Jain et al., 1999). Such bio and social-inspired methods try to solve the related problems using knowledge found in the way nature solves problems. Social inspired approaches intend to solve problems considering that an initial and previously defined weak solution can lead the whole population to find a better or a best so far solution.

Among them, the most successful image segmentation algorithm into homogeneous regions is fuzzy c-means algorithm (Bezdek, 1981). There are a lot of visual applications reporting the use of fuzzy c-means, e.g. in medical image analysis, soil structure analysis, satellite imagery (Felzen-

szwalb & Huttenlocher, 2004; Hijjatoleslami & Kitter, 1998; Mardia & Hainsworth, 1988; Perona & Malik, 1990). Many variations of approaches have been introduced over last 20 years, and image segmentation remains an open-solution problem. As global optimization techniques, evolutionary algorithms (EAs) are likely to be good tools for image segmentation task. In the past two decades, EAs have been applied to image segmentation with promising results (Andrey, 1999; Bhandarkar & Zhang, 1999; Bhanu et al., 1995; Gong et al., 2008; Koppen et al., 2003; Maulik, 2009; Melkemi et al., 2006; Veenman et al., 2003). These algorithms exploited the metaphor of natural evolution in the context of image segmentation.

The original FCM algorithm, due to its drawbacks such as poor ability of global searching, easy sticking at local optimal solution, is often improved by combining with other optimal algorithm and then used in image segmentation. In this paper, we adopt five bio-inspired optimization algorithms to search the center of cluster for FCM. The paper is organized as follows. At first, the FCM and image segmentation are introduced respectively. Second, BBO, AFSA, ABC, PSO and BFOA are introduced. Third, the hybrid clustering methods of the five BIOAs and FCM are tested on some standard images from the USC-SIPI Image Database and the simulation results are analyzed. At last, the conclusions are drawn.

BACKGROUND

Recently there has been an increase in the presence of bio-inspired optimization algorithms (BIOA) of image segmentation. Most of them focus on searching the right center of cluster for FCM. Yang et al. (2007) proposed a FCM based on Ant Colony Algorithm. Tian et al. (2008) applied the FCM optimized by PSO to segment SAR images and its experimental results on the MSTAR dataset had demonstrated that the proposed method was capable of effectively segmenting SAR images

24 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/image-segmentation-based-on-bio-inspired-optimization-algorithms/115308

Related Content

Metaheuristic Search with Inequalities and Target Objectives for Mixed Binary Optimization Part I: Exploiting Proximity

Fred Glover and Saïd Hanafi (2010). *International Journal of Applied Metaheuristic Computing* (pp. 1-15). www.irma-international.org/article/metaheuristic-search-inequalities-target-objectives/40905

Decision Support for Mental Health: Towards the Information-based Psychiatry

Jan Kalina and Jana Zvárová (2014). *International Journal of Computational Models and Algorithms in Medicine* (pp. 53-65). www.irma-international.org/article/decision-support-for-mental-health/148348

Optimization of Small Wind Turbines using Genetic Algorithms

Mohammad Hamdan and Mohammad Hassan Abderrazzaq (2016). *International Journal of Applied Metaheuristic Computing* (pp. 50-65). www.irma-international.org/article/optimization-of-small-wind-turbines-using-genetic-algorithms/165027

Feature Selection for Designing a Novel Differential Evolution Trained Radial Basis Function Network for Classification

Sanjeev Kumar Dash, Aditya Prakash Dash, Satchidananda Dehuri and Sung-Bae Cho (2013). *International Journal of Applied Metaheuristic Computing* (pp. 32-49). www.irma-international.org/article/feature-selection-designing-novel-differential/77298

Vector Evaluated and Objective Switching Approaches of Artificial Bee Colony Algorithm (ABC) for Multi-Objective Design Optimization of Composite Plate Structures

S. N. Omkar, G. Narayana Naik, Kiran Patil and Mrunmaya Mudigere (2013). *Trends in Developing Metaheuristics, Algorithms, and Optimization Approaches* (pp. 59-84). www.irma-international.org/chapter/vector-evaluated-objective-switching-approaches/69718