Chapter 7 Data Visualization Using Weighted Voronoi Diagrams

Raghuveer Devulapalli University of Minnesota, USA

Neil Peterson University of Minnesota, USA

John Gunnar Carlsson University of Southern California, USA

ABSTRACT

A Voronoi diagram is a standard spatial tessellation that partitions a domain into sub-regions based on proximity to a fixed set of landmark points. In order to maintain control over the size and shape of these sub-regions, a weighting scheme is often used, in which each landmark has a scalar value associated with it. This suggests a natural "inverse" problem: given a fixed set of landmark points in a given planar region and a set of "desired" areas, is it possible to calculate a set of weights so that each sub-region has a particular area? In this chapter, the authors give a fast scheme for determining these weights based on theory from convex optimization, which is then applied to a variety of problems in data visualization.

INTRODUCTION

A Voronoi diagram of a planar region \mathcal{R} and a set of points $\mathcal{P} = \{p_1, ..., p_n\} \subset \mathcal{R}$ is a tessellation of \mathcal{R} into n sub-regions $\{R_1, ..., R_n\}$ based on proximity to the

DOI: 10.4018/978-1-4666-8465-2.ch007

Copyright ©2015, IGI Global. Copying or distributing in print or electronic forms without written permission of IGI Global is prohibited.

nearest point in \mathcal{P} :

$$R_{i} := \left\{ x \in \mathcal{R} : \parallel x - p_{i} \parallel \leq \parallel x - p_{j} \parallel \forall j \right\}.$$

The norm $\|\cdot\|$ in the above expression is usually Euclidean, but may also be taken under the L^1 or L^{∞} norm, for example (Lee & Wong, 1980). Voronoi diagrams are widely applied in many different domains, such as data compression, facility location, robotics, and air traffic control, to name a few. Indeed, such structures are useful and intuitive for modelling many different kinds of spatial interactions: for example, if the points represent stores that are otherwise identical, then the Voronoi diagram describes the market regions for those stores, inasmuch as customers will prefer whichever store is closest to them. Voronoi diagrams are also of fundamental importance in classification: if the points represent reference data such as documents or images, then the Voronoi diagram describes the set of all "query" data that are most closely associated with a particular reference point. Figure 1a shows an example of a Voronoi diagram.

Voronoi diagrams have been generalized in a number of ways by introducing a *weight vector* $\mathbf{w} = \{w_1, \dots, w_n\}$ associated with the landmark points (Aurenhammer et al., 2013; Okabe et al., 2009); the tessellation $\{R_1, \dots, R_n\}$ then depends on these weights as well. The authors per this chapter consider three weighting schemes:

• In an additively weighted Voronoi diagram, the tessellation satisfies

$$R_{_{i}} \coloneqq \Big\{ x \in \mathcal{R} : \parallel x - p_{_{i}} \parallel -w_{_{i}} \leq \parallel x - p_{_{j}} \parallel -w_{_{j}} \forall j \Big\};$$

it can be shown that the boundaries between sub-regions are always hyperbolic arcs and that all sub-regions are connected.

• In a *multiplicatively weighted Voronoi diagram*, the tessellation satisfies

$$R_{i} := \left\{ x \in \mathcal{R} : \frac{\parallel x - p_{i} \parallel}{w_{i}} \leq \frac{\parallel x - p_{j} \parallel}{w_{j}} \forall j \right\};$$

it can be shown that the boundaries between sub-regions are always circular arcs.

22 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igiglobal.com/chapter/data-visualization-using-weightedvoronoi-diagrams/136104

Related Content

Spatial Modeling of Natural Phenomena and Events with Artificial Neural Networks and GIS

Silke Noack, Andreas Barth, Alexey Irkhin, Evelyn Bennewitzand Frank Schmidt (2013). *Geographic Information Systems: Concepts, Methodologies, Tools, and Applications (pp. 765-782).*

www.irma-international.org/chapter/spatial-modeling-natural-phenomena-events/70475

Research in Agricultural and Environmental Information Systems

François Pinetand Petraq Papajorgji (2019). *Geospatial Intelligence: Concepts, Methodologies, Tools, and Applications (pp. 1456-1477).* www.irma-international.org/chapter/research-in-agricultural-and-environmental-informationsystems/222956

Adopting BIM Standards for Managing Vision 2030 Infrastructure Development in Qatar

Fatima Al Mohannadi, Mohammed Arif, Zeeshan Azizand Phillip A. Richardson (2013). *International Journal of 3-D Information Modeling (pp. 64-73).* www.irma-international.org/article/adopting-bim-standards-for-managing-vision-2030-infrastructure-development-in-qatar/99618

The Digital Geography Lab at Salem State University: The Evolution of One of the Oldest Educational Digital Geospatial Labs

Kym Pappathanasiand Stephen S. Young (2012). *International Journal of Applied Geospatial Research (pp. 86-96).* www.irma-international.org/article/digital-geography-lab-salem-state/68858

Critical Incident Management and Geographically-Based Systems

David W. Webband David R. Hoffpauir (2010). *International Journal of Applied Geospatial Research (pp. 69-75).*

www.irma-international.org/article/critical-incident-management-geographically-based/45131