

# Chapter 4

## Some Properties on the Capability of Associative Memory for Higher Order Neural Networks

**Hiromi Miyajima**  
Kagoshima University, Japan

**Noritaka Shigei**  
Kagoshima University, Japan

**Shuji Yatsuki**  
Yatsuki Information System, Inc., Japan

**Hirofumi Miyajima**  
Kagoshima University, Japan

### ABSTRACT

*Higher order neural networks (HONNs) have been proposed as new systems. In this paper, we show some theoretical results of associative capability of HONNs. As one of them, memory capacity of HONNs is much larger than one of the conventional neural networks. Further, we show some theoretical results on homogeneous higher order neural networks (HHONNs), in which each neuron has identical weights. HHONNs can realize shift-invariant associative memory, that is, HHONNs can associate not only a memorized pattern but also its shifted ones.*

### 1. INTRODUCTION

Numerous advances have been made in developing some intelligent systems inspired by biological neural networks (Rumelhart, McClelland, & the PDP Research Group, 1986; Hertz, Krogh, & Palmer 1991; Kasabov, 1996; Mehrotra, Mohan, & Ranka, 1997; Gupta, Jin, & Homma, 2003). Scientific studies have been done with designing artificial neural networks to solve a variety of problems in pattern recognition, prediction, optimization, associative memory, and control (Hopfield, & Tnak, 1985; Reid, Spirkovska, & Ochoa, 1989; Meir, & Domany, 1987; Gupta, Jin, & Homma, 2003). Associative memory is one of the well-studied applications of neural networks. Numerous associative memory models processing static and sequential patterns have been studied such as auto, mutual and multidirectional associative memory (Amari, & Maginu, 1988; McEliece, Posner, Rodemich, & Venkatesh, 1987; Yanai, & Sawada,

DOI: 10.4018/978-1-5225-0788-8.ch004

1990; Amari, 1990; Okada, 1996; Oda, & Miyajima, 2001; Amit, Gutfreund, & Sompolinsky, 1985; Kohonen, 1972; Kosko, 1987; Yoshizawa, Morita, & Amari, 1993; Morita, 1996; Abbott, & Arian, 1987; Amari, & Yanai, H., 1993; Hattori, & Hagiwara, 1995). However, it is known that the capability of the conventional associative memory using neural networks is not so high. Therefore, many associative memory models are proposed such as HONNs, in which the potential of a neuron is represented as the weighted sum of products of input variables, and have been applied to associative memory. It has been shown that HONNs have higher associative capability than the conventional neural networks, in which the potential of a neuron is represented as the weighted sum of input variables (Chan, & Michael, 1988; Reid, Spirkovska, & Ochoa, 1989; Abbott, & Arian, 1987; Cheung, & Lee, 1993; Miyajima, Shigei, & Yatsuki, 2012). However, there are little theoretical studies for the reason why HONNs are effective and the capability of HONNs. Further, from the practical points of view, associative memory should be invariant to pattern transformation such as shift, scaling and rotation. However, the conventional neural networks, cannot inherently acquire any transformation invariant property. Therefore, the conventional neural networks require pre-processing of input patterns to support transformed patterns; a transformed pattern is converted into a standard one, and then the standard pattern is inputted to the network. In order that neural networks inherently acquire shift-invariant properties, their structure should be homogeneous like cellular automata (Wolfram, 1984). Then, how many patterns can HONNs memorize and how about HHONNs?

In this paper, the authors show the basic results about them. As for the conventional neural networks, theoretical results have been shown in (Amari, & Maginu, 1988; McEliece, Posner, Rodemich, & Venkatesh, 1987; and Yanai, & Sawada, 1990). The authors generalize their results and analyze memory capacity of HONNs. As one of them, memory capacity of HONNs is much larger than one of the conventional neural networks. Further, the authors show some theoretical results on homogeneous higher order neural networks (HHONNs), in which each neuron has identical weights. HHONNs can realize essentially shift-invariant associative memory, that is, without any pre-processing of input patterns HHONNs can associate not only a memorized pattern but also its shifted ones (Miyajima, Shigei, & Yatsuki, 2005). HHONNs need  $k \geq 2$  for associative memory. The transition property of HHONNs is analyzed by the statistical method. The authors show the probability that each neuron outputs correctly, and the error-correcting capability. Lastly, the relation between this chapter and other studies and the future works are discussed.

## **2. HIGHER ORDER NEURONS**

Let us explain the conventional neuron. Let  $I_i = \{1, \dots, i\}$  for a positive integer  $i$ . The output  $y$  for each neuron is given by

$$u = \sum_{j=0}^n w_j x_j \tag{1}$$

$$y = f(u), \tag{2}$$

28 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/some-properties-on-the-capability-of-associative-memory-for-higher-order-neural-networks/161023](http://www.igi-global.com/chapter/some-properties-on-the-capability-of-associative-memory-for-higher-order-neural-networks/161023)

## Related Content

---

### Heuristics for the Periodic Mobile Piston Pump Unit Routing Problem

Marcos R. Q. Andrade, Luiz S. Ochiand Simone L. Martins (2015). *International Journal of Natural Computing Research* (pp. 1-25).

[www.irma-international.org/article/heuristics-for-the-periodic-mobile-piston-pump-unit-routing-problem/124878](http://www.irma-international.org/article/heuristics-for-the-periodic-mobile-piston-pump-unit-routing-problem/124878)

### Applications of JGA to Operations Management and Vehicle Routing

A. L. Medaglia (2007). *Handbook of Research on Nature-Inspired Computing for Economics and Management* (pp. 625-641).

[www.irma-international.org/chapter/applications-jga-operations-management-vehicle/21156](http://www.irma-international.org/chapter/applications-jga-operations-management-vehicle/21156)

### Modification of Happiness Expression in Face Images

Dao Nam Anhand Trinh Minh Duc (2017). *International Journal of Natural Computing Research* (pp. 58-69).

[www.irma-international.org/article/modification-of-happiness-expression-in-face-images/198501](http://www.irma-international.org/article/modification-of-happiness-expression-in-face-images/198501)

### Multi-Objective Evolutionary Algorithm NSGA-II for Variables Selection in Multivariate Calibration Problems

Daniel Vitor de Lucena, Telma Woerle de Lima, Anderson da Silva Soaresand Clarimar José Coelho (2012). *International Journal of Natural Computing Research* (pp. 43-58).

[www.irma-international.org/article/multi-objective-evolutionary-algorithm-nsga-ii-for-variables-selection-in-multivariate-calibration-problems/93623](http://www.irma-international.org/article/multi-objective-evolutionary-algorithm-nsga-ii-for-variables-selection-in-multivariate-calibration-problems/93623)

### Ultra High Frequency Polynomial and Trigonometric Higher Order Neural Networks for Control Signal Generator

Ming Zhang (2017). *Nature-Inspired Computing: Concepts, Methodologies, Tools, and Applications* (pp. 648-681).

[www.irma-international.org/chapter/ultra-high-frequency-polynomial-and-trigonometric-higher-order-neural-networks-for-control-signal-generator/161047](http://www.irma-international.org/chapter/ultra-high-frequency-polynomial-and-trigonometric-higher-order-neural-networks-for-control-signal-generator/161047)