

Chapter 4

Some Properties on the Capability of Associative Memory for Higher Order Neural Networks

Hiromi Miyajima
Kagoshima University, Japan

Noritaka Shigei
Kagoshima University, Japan

Shuji Yatsuki
Yatsuki Information System, Inc., Japan

Hirofumi Miyajima
Kagoshima University, Japan

ABSTRACT

Higher order neural networks (HONNs) have been proposed as new systems. In this paper, we show some theoretical results of associative capability of HONNs. As one of them, memory capacity of HONNs is much larger than one of the conventional neural networks. Further, we show some theoretical results on homogeneous higher order neural networks (HHONNs), in which each neuron has identical weights. HHONNs can realize shift-invariant associative memory, that is, HHONNs can associate not only a memorized pattern but also its shifted ones.

1. INTRODUCTION

Numerous advances have been made in developing some intelligent systems inspired by biological neural networks (Rumelhart, McClelland, & the PDP Research Group, 1986; Hertz, Krogh, & Palmer 1991; Kasabov, 1996; Mehrotra, Mohan, & Ranka, 1997; Gupta, Jin, & Homma, 2003). Scientific studies have been done with designing artificial neural networks to solve a variety of problems in pattern recognition, prediction, optimization, associative memory, and control (Hopfield, & Tnak, 1985; Reid, Spirkovska, & Ochoa, 1989; Meir, & Domany, 1987; Gupta, Jin, & Homma, 2003). Associative memory is one of the well-studied applications of neural networks. Numerous associative memory models processing static and sequential patterns have been studied such as auto, mutual and multidirectional associative memory (Amari, & Maginu, 1988; McEliece, Posner, Rodemich, & Venkatesh, 1987; Yanai, & Sawada,

DOI: 10.4018/978-1-5225-0788-8.ch004

1990; Amari, 1990; Okada, 1996; Oda, & Miyajima, 2001; Amit, Gutfreund, & Sompolinsky, 1985; Kohonen, 1972; Kosko, 1987; Yoshizawa, Morita, & Amari, 1993; Morita, 1996; Abbott, & Arian, 1987; Amari, & Yanai, H., 1993; Hattori, & Hagiwara, 1995). However, it is known that the capability of the conventional associative memory using neural networks is not so high. Therefore, many associative memory models are proposed such as HONNs, in which the potential of a neuron is represented as the weighted sum of products of input variables, and have been applied to associative memory. It has been shown that HONNs have higher associative capability than the conventional neural networks, in which the potential of a neuron is represented as the weighted sum of input variables (Chan, & Michael, 1988; Reid, Spirkovska, & Ochoa, 1989; Abbott, & Arian, 1987; Cheung, & Lee, 1993; Miyajima, Shigei, & Yatsuki, 2012). However, there are little theoretical studies for the reason why HONNs are effective and the capability of HONNs. Further, from the practical points of view, associative memory should be invariant to pattern transformation such as shift, scaling and rotation. However, the conventional neural networks, cannot inherently acquire any transformation invariant property. Therefore, the conventional neural networks require pre-processing of input patterns to support transformed patterns; a transformed pattern is converted into a standard one, and then the standard pattern is inputted to the network. In order that neural networks inherently acquire shift-invariant properties, their structure should be homogeneous like cellular automata (Wolfram, 1984). Then, how many patterns can HONNs memorize and how about HHONNs?

In this paper, the authors show the basic results about them. As for the conventional neural networks, theoretical results have been shown in (Amari, & Maginu, 1988; McEliece, Posner, Rodemich, & Venkatesh, 1987; and Yanai, & Sawada, 1990). The authors generalize their results and analyze memory capacity of HONNs. As one of them, memory capacity of HONNs is much larger than one of the conventional neural networks. Further, the authors show some theoretical results on homogeneous higher order neural networks (HHONNs), in which each neuron has identical weights. HHONNs can realize essentially shift-invariant associative memory, that is, without any pre-processing of input patterns HHONNs can associate not only a memorized pattern but also its shifted ones (Miyajima, Shigei, & Yatsuki, 2005). HHONNs need $k \geq 2$ for associative memory. The transition property of HHONNs is analyzed by the statistical method. The authors show the probability that each neuron outputs correctly, and the error-correcting capability. Lastly, the relation between this chapter and other studies and the future works are discussed.

2. HIGHER ORDER NEURONS

Let us explain the conventional neuron. Let $I_i = \{1, \dots, i\}$ for a positive integer i . The output y for each neuron is given by

$$u = \sum_{j=0}^n w_j x_j \quad (1)$$

$$y = f(u), \quad (2)$$

28 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:
www.igi-global.com/chapter/some-properties-on-the-capability-of-associative-memory-for-higher-order-neural-networks/161023

Related Content

Biologically-Inspired Learning: An Overview and Application to Odor Recognition

Turgay Temel (2011). *System and Circuit Design for Biologically-Inspired Intelligent Learning* (pp. 59-92).
www.irma-international.org/chapter/biologically-inspired-learning/48891

Co-Evolving Better Strategies in Oligopolistic Price Wars

R. Marks, D. Midgley and L. Cooper (2007). *Handbook of Research on Nature-Inspired Computing for Economics and Management* (pp. 806-821).
www.irma-international.org/chapter/evolving-better-strategies-oligopolistic-price/21167

A Fireworks-Based Approach for Efficient Packet Filtering in Firewall

Sreelaja N. K. (2020). *Handbook of Research on Fireworks Algorithms and Swarm Intelligence* (pp. 315-333).
www.irma-international.org/chapter/a-fireworks-based-approach-for-efficient-packet-filtering-in-firewall/252915

Asynchronous P Systems

Tudor Balanescu, Radu Nicolescu and Huiling Wu (2011). *International Journal of Natural Computing Research* (pp. 1-18).
www.irma-international.org/article/asynchronous-systems/57967

Connecting Microbial Population Genetics with Microbial Pathogenesis Engineering Microfluidic Cell Arrays for High-throughput Interrogation of Host-Pathogen Interaction

Palaniappan Sethu, Kalyani Putty, Yongsheng Lian and Awdhesh Kalia (2011). *Handbook of Research on Computational and Systems Biology: Interdisciplinary Applications* (pp. 533-548).
www.irma-international.org/chapter/connecting-microbial-population-genetics-microbial/52331