

Mobile Radio Technologies

Christian Kaspar

Georg-August-University of Goettingen, Germany

Svenja Hagenhoff

Georg-August-University of Goettingen, Germany

INTRODUCTION

Mobile radio technologies have been subject to speculations in recent years. The initial euphoria about opportunities and market potentials of mobile services and applications has mainly been caused by growth expectations in the field of non-voice-orientated services. For the year 2003 optimistic analysis of the market development already predicted an expected total volume for the European sales of more than 23 billion Euros (Müller-Verse, 1999). But such expectations appear to be hardly achievable. In 2003 the German Ministry of Labour and Economics merely show a sales volume of US\$71 million for Europe. Based on this number, an increase up to US\$119 million until 2007 is predicted (Graumann/Köhne, 2003).

Due to the lack of successful business and product concepts, the gap between expectation and reality leads to insecurity about the opportunities of mobile commerce. This insecurity is mainly caused by the continuing high complexity and dynamic of mobile technologies. Therefore, particular aspects of mobile technologies as a basis of promising business concepts within mobile commerce are illustrated in the following. In order to solve insecurity problems, the application possibilities of present mobile technologies need to be analyzed on three different levels: First on the network level, whereas available technology alternatives for the generation of digital radio networks need to be considered; secondly, on the service level in order to compare different transfer standards for the development of mobile information services; thirdly, on the business level, in order to identify valuable application scenarios from the customer point of view. The following analysis considers alternative technologies on the network and service level in order to determine application scenarios of mobile technologies in the last chapter.

DIGITAL RADIO NETWORKS

In the past the analysis of mobile radio technology has often been limited to established technology standards as well as their development in the context of wide-area communication networks. Today it is recognizable that wireless technologies that have been developed for networks within locally limited infrastructures represent good and cheap alternatives to wide-area networks (Webb, 2001). Thus, in the following three alternatives, architecture and technology are represented.

General Basics of Mobile Radio Technology

Generally, connections within mobile radio networks can be established between mobile and immobile stations (infrastructure networks) or between mobile stations (ad-hoc networks) only (Müller, Eymann, & Kreutzer, 2003). Within the mobile radio network, the immobile transfer line is displaced by an unadjusted radio channel. In contrast to analogous radio networks, where the communication signal is directly transferred as a continuing signal wave, within the digital radio network the initial signal is coded in series of bits and bytes by the end terminal and decoded by the receiver.

The economically usable frequency spectrum is limited by the way of usage as well as by the actual stage of technology and therefore represents a shortage for mobile radio transmissions. Via so called "multiplexing", a medium can be provided to different users by the division of access area, time, frequency, or code (Müller, Eymann, & Kreutzer, 2003; Schiller, 2003).

In contrast to fixed-wire networks within radio networks, the signal spread takes place directly similar to light waves. Objects within the transfer area can

interfere with the signal spread that is why there is the danger of a signal deletion within wireless transmission processes. In order to reduce such signal faults, spread spectrum techniques distribute the initial transmission bandwidth of a signal onto a higher bandwidth (Schiller, 2003). The resulting limitation of available frequency can be minimized by the combination of spread spectrum techniques with multiple access techniques. Those forms of combination are represented, for example by the *Frequency Hopping Spread Spectrum* (FHSS), where each transmitter changes the transfer frequency according to a given hopping sequence, or the *Direct Sequence Spread Spectrum* (DSSS), where the initial signal spread is coded by a predetermined pseudo random number.

Wireless Local Area Networks (IEEE 802.11)

The developers of the 802.11 standards aimed at establishing application and protocol transparency, seamless fixed network integration and a worldwide operation ability within the license-free ISM (Industrial, Scientific and Medical) radio bands (Schiller, 2003). The initial 802.11 standard of 1997 describes three broadcast variants: one infrared variant uses light waves with wave-lengths of 850-950 nm and two radio variants within the frequency band of 2.4 GHz which are economically more important (Schiller, 2003). Within the designated spectrum of the transfer power between a minimum of 1 mW and a maximum of 100 mW in Europe the radio variants can achieve a channel capacity of 1-2 Mbit/s. Following the 802.3 (Ethernet) and 802.4 (Token Ring) standards for fixed-wire networks the 802.11 standard specifies two service classes (IEEE, 2001): an asynchronous service as a standard case analogous to the 802.3 standard and an optional, temporally limited synchronous service. Typically WLANs operate within the infrastructure modus whereby the whole communication of a client takes place via an access point. The access point supplies every client within its reach or serves as a radio gateway for adjoining access points.

Developments of the initial standards are mainly concentrated on the area of the transfer layer (Schiller, 2003). Within the 802.11a standard the initial 2.4

GHz band is displaced by the 5 GHz band, allowing a capacity of up to 54 Mbit/s. In contrast to this, the presently most popular standard 802.11b uses the encoded spread spectrum technique DSSS. It achieves a capacity up to 11 Mbit/s operating within the 2.4 GHz band.

Wireless Personal Area Networks (Bluetooth)

In 1998 Ericsson, Nokia, IBM, Toshiba, and Intel founded a "Special Interest Group" (SIG) for radio networks for the close-up range named "Bluetooth" (SIG, 2004). Like WLAN networks, Bluetooth devices transfer within the 2.4 GHz ISM bands, which is why interferences may occur between both network technologies. In general, 79 channels are available within Bluetooth networks. FHSS is implemented with 100 hops per second as spread spectrum technique (Bakker & McMichael, 2002). Devices with identical hop sequences constitute a so-called "pico-network". Within this network, two service categories are specified: a synchronous, circuit-switched method and an asynchronous method. Within the maximum transfer power of 10 mW Bluetooth devices can reach a transfer radius of 10 m up to a maximum of 100 m and a data capacity of up to 723 Kbit/s (Müller, Eymann, & Kreutzer, 2003).

The main application areas of Bluetooth technologies are the connection of peripheral devices like computer mouse, headphones, automotive electronics, and kitchen equipment or the gateway function between different network types like the cross linking of fixed-wire networks and mobile radio devices (Diederich, Lerner, Lindemann, & Vehlen, 2001). Generally, Bluetooth networks are therefore linked together as ad-hoc networks. Ad-hoc networks do not require decided access points; mobile devices communicate equally and directly with devices within reach. Among a network of a total maximum of eight terminals, exactly one terminal serves as a master station for the specification and synchronization of the hop frequency (Haartsen, 2000; Nokia, 2003). Bluetooth devices can be involved in different pico-networks at the same time but are not able to communicate actively within more than one of these networks at a particular point in time. These overlapping network structures are called scatter-networks.

5 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/mobile-radio-technologies/17310

Related Content

Time Series Analysis for Crime Forecasting Using ARIMA (Autoregressive Integrated Moving Average) Model

Neetu Faujdar and Anant Joshi (2021). *Advancements in Security and Privacy Initiatives for Multimedia Images* (pp. 158-198).

www.irma-international.org/chapter/time-series-analysis-for-crime-forecasting-using-arima-autoregressive-integrated-moving-average-model/262073

Toward LessonCapture: A New Approach to Screencasting and Lecture Capture

Steve Garwood (2013). *Enhancing Instruction with Visual Media: Utilizing Video and Lecture Capture* (pp. 89-105).

www.irma-international.org/chapter/toward-lessoncapture-new-approach-screencasting/75415

Implementing DWDM Lambda-Grids

Marlyn Kemper Littman (2009). *Encyclopedia of Multimedia Technology and Networking, Second Edition* (pp. 661-667).

www.irma-international.org/chapter/implementing-dwdm-lambda-grids/17463

Design and Evaluation of a Content-Based Image Retrieval System

David Squire, Henning Muller, Wolfgang Muller, Stephane Marchand-Maillet and Thierry Pun (2001). *Design and Management of Multimedia Information Systems: Opportunities and Challenges* (pp. 125-151).

www.irma-international.org/chapter/design-evaluation-content-based-image/8110

A Serious Game for Geo-Education in the Arouca Geopark Territory

Tiago Martins, Júlio Coelho and Vitor Carvalho (2020). *Multidisciplinary Perspectives on New Media Art* (pp. 161-188).

www.irma-international.org/chapter/a-serious-game-for-geo-education-in-the-arouca-geopark-territory/260025