3D Scanning and Simulation of a Hybrid Refrigerator Using Photovoltaic Energy

Edith Obregón Morales

Centro de Investigación y Desarrollo Tecnológico en Electroquímica, Mexico

José de Jesús Pérez Bueno Centro de Investigación y Desarrollo Tecnológico en Electroquímica, Mexico

Juan Carlos Moctezuma Esparza Universidad Politécnica Metropolitana de Hidalgo, Mexico

Diego Marroquín García

Universidad Tecnológica de San Juan del Río, Mexico

Arturo Trejo Pérez Universidad Tecnológica de San Juan del Río, Mexico

Roberto Carlos Flores Romero Universidad Tecnológica de San Juan del Río, Mexico

Juan Manuel Olivares Ramírez Universidad Tecnológica de San Juan del Río, Mexico

Maria Luisa Mendoza López Tecnológico Nacional de México, Instituto Tecnológico de Querétaro, Mexico

Juan Carlos Solís Ulloa Instituto Tecnológico Superior de Cintalapa, Mexico

Yunny Meas Vong Centro de Investigación y Desarrollo Tecnológico en Electroquímica, Mexico

Víctor Hugo Rodríguez Obregón Centro de Investigación y Desarrollo Tecnológico en Electroquímica, Mexico

INTRODUCTION

In this chapter, a methodology that starts with the measurement and recording of real prototype geometries up to simulations to evaluate parameters, improvements or performance under various conditions is proposed. Here it is presented a case study of a solar powered refrigerator with storage capacity for 50 kg of fruit. The refrigerator comprises two systems, vapor-compression and Peltier. The methodology consisted in acquiring by a 3D laser scanner or Coordinate Measuring Machine (CMM) and in some small complex items using a 3D photogrammetry scanner (James, 2017; Ozdarici-Ok, 2015). These data were transferred first as a CAD or SolidWorks[®] geometry and subsequently transferred to domains geometry useful for ANSYS or COMSOL simulation software. These models with high-resolution brings the simulations closer to real prototypes. As a

DOI: 10.4018/978-1-5225-2255-3.ch110

С

source of direct information from the prototypes, thermal images obtained using a thermographic camera were taken. Also, wireless sensors were installed for temperature and humidity monitoring. The analyses of the energy efficiencies of both prototypes were performed. The idea of presenting this methodology is to demonstrate that it is possible to apply it in various prototypes regardless of sizes, geometries or whether they are or not solar powered.

The work seeks to develop a hybrid cooling system based on a system of traditional compression system and a Peltier cooling system. The construction or production of this system is focused on being able to assist the agribusiness sector that is away from the public electric network, directly in the crop areas, proposing that this system will be powered completely by photovoltaic modules and in turn, be able to innovate with the cooling systems adaptations.

The starting point was a commercial compression system, to build or make an approach of the required refrigerator with a capacity of 50 kilograms. The material used in the Peltier cooling system consisted of: four Peltier modules of 50 W, eight heat sinks and eight fans that assist with the distribution of heat within the refrigerator.

The following steps were the elaboration of the construction drawings, drilling and placing of the Peltier systems, in a distribution geometry designed in the SolidWorks[®] software. All the parts were put in place both physical and mechanical. Some of them were affected during the modification process. The geometry was acquired and exported for its analysis in a virtual simulation module of finite element (Work Bench ANSYS), to obtain a validation or improvement of the system with the efficiency of space and location, considering the fluid dynamics and thermodynamics.

A general scanning was conducted for a commercial refrigerator with a laser system (ZX 800 Corp) and, for the smaller parts, with a system of photogrammetry (PicoScan Pro). The scannings were conducted using these devices for the development of a virtual 3D modeling. In this process, a polygonal mesh was applied to the virtual model initially constituted only of a point cloud (Bici, 2014), which is transformed into a file compatible with the simulation software.

Once that the process with the commercial refrigerator model reaches the simulation stage, the methodology is applicable to the construction and adaptation of the Peltier system using as a guide the electrical drawings previously made. To achieve a relationship between the Peltier system and the compression system uses a temperature sensor programmed to monitor the functioning of these systems on the basis of specific conditions known during the simulation process.

BACKGROUND

Design and Computer Aided Engineering

Design is an activity that is projected toward the solution of problems in the process of adaptation to the environment that surrounds it, for such purpose resources as the technology CAD/ CAE are used. The most developed technique in Computer Aided Engineering (CAE) is the application of Finite Element Analysis (FEA) that, with the improvement of computers has become more accessible to all users. These techniques are used industrially from design to manufacturing getting optimize costs, quality, time, security, etc.

The implementation of the CAD software in engineering includes the development of synoptic charts, diverse kinds of diagrams, statistical graphics, standard representation of parts for its design and construction, tridimensional representation of dynamic models in multimedia, finite element analysis, applications in virtual reality, robotics, etc. 18 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/3d-scanning-and-simulation-of-a-hybridrefrigerator-using-photovoltaic-energy/183841

Related Content

Using Total Quality Management to Mitigate Supply Chain Risk

Terry D. Crippen (2015). Encyclopedia of Information Science and Technology, Third Edition (pp. 1508-1515).

www.irma-international.org/chapter/using-total-quality-management-to-mitigate-supply-chain-risk/112553

Cryptographic Approaches for Privacy Preservation in Location-Based Services: A Survey

Emmanouil Magkos (2011). International Journal of Information Technologies and Systems Approach (pp. 48-69).

www.irma-international.org/article/cryptographic-approaches-privacy-preservation-location/55803

Minimising Collateral Damage: Privacy-Preserving Investigative Data Acquisition Platform

Zbigniew Kweckaand William J. Buchanan (2011). International Journal of Information Technologies and Systems Approach (pp. 12-31).

www.irma-international.org/article/minimising-collateral-damage/55801

Two Rough Set-based Software Tools for Analyzing Non-Deterministic Data

Mao Wu, Michinori Nakataand Hiroshi Sakai (2014). *International Journal of Rough Sets and Data Analysis* (pp. 32-47).

www.irma-international.org/article/two-rough-set-based-software-tools-for-analyzing-non-deterministic-data/111311

An Overview of 3GPP Long Term Evolution (LTE)

Elisavet Grigoriouand Periklis Chatzimisios (2015). *Encyclopedia of Information Science and Technology, Third Edition (pp. 6122-6131).*

www.irma-international.org/chapter/an-overview-of-3gpp-long-term-evolution-lte/113069