

## Chapter XXV

# An Integrated Approach for the Planning and Control of Flexible Retro-Production Systems

Jürgen Hesselbach and Karsten v. Westernhagen  
Technical University Braunschweig, Germany


### INTRODUCTION

While in the past only the product phases of development, production, distribution as well as use and service were considered, today, more complete consideration up to the end of a product life is common. Along with the demand for an environmentally-friendly handling of important resources, recycling of worn-out products, for example, in the automotive sector, electrical and electronic equipment, or industrial goods, will gain crucial importance in the near future. In addition, comprehensive environmentally-related legal demands force the industry to take recycling of products into consideration (BMU, 1999; EU, 1999; Griese, 1997; Seliger et al., 1997; Thierry et al., 1995). Additionally this includes several processes (Figure 1) of the post-usage phase, such as:

- systematic take-back of used products to specific facilities,
- definition of adequate recycling strategies,
- dismantling of products,
- reprocessing of components,
- mechanical treatment,
- reuse of components and utilization of materials as well as
- redistribution of the recycled goods into production and secondary raw material market.

The focus of this chapter is set to the key process *dismantling*, so-called retro-pro-

Figure 1: Enlargement of the Products Life Cycle



duction, in order to close the loop of components, parts or materials in the production. Dismantling of worn-out products is a difficult process for different reasons. On the one hand, dismantling enables the separation of components suitable for reuse, to regain pure materials, as well as the isolation of harmful substances. In addition, the process retro-production also receives a higher importance because aspects like maintenance and service of products, whereby disassembly activities are also performed. In the automotive industry, for example, old generators and starters as well as compressors of trucks are repaired, checked and resold. On the other hand, dismantling is time-intensive and costly because of the large share of manual work. This is caused by the great heterogeneity of the products arising at the recycling facilities: the product spectrum is multifarious in functionality, design and years of construction as well as manufacturers that makes automation difficult (Lund, 1996; Seliger et al., 1999; Wiendahl et al., 1998).

Therefore, it is necessary to enlarge the possible application fields of common environmental information systems. Suitable instruments have to be developed to plan and to control dismantling processes and to integrate these processes into suitable retro-production systems. Methods known from the production planning are enlarged and integrated into this approach.

A brief overview about the actual status of dismantling and important requirements on appropriate instruments are given next. In the following parts, the approach is outlined, whereas the specific parts and the underlying methods are described in more detail.

## **OVERVIEW OF THE STATUS OF RETRO-PRODUCTION SYSTEMS**

The actual situation in the recycling field is mainly featured by workmanship. Apart of the great variety of variants and the complex product structures, their emergence and distribution in a recycling facility are subjected to strong stochastic fluctuations. Aggravating for dismantling is the fact that the outdated products of today are generally not designed to be disassembled (Hesselbach et al. 1998a; 1999a).

At the recycling facilities, the optimal recycling strategy of the products has to be determined. For products to be dismantled, the related expenditure has to be estimated and the corresponding processes have to be planned. In practice, products are dismantled in several work steps into a certain amount of fractions resulting in a diverging material flow. It is difficult to automate the individual dismantling operations due to these reasons mentioned above. Therefore, existing organizational structures in recycling facilities are based mainly on manual disassembly at individual working places. The differences between the actual retro-production in practice and the highly industrialized production become quite clear. Rationalizing potentials, by an optimized use of existing equipment or job sharing and the herewith resulting exploitation of learning effects, will not be fully exhausted.

Studies performed at recycling facilities showed positive results when reducing the variety of dismantling operations and unifying the corresponding processes (Figure 2). In this case, a group of similar monitors (Nokia 41BJ251) were dismantled by the same operator at one place and the corresponding processes were analyzed.

10 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/integrated-approach-planning-control-flexible/18548](http://www.igi-global.com/chapter/integrated-approach-planning-control-flexible/18548)

## Related Content

---

### Hybrid Materiality: Combining Digital and Analogue Fabrication in the Design of a Freeform Gridshell Structure

Mauricio Morales-Beltran, Esra Karatepe, Kaan Çetin and Berk Selamolu (2021). *International Journal of Digital Innovation in the Built Environment* (pp. 46-62).

[www.irma-international.org/article/hybrid-materiality/283116](http://www.irma-international.org/article/hybrid-materiality/283116)

### Bioremediation of Industrial Waste Using Microbial Metabolic Diversity

Saurabh Gangola, Pankaj Bhatt, Parul Chaudhary, Priyanka Khatri, Narendra Kumar and Anita Sharma (2018). *Microbial Biotechnology in Environmental Monitoring and Cleanup* (pp. 1-27).

[www.irma-international.org/chapter/bioremediation-of-industrial-waste-using-microbial-metabolic-diversity/196789](http://www.irma-international.org/chapter/bioremediation-of-industrial-waste-using-microbial-metabolic-diversity/196789)

### A Generic Spatial OLAP Model for Evaluating Natural Hazards in a Volunteered Geographic Information Context

Sandro Bimonte, Omar Boucelma, Olivier Machabert and Sana Sellami (2014). *International Journal of Agricultural and Environmental Information Systems* (pp. 40-55).

[www.irma-international.org/article/a-generic-spatial-olap-model-for-evaluating-natural-hazards-in-a-volunteered-geographic-information-context/120435](http://www.irma-international.org/article/a-generic-spatial-olap-model-for-evaluating-natural-hazards-in-a-volunteered-geographic-information-context/120435)

### Nitrate, Total Ammonia, and Total Suspended Sediments Modeling for the Mobile River Watershed

Vladimir J. Alarcon and Gretchen F. Sassenrath (2017). *International Journal of Agricultural and Environmental Information Systems* (pp. 20-31).

[www.irma-international.org/article/nitrate-total-ammonia-and-total-suspended-sediments-modeling-for-the-mobile-river-watershed/179581](http://www.irma-international.org/article/nitrate-total-ammonia-and-total-suspended-sediments-modeling-for-the-mobile-river-watershed/179581)

### An Exploration of COVID-19 and Its Consideration as a Black Swan for the Construction Industry in Switzerland

Adrian August Wildenauer and Josef Basl (2021). *International Journal of Digital Innovation in the Built Environment* (pp. 62-82).

[www.irma-international.org/article/an-exploration-of-covid-19-and-its-consideration-as-a-black-swan-for-the-construction-industry-in-switzerland/277122](http://www.irma-international.org/article/an-exploration-of-covid-19-and-its-consideration-as-a-black-swan-for-the-construction-industry-in-switzerland/277122)