New Approach to Optimize Cooperation Mobile Robots for Ideal Coverage with an Architecture Designed with Multi-Agent Systems

Mami Mohammed Amine, Department of Computer Science, University of Oran1 Ahmed Ben Bella, Oran, Algeria Khelfi Mohamed Fayçal, University of Oran1 Ahmed Ben Bella, Oran, Algeria Zineb Laouici, Department of Computer Science, University of Blida, Jijel, Algeria Benyettou Noria, USTOMB Oran, Oran, Algeria

ABSTRACT

Mobile Robotics have taken an ever increasing role in everyday life in the past few years. The main objective often reflected in research is to try to have an optimal cooperation between the different robots to achieve a given objective. This cooperation allows one to have optimal solutions for sharing and resolving conflicts. This article proposes a solution to solve the problem of the coverage in environment with obstacles and the cooperation between several mobile robots. The authors developed a heuristic algorithm to optimize the coverage in a multi-robot system, while maintaining the connection between the robots. The proposed algorithm is based on the propagation of the robots as a function of the expansion of a wave in a uniform manner. The authors also integrate a self-reorientation approach to failure if a robot becomes out of race. Finally, this approach is modelled with the ADMs.

KEYWORDS

ADMs, Area Coverage, Communication, Cooperation, Maintaining Connectivity, Multi-Robots, Navigation, Optimization, Overhead Network, Robot Fails, Unknown Environment

PROBLEM STATEMENT

Recent advances in the field of mobile robotics has led to many interesting results on the uses of robots in several areas, regardless of their number in each mission. Using one or more robots is relevant to the task. However, recently the multi-robots have highly experienced increased attention because of their performance compared to a single robot. Cooperation and coordination between the different members tend to improve their performance. Many applications use the multi-robot: rescuing survivors during natural disasters, surveillance in several environments and monitoring in areas contaminated by nuclear or chemical waste, etc.

Concerning the above-mentioned tasks, the coverage is the common problem with each other. In order to have optimal coverage area, the proposed method needs to reach two important questions: Maximizing Team coverage area of robots and maintaining connectivity between robots. In the first

DOI: 10.4018/JCIT.2017100105

Copyright © 2017, IGI Global. Copying or distributing in print or electronic forms without written permission of IGI Global is prohibited.

problem, the team members deployed randomly, they cooperate to maximize network coverage. The robots communicate to achieve the most appropriate positions, reducing the distance travelled and optimized network deployment. In the second issue, the authors expect to maintain connectivity of botnet in the hedging process and construction of the optimal network connected robot, even if there are robot failures.

The authors have attempted to find a solution to both problems. Initially, mobile robots deployed randomly. Each autonomous robot reacts to navigate; it communicates and cooperates to specify the next destination.

The main contribution of this paper is to address the problem of coverage and maintaining connectivity. The solution envisaged is to maximize the coverage area using multiple robots and maintain connectivity. Moreover, it is necessary to have optimal deployment in less time and less movement. These two features are very important in these cases: the search and rescue missions, etc. and maintaining connectivity between mobile robots during their redeployment guaranteed, the authors have also presented a solution in case of failure robots. This document in addition provides an efficient algorithm that minimizes general messages related to:

- Local calls of each robot;
- Each mobile robot executes the process once.

The results of the simulation, which includes one method and comparison to other methods, the solution validate and prove the efficiency of the algorithm proposed.

RELATED WORK

Various searches were performed in the literature considering the multi-robot cooperation issues, particularly the problem of coverage but also for exploration Baglietto et al. (2002) and Yuan et al. (2010). On the topic coverage problem, many researchers show how to increase the coverage area and how to maintain connectivity. The authors of Mathews et al. (2012) decompose existing solutions of this problem based on force Voronoi and behavior. The research presented by Mathews et al. (2012) simulates the behavior of a swarm of fish that remain as a group. In Mathews et al. (2012), three rules used to determine strengths: the separation force, the cohesive force and the alignment force (neighbours).

Akkaya and Younis (2007), present an algorithm based on the repulsive forces between molecules in medicine for spreading the robots through a zone; the movement of each member is limited. Proposed approach is close to this work in the context of cooperation and modification of information between robots of the team. However, there are a number of important differences between proposed method and Akkaya and Younis (2007): Firstly, Akkaya and Younis (2007) in a group, only the robot with the highest priority will move, others will remain stationary. In the same time, in proposed approach the current robot that gathers information about its neighbours, will remain stationary and its neighbours achieve their defined positions. Through this priority, the botnet will be hired as quickly as possible. Secondly, in Akkaya and Younis (2007) all the nodes broadcast two types of messages provide information about their neighbours, the robots also repeat the process while coverage increases. This procedure causes a supervision message. In proposed approach, the robot executes the process that broadcasts a message to each processor who is running the process once.

Using this approach Tan et al. (2004) provides an algorithm that solves the problem of the cover and presents a control of the formation of a plurality of robots. The algorithm based on the Voronoi diagram and Delaunay triangulation; it builds the current state of the Voronoi diagram of the network of robots and determines the cell centre of gravity. Each robot moves to the cell on centre of gravity.

0 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-

global.com/article/new-approach-to-optimize-cooperationmobile-robots-for-ideal-coverage-with-an-architecturedesigned-with-multi-agent-systems/189205

Related Content

An Automatic Data Warehouse Conceptual Design Approach

Jamel Feki (2009). Encyclopedia of Data Warehousing and Mining, Second Edition (pp. 110-119).

www.irma-international.org/chapter/automatic-data-warehouse-conceptual-design/10807

Mass Informatics in Differential Proteomics

Xiang Zhang, Seza Orcun, Mourad Ouzzaniand Cheolhwan Oh (2009). *Encyclopedia of Data Warehousing and Mining, Second Edition (pp. 1176-1181).*

www.irma-international.org/chapter/mass-informatics-differential-proteomics/10971

Clustering Categorical Data with k-Modes

Joshua Zhexue Huang (2009). Encyclopedia of Data Warehousing and Mining, Second Edition (pp. 246-250).

www.irma-international.org/chapter/clustering-categorical-data-modes/10828

A Novel Approach on Negative Association Rules

Ioannis N. Kouris (2009). Encyclopedia of Data Warehousing and Mining, Second Edition (pp. 1425-1430).

www.irma-international.org/chapter/novel-approach-negative-association-rules/11008

Ensemble Learning for Regression

Niall Rooney (2009). Encyclopedia of Data Warehousing and Mining, Second Edition (pp. 777-782).

www.irma-international.org/chapter/ensemble-learning-regression/10908