

Chapter XI

Runtime Service Discovery for Grid Applications

James Dooley
City University, UK

Andrea Zisman
City University, UK

George Spanoudakis
City University, UK

ABSTRACT

This chapter describes a framework to support runtime service discovery for Grid applications based on service discovery queries in both push and pull modes of query execution. The framework supports six different types of trigger conditions that may prompt service replacement during run-time of grid business application, and evaluates the relevance of a set of candidate services against service discovery queries. The chapter also describes the language used to express service discovery queries and the three types of fitness measurement used to evaluate the candidate services against these queries. Both synchronous (pull) and asynchronous (push) mechanisms for service discovery are presented and shown to be complimentary in dealing with all six service discovery trigger conditions. The chapter is illustrated through examples.

INTRODUCTION

Traditionally, grid computing has been a form of distributed computing that is concerned with resource sharing across communications networks.

In this model, individual computers are called nodes and virtualize certain resources such as processor, memory and storage. Other nodes can then access these virtual resources over a network connection. These nodes are physically distributed

and are usually under the control and ownership of different entities. Examples of controlling entities are: governments, universities, corporations, and businesses. Grids implement models of virtualisation and rely on standard protocols for communication, both of which are captured in a software layer known as middleware.

More recently, Service Oriented Architecture (SOA) has emerged from the IT world in the form of web-services. SOA is an approach to enable a set of loosely coupled functional components to exist and be remotely usable. As opposed to grid computing, the emphasis of SOA is more on how to exchange information which is well defined whilst still being of open standard (as opposed to grid computing that places emphasise on the infrastructure). Foster and Tuecke (2005) capture the description of a service as *"A service is a self-contained implementation of some function(s) with a well defined interface specifying the message exchange patterns used to interact with the function(s)."*

The web-services incarnation, allows a service to exist as a Uniform Resource Locator (URL) to which requests can be sent and responses solicited in both synchronous and asynchronous modes. Over the following four paragraphs we account for some approaches that have been recently proposed to support different areas of SOA. The approaches discussed are concerned with (a) languages to describe services, (b) service discovery, (c) service composition, and (d) service monitoring, validation, verification, and evolution.

Various XML-based languages have been proposed to support descriptions of service components and choreography. Web Services Description Language - WSDL (Christensen et al., 2001) is currently the most used language for service description and supports interface-based definition in terms of input/output signatures. The semantic markup for Web Services - OWL-S (Martin et al., 2004) is an ontology that exists within the web ontology language (OWL) and extends input/output signatures by allowing the

description of pre- and post-conditions to represent value-based restrictions, while Web Services Modelling Ontology - WSMO (Bruijn et al., 2005) provides a language for describing semantic aspects of services. The Business Process Execution Language for Web Services - BPEL4WS (Andrews et al., 2003) is a language that describes observable behaviour of web services by message-flow oriented interface. The Web Service Conversation Language - WSCL, (Banerji et al., 2002) goes beyond description of input/output messages, and defines transitions with associated conditions. More recently, OpenModel Modelling Language - OMML (Hall & Zisman, 2004b) has been proposed to support full behaviour specification of computer-based services.

Different approaches have been proposed to support service discovery. Some semantic match-making approaches have been suggested to support service discovery based on logic reasoning of terminological concept relations represented as ontology's. METEOR-S (Aggarwal et al., 2004) adopts a constraint driven discovery approach in which queries are integrated into a system composition process. In (Horrocks et al., 2003) the discovery of services is addressed by matching queries specified as a variant of description logic with services specified in OWL-S. The work in (Klusck, 2006) extends existing approaches by supporting explicit and implicit semantic by using logic based, approximate matching, and information retrieval techniques. The discovery mechanism in (Hausmann et al., 2004) is based on the use of Resource Description Framework Data Query Language (RDQL) by testing sub-graph relations and establishing whether specification matching relation holds between the query and the service description. The approach in (Horrocks et al., 2003) identifies services that satisfy task requirement properties expressed in temporal logic by using a lightweight reasoning tool. A flexible and modular Web Service Discovery Architecture (WSDA) was introduced in (Hoschek, 2002) where interface queries are checked

21 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/runtime-service-discovery-grid-applications/19346

Related Content

Peer-to-Peer Service Discovery for Grid Computing

Eddy Caron, Frédéric Desprez, Franck Petitand Cédric Tedeschi (2012). *Grid and Cloud Computing: Concepts, Methodologies, Tools and Applications* (pp. 232-259).

www.irma-international.org/chapter/peer-peer-service-discovery-grid/64486

Deep Reinforcement Learning and In-Network Caching-Based Martial Arts Physical Training

Qi Zhang (2022). *International Journal of Distributed Systems and Technologies* (pp. 1-8).

www.irma-international.org/article/deep-reinforcement-learning-network-caching/291079

Watermarking of EEG Data to Provide Security Based on DWT-SVD and Optimized by Firefly Algorithm

Akash Kumar Gupta, Chinmay Chakrabortyand Bharat Gupta (2022). *International Journal of Distributed Systems and Technologies* (pp. 1-16).

www.irma-international.org/article/watermarking-of-eeeg-data-to-provide-security-based-on-dwt-svd-and-optimized-by-firefly-algorithm/307902

A Service Component Model and Implementation for Institutional Repositories

Yong Zhang, Quansong Deng, Chunxiao Xing, Yigang Sunand Michael Whitney (2012). *Grid and Cloud Computing: Concepts, Methodologies, Tools and Applications* (pp. 466-486).

www.irma-international.org/chapter/service-component-model-implementation-institutional/64497

Peer-to-Peer Desktop Grids Based on an Adaptive Decentralized Scheduling Mechanism

H. Arafat Ali, A.I. Saleh, Amany M. Sarhanand Abdulrahman. A. Azab (2012). *Evolving Developments in Grid and Cloud Computing: Advancing Research* (pp. 47-66).

www.irma-international.org/chapter/peer-peer-desktop-grids-based/61982