# Chapter 6 The Hyper–Zagreb Index and Some Properties of Graphs

#### Rao Li

University of South Carolina at Aiken, USA

## ABSTRACT

Let G = (V(G), E(G)) be a graph. The complement of G is denoted by Gc. The forgotten topological index of G, denoted F(G), is defined as the sum of the cubes of the degrees of all the vertices in G. The second Zagreb index of G, denoted M2(G), is defined as the sum of the products of the degrees of pairs of adjacent vertices in G. A graph G is k-Hamiltonian if for all  $X \subset V(G)$  with  $|X| \le k$ , the subgraph induced by V(G) - X is Hamiltonian. Clearly, G is 0-Hamiltonian if and only if G is Hamiltonian. A graph G is k-path-coverable if V(G) can be covered by k or fewer vertex-disjoint paths. Using  $F(G^c)$  and  $M_2(G^c)$ , Li obtained several sufficient conditions for Hamiltonian and traceable graphs (Li, The Hyper-Zagreb Index and Some Properties of Graphs). In this chapter, the author presents sufficient conditions based upon  $F(G^c)$  and  $M_2(G^c)$  for k-Hamiltonian, k-edge-Hamiltonian, k-path-coverable, k-connected, and k-edge-connected graphs.

### INTRODUCTION

We consider only finite undirected graphs without loops or multiple edges. Notation and terminology not defined here follow that in Bondy and Murty (1976). Let G = (V(G), E(G)) be a graph. We use  $n, e, \delta$ , and  $\kappa$  to denote the order, size, minimum degree, and connectivity of G, respectively. The complement of G is denoted by  $G^c$ . We also use  $K_n$  and  $E_n$  to denote the complete graph and the empty graph of order n. The forgotten topological index of G, denoted F(G), is defined as  $\sum_{v \in V(G)} (d(v))^3$  (see Furtala & Gutman, 2015). The second Zagreb index of G, denoted HZ(G), is defined as  $\sum_{v \in E(G)} d(u) d(v)$  (see Gutman et al., 1975). The hyper-Zagreb index of G, denoted HZ(G), is defined as  $F(G) + 2M_2(G)$  (see Milovanovic, Matejic & Milovanovic, 2019). We use  $\mu_n(G)$  to denote the largest eigenvalue of DOI: 10.4018/978-1-5225-9380-5.ch006

the adjacency matrix of a graph G of order n. For two disjoint graphs  $G_1$  and  $G_2$ , we use  $G_1 + G_2$  and  $G_1 \lor G_2$  to denote respectively the union and join of  $G_1$  and  $G_2$ . The concept of closure of a graph G was introduced by Bondy and Chvátal in Bondy and Chvatal (1976). The k-closure of a graph G, denoted  $cl_{k}(G)$ , is a graph obtained from G by recursively joining two nonadjacent vertices such that their degree sum is at least k until no such pair remains. We use C(n,r) to denote the number of r-combinations of a set with n distinct elements. A cycle C in a graph G is called a Hamiltonian cycle of G if C contains all the vertices of G. A graph G is called Hamiltonian if G has a Hamiltonian cycle. A path P in a graph G is called a Hamiltonian path of G if P contains all the vertices of G. A graph G is called traceable if G has a Hamiltonian path. A graph G is k-Hamiltonian if for all  $X \subset V(G)$  with  $|X| \leq k$ , the subgraph induced by V(G) - X is Hamiltonian. Clearly, G is 0-Hamiltonian if and only if G is Hamiltonian. A graph G is k-edge-Hamiltonian if any collection of vertex-disjoint paths with at most k edges is in a Hamiltonian cycle in G. Clearly, G is 0-edge-Hamiltonian if and only if G is Hamiltonian. A graph G is k-path-coverable if V(G) can be covered by k or fewer vertex-disjoint paths. Clearly, G is 1-path-coverable if and only G is a traceable. A graph G is k-connected if it has more than k vertices and G is still connected whenever fewer than k vertices are removed from G. A graph G is k-edgeconnected if it has at least two vertices and G is still connected whenever fewer than k edges are removed from G.

The following results were obtained by Fiedler and Nikiforov.

**Theorem 1:** (Fiedler & Nikiforov, 2010) Let *G* be a graph of order *n*.

1. If  $\mu_n(G^c) \le \sqrt{n-1}$ , then G contains a Hamiltonian path unless  $G = K_{n-1} + v$ .

2. If  $\mu_n(G^c) \leq \sqrt{n-2}$ , then G contains a Hamiltonian cycle unless  $G = K_{n-1} + e$ .

Using the ideas and techniques developed by Fiedler and Nikiforov (2010), Li (2019) obtained sufficient conditions which involve the hyper-Zagreb indexes of the complements of the graphs for the Hamiltonian and traceable graphs. It is found that the ideas and techniques in Li (2019) can also be utilized to obtain sufficient conditions based upon hyper-Zagreb indexes for the additional properties of graphs. The aim of this paper is to present those conditions for *k*-Hamiltonian, *k*-edge-Hamiltonian, *k*path-coverable, *k*-connected, and *k*-edge-connected graphs. The main results of this paper are as follows.

**Theorem 2:** Let G be a graph of order  $n \ge k + 6$ , where k is an integer and  $k \ge 1$ . If

$$HZ\left(G^{c}\right) = F\left(G^{c}\right) + 2M_{2}\left(G^{c}\right) \leq (n-1)^{2}\left(n-k-2\right),$$

then G is k-Hamiltonian or

$$G = K_{k+1} \vee \left(K_1 + K_{n-k-2}\right)$$

**Theorem 3:** Let G be a graph of order  $n \ge k + 6$ , where k is an integer and  $k \ge 1$ . If

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/the-hyper-zagreb-index-and-some-properties-ofgraphs/235535

## **Related Content**

#### Use of Eggshell as a Partial Replacement for Sand in Concrete Used in Biomedical Applications

Sebastin S.and Murali Ram Kumar S. M. (2020). *Deep Neural Networks for Multimodal Imaging and Biomedical Applications (pp. 256-264).* 

www.irma-international.org/chapter/use-of-eggshell-as-a-partial-replacement-for-sand-in-concrete-used-in-biomedicalapplications/259498

#### ANN Optimization Experiments for Classification

(2014). *Medical Diagnosis Using Artificial Neural Networks (pp. 200-212).* www.irma-international.org/chapter/ann-optimization-experiments-for-classification/111011

## Formalization and Discrete Modelling of Communication in the Digital Age by Using Graph Theory

Radi Petrov Romansky (2020). Handbook of Research on Advanced Applications of Graph Theory in Modern Society (pp. 320-353).

www.irma-international.org/chapter/formalization-and-discrete-modelling-of-communication-in-the-digital-age-by-usinggraph-theory/235542

## Higher Order Neural Networks with Bayesian Confidence Measure for the Prediction of the EUR/USD Exchange Rate

Adam Knowles, Abir Hussain, Wael El Deredy, Paulo G.J. Lisboaand Christian L. Dunis (2009). *Artificial Higher Order Neural Networks for Economics and Business (pp. 48-59).* www.irma-international.org/chapter/higher-order-neural-networks-bayesian/5276

## Metaheuristics Approaches to Solve the Employee Bus Routing Problem With Clustering-Based Bus Stop Selection

Sinem Büyüksaatç Kiriand Tuncay Özcan (2020). Artificial Intelligence and Machine Learning Applications in Civil, Mechanical, and Industrial Engineering (pp. 217-239).

www.irma-international.org/chapter/metaheuristics-approaches-to-solve-the-employee-bus-routing-problem-withclustering-based-bus-stop-selection/238147