Chapter 9 Sumset Valuations of Graphs and Their Applications

Sudev Naduvath

b https://orcid.org/0000-0001-9692-4053 Christ University, India

Germina K. Augusthy Central University of Kerala, India

Johan Kok

Tshwane Metropolitan Police Department, South Africa

ABSTRACT

Graph labelling is an assignment of labels to the vertices and/or edges of a graph with respect to certain restrictions and in accordance with certain predefined rules. The sumset of two non-empty sets A and B, denoted by A+B, is defined by A+B=\{a=b: a\inA, b\inB\}. Let X be a non-empty subset of the set \Z and $\sP(X)$ be its power set. An \textit{sumset labelling} of a given graph G is an injective set-valued function $f: V(G) \to \sP_0(X)$, which induces a function $f^*: E(G) \to \sP_0(X)$ defined by $f^*(uv)=f(u)+f(v)$, where f(u)+f(v) is the sumset of the set-labels of the vertices u and v. This chapter discusses different types of sumset labeling of graphs and their structural characterizations. The properties and characterizations of certain hypergraphs and signed graphs, which are induced by the sumset-labeling of given graphs, are also done in this chapter.

INTRODUCTION

In graph theory, graph labelling is an assignment of labels to the vertices and/or edges of a graph with respect to certain restrictions and in accordance with certain predefined rules. For the past few decades, graph labelling has become a fruitful research area in graph theory. Different graph labellings have resulted from practical considerations. They are not only of theoretical interests but have many practical implications also. For many applications, the edges or vertices of a given graph are given labels that are meaningful in the context.

DOI: 10.4018/978-1-5225-9380-5.ch009

Graph Labelling

Valuation of a graph G is a one to one mapping of the vertex set of G on to the set of all integers \mathbb{Z} . Graph labeling has become a fertile research area in graph theory after the introduction of the notion of certain types number valuations, called β -valuations, of graphs in Rosa (1967). The most popular one among the number valuations of graphs is β -valuation or graceful labelling of a graph (see Golomb, 1972; Rosa, 1967) which is defined as an injective function

$$f: V(G) \to \left\{1, 2, 3, \dots, \left|E\right|\right\}$$

such that, when each edge xy is assigned the label |f(x) - f(y)|, the resulting edge labels are distinct. A graph G(V, E) is said to be *edge-graceful* if there exists a bijection

 $f: E \to \Big\{1, 2, 3, \dots, \Big|E\Big|\Big\}$

such that the induced mapping

$$f^{+}:V\rightarrow\left\{ 0,1,\cdots,\left|V\right|-1\right\}$$

given by

$$f^+\left(u\right) = f\left(uv\right) \left(\text{mod} \left|V\right| \right)$$

taken over all edges uv is a bijection.

Motivated by various problems in social networks, a set analogue of number valuations called setvaluation of graphs, has been introduced in Acharya (1983). In the number valuations, the elements of a graph are assigned to numbers while in the set-valuations, the elements of a graph are assigned to sets subject to certain conditions. The mathematical definition of a set-valuation of a graph concerned is as given below (see Acharya, 1983):

For a graph G and a non-empty set X, a *set-labeling* or a set-valuation of G, with respect to the set X, is an injective set-valued function

 $f: V(G) \to \mathcal{P}(X)$

such that the function

$$f^{\oplus}: E\left(G\right) \to \mathcal{P}\left(X\right) - \left\{\varnothing\right\}$$

41 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/sumset-valuations-of-graphs-and-their-

applications/235538

Related Content

Neural Network for Big Data Sets

Vo Ngoc Phuand Vo Thi Ngoc Tran (2022). *Research Anthology on Artificial Neural Network Applications* (pp. 41-67).

www.irma-international.org/chapter/neural-network-for-big-data-sets/288950

Ultra High Frequency SINC and Trigonometric Higher Order Neural Networks for Data Classification

Ming Zhang (2016). Applied Artificial Higher Order Neural Networks for Control and Recognition (pp. 113-153).

www.irma-international.org/chapter/ultra-high-frequency-sinc-and-trigonometric-higher-order-neural-networks-for-dataclassification/152100

ML-Based Finger-Vein Biometric Authentication and Hardware Implementation Strategies

Nayan Keshri, Swapnadeep Sarkar, Yash Raj Singh, Sumathi Gokulanathan, Konguvel Elangoand Sivakumar Ponnusamy (2023). *Neuromorphic Computing Systems for Industry 4.0 (pp. 204-225).* www.irma-international.org/chapter/ml-based-finger-vein-biometric-authentication-and-hardware-implementationstrategies/326839

Procedure of Medical Diagnosis

(2014). *Medical Diagnosis Using Artificial Neural Networks (pp. 24-42).* www.irma-international.org/chapter/procedure-of-medical-diagnosis/110997

Digital Mechanisms of Management System Optimization in the Forest Industry

Yulia Vertakova, Saniyat Agamagomedova, Irina Sergeeva, Andrey Tarasov, Svetlana Morkovina, Enric Seedineand Potapova Irina (2020). *Avatar-Based Control, Estimation, Communications, and Development of Neuron Multi-Functional Technology Platforms (pp. 174-198).* www.irma-international.org/chapter/digital-mechanisms-of-management-system-optimization-in-the-forest-

industry/244792