

Chapter 72

A Hybridization of Gravitational Search Algorithm and Particle Swarm Optimization for Odor Source Localization

Upma Jain

ABV-IIITM Gwalior, India

W. Wilfred Godfrey

ABV-IIITM Gwalior, India

Ritu Tiwari

ABV-IIITM Gwalior, India

ABSTRACT

This paper concerns with the problem of odor source localization by a team of mobile robots. The authors propose two methods for odor source localization which are largely inspired from gravitational search algorithm and particle swarm optimization. The intensity of odor across the plume area is assumed to follow the Gaussian distribution. As robots enter in the vicinity of plume area they form groups using K-nearest neighbor algorithm. The problem of local optima is handled through the use of search counter concept. The proposed approaches are tested and validated through simulation.

INTRODUCTION

The ability of a multi-robot system to detect, locate or follow a target either in known or unknown area, has various valuable applications in real life. Applications of target searching include search and rescue after disaster, toxic gas detection, narcotics or explosives localization and so on. For instance, the use of autonomous robots for search task in dangerous environment has been receiving consistent attention. Searching using a team of mobile robots, instead of a single robot has potential advantages (viz. fault

DOI: 10.4018/978-1-7998-1754-3.ch072

tolerance, accuracy) and also has numerous challenges (viz.coordination, communication, collision avoidance). Information of odor is widely used by animals for information exchange, finding mates and searching for food in nature. Advancement in the area of robotics and sensor technology has motivated researchers to use robots for odor source localization in environment harmful for human beings. The process of odor source localization can be divided into three phases: odor plume finding, plume following and odor source declaration.

Nature inspired paradigms have been used consistently in robotics for control, decision making and learning. Simple control rules drawn by the study of social insects and animals have been found suitable for multi-robot systems. We have proposed two approaches for odor source localization. The first approach is inspired from gravitational search algorithm, GSA (Esmail Rashedi et al., 2009) and the second approach uses a hybrid of Gravitational Search Algorithm and Particle Swarm Optimization, PSO (Eberhart & Kennedy, 1995) proposed by Kennedy and Eberhart in 1995.

This paper discusses an approach which minimizes the time required to locate the odor source, by utilizing the strengths of GSA and PSO.

This paper is organized as follows: Section Related work provides a brief review of target searching methods. Section Methodology discusses the proposed target localization approaches. Simulation setup details and results are discussed in section Simulation setup and Simulation results. Section Conclusion concludes the paper with a discussion on possible future work.

RELATED WORK

Target search is the process of localizing an object of interest on the basis of current information available about the environment. This problem has been studied under various scenarios such as static or dynamic target, constant or variable plume intensity, single or multiple targets etc. Depending on the target, a broader spectrum of target locating problems has emerged. For instance, odor source localization (Jatmiko et al. 2011), target localization and tracking (Ramya et al., 2012), search and rescue (Liu & Nejat, 2013) and so on.

Research on locating the odor source using robots began in 1990s (Sandini et al., 1993). Problem of odor source localization has already been studied by many researchers (Russell et al., 2003; Marques et al., 2006; Jatmiko et al., 2011; Marjovi et al., 2011) Several methods have been proposed namely: Hex-path algorithm (Russell, 2003; Lilienthal et al., 2003), Gradient following (Li et al., 2007), the Zigzag path search strategy (Holland & Melhuish, 1996), rule based strategy (Zarzhitsky et al., 2004), Fluxotaxis (Gong et al., 2011), Odor tracking

(Vergassola et al., 2007), Infotaxis (Kuwana & Shimoyama, 1998), combination of Chemotaxis and Anemotaxis (Hayes et al. 2002), cooperation based on swarm intelligence (Hayes et al., 2003), etc.

Li et al. (Li et al. 2007) has proposed a gradient-based method to locate the odor source. In this approach, robots make the use of the concentration-gradient information and apply global stochastic strategy to decide the next move. But the cooperation mechanism employed among robots does not utilize the complete information available from other robots. Marques et al. (Marques et al., 2006) proposed a new PSO inspired cooperative algorithm which is based on the exchange of information among neighboring agents for searching odor sources across large search spaces. The spreading of the agents across the large search space is made possible through modeling and implementation of repulsive forces among the agents and crosswind biased motion. Marques et al. (Marques et al., 2002) proposed a method for odor source

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:
www.igi-global.com/chapter/a-hybridization-of-gravitational-search-algorithm-and-particle-swarm-optimization-for-odor-source-localization/244070

Related Content

A Multi Attribute Selection of Mobile Robot using AHP/M-GRA Technique: A Multi Attribute Selection of Mobile Robot using AHP/M-GRA Technique

Surinder Kumar and Tilak Raj (2020). *Robotic Systems: Concepts, Methodologies, Tools, and Applications* (pp. 262-284).

www.irma-international.org/chapter/a-multi-attribute-selection-of-mobile-robot-using-ahpm-gra-technique/244009

RFID-Based Robotic Process Automation for Smart Museums With an Alert-Driven Approach

Giny Y. L. Chin and Dickson K. W. Chiu (2023). *Application and Adoption of Robotic Process Automation for Smart Cities* (pp. 1-27).

www.irma-international.org/chapter/rfid-based-robotic-process-automation-for-smart-museums-with-an-alert-driven-approach/333085

2D Shape Recognition and Retrieval Using Shape Contour Based on the 8-Neighborhood Patterns Matching Technique

Muzameel Ahmed and Manjunath Aradhya (2019). *International Journal of Synthetic Emotions* (pp. 49-61).

www.irma-international.org/article/2d-shape-recognition-and-retrieval-using-shape-contour-based-on-the-8-neighborhood-patterns-matching-technique/243686

Mobile Target Tracking of Swarm Robotics in Unknown Obstructive Environment

Zhongyang Zheng and Ying Tan (2016). *Handbook of Research on Design, Control, and Modeling of Swarm Robotics* (pp. 397-420).

www.irma-international.org/chapter/mobile-target-tracking-of-swarm-robotics-in-unknown-obstructive-environment/142011

Organ-Based Medical Image Classification Using Support Vector Machine

Monali Y. Khachane (2017). *International Journal of Synthetic Emotions* (pp. 18-30).

www.irma-international.org/article/organ-based-medical-image-classification-using-support-vector-machine/181638