

Chapter 2

Design of Experiments to Optimize Soxhlet–HTP Method to Establish Environmental Diagnostics of Polluted Soil: Optimization of the Soxhlet–HTP Method by DOE


Carlos Mario Morales-Bautista

Universidad Juárez Autónoma de Tabasco, Mexico

Candelario Méndez-Olán


División Académica de Ciencias Básicas, Universidad Juárez Autónoma de Tabasco, Mexico

Sugey López-Martínez

 <https://orcid.org/0000-0002-3681-4001>

División Académica de Ciencias Biológicas, Universidad Juárez Autónoma de Tabasco, Mexico

Marcia E. Ojeda-Morales

 <https://orcid.org/0000-0003-0360-4654>

División Académica de Ingeniería y Arquitectura, Universidad Juárez Autónoma de Tabasco, Mexico

ABSTRACT

One of the great challenges of the environmental diagnoses of soils contaminated with hydrocarbons is the optimization of analytical determinations. For this reason, this chapter evaluates the extraction of hydrocarbons by the Soxhlet method through the design of experiments (DOE), varying three different solvents, three soils, and three extraction times. Soil was experimentally contaminated at different concentrations, and hydrocarbons totals relying on conditions organic matter, electrical conductivity,

DOI: 10.4018/978-1-7998-1518-1.ch002

pH and textures, amount of sample, solvents, and NaSO₄, were studied. The variables were evaluated by means of an analysis of the Taguchi design and a factorial design, with the results the significant and optimal parameters of the process were determined, which were solvent type and time (10 hours and dielectric constant of 9). Also, the model discards the soil properties. These results will save time and resources, and they reduce errors.

INTRODUCTION

During the last decade, Mexico has been involved in some major changes, mainly focused in the public policies, for example, recently the Mexican government enacted a law to reform the constitution, this law consisted on the allowance of private capital investment in the energy sector in order to maximize the use of our natural resources, also to improve the economy of our country. After that, institutions such as the National Hydrocarbons Commission (CNH), and the Safety Energy and Environment Agency (ASEA) were formed. Currently, these organizations regulate the activities of the petroleum industry and determine the mechanisms for evaluating the impacts that they have and will have on our ecological systems (Hernández, Santillan, Sabelkin, and Parra, 2003; Barrientos & Añorve, 2014, Merchand, 2015; Martínez-Lara & Páez Melo, 2017).

Within the regulations that were established by these newly created public agencies it is specified that analyzes and studies performed should be based on scientific studies, an example is the environmental-base-lines made for reopening or development in the hydrocarbons sector, which specify that the proposed analytical methods must be supported by rigorous scientific studies, mainly, if these are not regulated at least they should be validated, this is the reason why some tools such as design experiments (DOE) and experimental mathematical models have a high application and potential, including some that have already been successfully tested (Morales-Bautista, Méndez-Olán, Hernández-Jiménez, and Adams, 2018).

Currently, one of the great challenges of environmental analytical chemistry is the complexity of the behavior of analytes in the different matrices, in the case of soils, there are still few basic studies in tropical areas that have been subject to constant oil spills, many of them, have been restored but some of the areas with agricultural use vocation continue with problems to establish crops and have resulted in negative impacts in the primary sector, leading to legal and social conflicts for many decades, especially in the southeast states (Castro, Acevedo-Berruecos, Urbieta, Iturbe and, Delgado-Rodríguez, 2012; Adams, Álvarez-Ovando, and Castañón, 2015). In these sites, residual hydrocarbons associated with those effects have been identified, some studies mention that there is a different effect between each type of soil, since these can vary from one site to another and, therefore, have different capacity to respond to a similar pollutant (Zamora, Ramos y Arias, 2012; Palma-Cruz, Pérez-Vargas, Casado, Guzmán, and Calva-Calva, 2016).

Different studies have shown that omitting this parameter causes high uncertainties in declared environmental diagnoses, besides recently was found that the type of hydrocarbon can also influence the level of affectation, in general, it was observed that depending on the fraction of hydrocarbon present in the environment is the type of remediation to be used (García-López, Zavala-Cruz, and Palma-López,

18 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/design-of-experiments-to-optimize-soxhlet-http-method-to-establish-environmental-diagnostics-of-polluted-soil/245585

Related Content

Phenanthroimidazole-Based Organic Fluorophores for Organic Light-Emitting Diodes: An Overview

Sivakumar Vaidyanathan and Jairam Tagare (2018). *Emerging Synthesis Techniques for Luminescent Materials* (pp. 305-388).

www.irma-international.org/chapter/phenanthroimidazole-based-organic-fluorophores-for-organic-light-emitting-diodes/204653

K-Shell X-Ray Fluorescence Studies of Some Elements in the Atomic Number Range $26 \leq Z \leq 70$

Punchithaya K. Sripathi and K. M. Balakrishna (2013). *International Journal of Chemoinformatics and Chemical Engineering* (pp. 27-44).

www.irma-international.org/article/shell-ray-fluorescence-studies-some/78486

Supercritical Fluids and Their Applications in Power Generation

Huijuan Chen, Ricardo Vasquez Padilla and Saeb Besarati (2017). *Advanced Applications of Supercritical Fluids in Energy Systems* (pp. 369-402).

www.irma-international.org/chapter/supercritical-fluids-and-their-applications-in-power-generation/180277

Effect of Flow Acceleration and Buoyancy on Thermalhydraulics of sCO₂ in Mini/Micro-Channel

Nitesh Kumar, Dipankar Narayan Basu and Lin Chen (2021). *Handbook of Research on Advancements in Supercritical Fluids Applications for Sustainable Energy Systems* (pp. 161-182).

www.irma-international.org/chapter/effect-of-flow-acceleration-and-buoyancy-on-thermalhydraulics-of-sco2-in-minimicro-channel/259837

Wavy Motion of Viscous Bubbly Liquid in Tubes of Orthotropic Material

Rafael Yusif Amenzadeh, Akperli Reyhan Sayyad and Faig Bakhman Ogli Naghiyev (2012). *International Journal of Chemoinformatics and Chemical Engineering* (pp. 39-47).

www.irma-international.org/article/wavy-motion-viscous-bubbly-liquid/63433