# Chapter 6 FLC Technique in Smart Grid for Demand Side Management

#### **Kitty Tripathi**

Babu Banarsi Das Northern India Institute of Technology, India

#### Sarika Shrivastava

Ashoka Institute of Technology and Management, Varanasi, India

## ABSTRACT

The chapter discusses the general characteristics of smart grid, which combines different state-of-theart technologies intended for operative power distribution when the generation is decentralized. Fault's existence in the power grid is entirely unanticipated. Fuzzy logic is the computational intelligence technique that integrates the knowledge base of experts that is either human or system using the qualitative expression. This technique can successfully be applied for end-user who is a prosumer and aims for low electricity bill as well as provide intelligent decision-making skill in the agents of the multi-agent system. Fuzzy inference system can be efficiently used in such systems due to its capability to deal with imprecision, incomplete data, and its strong knowledge base.

## INTRODUCTION

The power Sector is effectively using the conventional model of electric grid which was designed in the year 1896 based on the design theory of Nichol's Tesla, but due to the exhaustion of global energy source at a distressing rate, there is growing concerns over the intensifying greenhouse emissions which is produced due to the numerous conventional energy sources (U K Madawala, 2008). The established power system feed power from large central generating units through transformers to a high voltage interconnected network. Conventionally every generating unit is powered by thermal, hydropower, or nuclear power and the grid is used to transport the produced power to substantial, vast distances. This power is then passed through a number of distribution transformers and then delivered to the end-user. The distribution system prevailing feeds load and is the wide-ranging but almost passive network and

DOI: 10.4018/978-1-7998-2718-4.ch006

has minute communication and restricted control. There is no real-time monitoring of this load except huge industrial load so there exists little or no interaction amongst load and power system.

By means of its nature, power demand swings vastly; besides often, here exists circumstances when power demand turns out to be far more than what system can really deliver (M Brown, 2011). Every so often, managing an abrupt upsurge in demand turns out to be uncontrollable, and improper management of the demand produces failure. The system can also fail once an essential power line fails or else a big power plant trips down suddenly. The grid operator searches the problem then make efforts to correct it. This method is time-consuming and is dependent on the nature of the fault (Southern California Edision Smart Grid Strategy & Roadmap, 2011).

The Smart Grid is an effective solution for this increasing complexity prevailing nowadays in electricgrid processes. The Smart Grid is administrated by well-designed software systems that aid in making the grid more efficient in resource distribution, permits computerized decision-making, increase consistency, integration of renewable energy sources, then yield dynamic pricing amid the parties involved. The Smart Grid notion has stretched its action area from the industrial area towards home-electric consumers (J. Rventausta, 2010).

Energy Management Systems have turn out to be an authoritative aspect of smart grids (Bharat Menon Radhakrishnan, 2016), due to the massive challenges levied owing to real-time pricing, distributed generation along with the incorporation of erratic renewables. Owing to the uncertainty associated with renewable sources along with prominent fluctuations in the load demand, it is enormously significant to preserve the complete energy balance in such grids.

Relating the Renewable Energy Sources and Systems (RESSs) to utility power grids remains one of the most striving endeavors of Smart Grid (SG) development in many countries (Moaad Aboumalika, 2019). The challenge of assimilating RESSs remains that it is extremely inconstant, irregular as well as variable. Electric power grids should thus engross this inconsistency by means of a range of solutions.

Here are two general methods to the administration of any smart grid. Primarily, it is thinkable to stretch the utility to straight control over every DERs in the structure, that allows several types of optimization at the level of the complete grid. Furthermore, it is likely to give the prosumers that owns the DERs as an opportunity to exchange how individual DERs are used to accomplish grid-level purposes, created on economic encouragements, in this circumstance the prosumer is not certainly essential to disclose all related negotiating information with the utility (A. Masoum, 2014) (B.Qela, 2014).

#### BACKGROUND

From the global outlook, major factors behind smart grid are capacity, effectiveness, consistency, sustainability as well as the customer assignation. The greater capacity electricity grid is required in the utmost every developing country. Next to it, the electric vehicles will correspondingly claim a few changes on the grid within the developed countries. Electricity yield can be augmented by enhancing the effectiveness of the grid system. Next to it, the virtual capacity might also be increased by means of peak shredding practices (Zhuo, Gao, & Li, 2008).

Two key elements when seeing efficiency are losses in the system and how the resources are arranged/ used. Losses frequently are subject to the load shape within the system; for example, moderately loaded trans-formers remain less effective, so it is anticipated that system functions at the adjacent capacity level. Consumption of system is a foremost factor once we are considering outlay in system resources. 13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/flc-technique-in-smart-grid-for-demand-sidemanagement/252598

## **Related Content**

## A Double Actuator-Based DC Attraction Type Levitation System for the Suspension of a Cylindrical Rod

(2023). Studies on Single and Double Actuator Based DC Attraction Type Levitation Systems: Optimization Techniques (pp. 109-128).

www.irma-international.org/chapter/a-double-actuator-based-dc-attraction-type-levitation-system-for-the-suspension-ofa-cylindrical-rod/327146

#### A Wideband Microstrip Patch Antenna for NB-IOT Applications

Balachandra Pattanaik, Muddineni Raveendra, Suresh Babu Thangavel, Ashraf Mohammad, Saam Prasanth Dheeraj Pedapalliand Akhileswari Sirigineedi (2022). *Antenna Design for Narrowband IoT: Design, Analysis, and Applications (pp. 35-42).* 

www.irma-international.org/chapter/a-wideband-microstrip-patch-antenna-for-nb-iot-applications/300187

### Comparative Study of Transmission Line Junction vs. Asynchronously Coupled Junction Diplexers

Eugene A. Ogbodo (2021). Handbook of Research on 5G Networks and Advancements in Computing, Electronics, and Electrical Engineering (pp. 326-336).

www.irma-international.org/chapter/comparative-study-of-transmission-line-junction-vs-asynchronously-coupled-junctiondiplexers/279976

#### Wireless Nanosensor Networks: Prospects and Challenges

Sohail Anwar (2017). Handbook of Research on Nanoelectronic Sensor Modeling and Applications (pp. 505-511).

www.irma-international.org/chapter/wireless-nanosensor-networks/166421

#### Design of Grounding System

(2018). Design Parameters of Electrical Network Grounding Systems (pp. 38-83). www.irma-international.org/chapter/design-of-grounding-system/191883