

Robust Stabilization And Control Of Takagi-Sugeno Fuzzy Systems With Parameter Uncertainties And Disturbances Via State Feedback And Output Feedback

Iqbal Ahammed A.K., Anjuman Institute of Technology and Management, Bhatkal, India
Mohammed Fazle Azeem, King Khalid University, Guraiger, Kingdom of Saudi Arabia

ABSTRACT

Most of the systems in the industry contain extreme non-linearity and uncertainties, which are hard to design and control utilizing general nonlinear systems. To conquer this sort of troubles, different plans have been produced in the most recent two decades, among which a popular methodology is Takagi-Sugeno fuzzy control. In this article, we present robust stabilization and control of Takagi-Sugeno (T-S) fuzzy systems with parameter uncertainties and disturbances. Initially, Takagi and Sugeno (TS) fuzzy model is used to represent a nonlinear system. Based on this T-S fuzzy model, fuzzy controller design schemes for state feedback and output feedback is also developed. Then, necessary conditions are derived for robust stabilization in the intelligence of Lyapunov asymptotic stability and are expressed in the arrangement of linear matrix inequalities (LMIs). The proposed system is implemented in the working platform of MATLAB and the simulation results are provided to illustrate the effectiveness of the proposed methods.

KEYWORDS

Disturbances, Lyapunov Stability theory, Output Feedback, Parameter Uncertainties, State Feedback, TS Fuzzy System

1. INTRODUCTION

In practice, most plants are nonlinear and comprise uncertainties. During the past decades, several people have dedicated a lot of effort to both theoretical research and implementation methods to handle nonlinear control problems. Based on this, various control schemes have been developed, one of the most important of which is fuzzy logic theory. Since then this field has been explored further, both theoretically and practically, among which a popular usage method is fuzzy control (Chen, (2011)). In conventional modeling a single system is modeled to define the entire characteristics of the global non-linear system. A fuzzy controller or model uses fuzzy rules, which are linguistic if-then statements involving fuzzy sets, fuzzy logic, and fuzzy inference (Pereira, Nunes de Almeida et al., 2015). Fuzzy rules play a key role in representing expert control knowledge and experience in linking the input variables of fuzzy controllers to output variable. Two major types of fuzzy rules exist, namely, Mamdani fuzzy rules (Davood & Khooban, 2015) and Takagi-Sugeno (TS) fuzzy rules. The constructions of a fuzzy model represent an important and basic procedure in this approach. In

DOI: 10.4018/IJFSA.2020070104

general, there are two approaches for constructing fuzzy models, fuzzy modeling using input-output data and derivation from given nonlinear system equations (Morente-Molinera, Perez, et al., 2015).

To design a T-S fuzzy controller, we need a T-S fuzzy model for a nonlinear system. TS fuzzy model is widely accepted as a powerful modeling tool for describing complex nonlinear plants, which has been successfully applied into industrial control. T-S fuzzy model define the non-linear system into simple sub-linear modules and define the global characteristics of the nonlinear system. (Tao, Taur et al., 2010). TS fuzzy system since it is a powerful solution that bridges the gap between linear and nonlinear control systems (Qiu, Feng et al., 2010). The important advantage of the T-S fuzzy system is its universal approximation of any smooth nonlinear function by a “blending” of some local linear system models, which greatly facilitates the analysis and synthesis of the complex nonlinear system (Jiang, Gao et al., 2011; Nian and Zheng, 2012). The complex non-linear plant can be described as a weighted sum of linear state equations (Lai, Wu et al., 2015; Xie, Yue et al., 2016). In order to meet control objectives, conceptually, there exist two distinct approaches to design a fuzzy adaptive control system: direct and indirect schemes. In the direct method, a fuzzy system is used to describe the control action and the parameters of the fuzzy system are adjusted directly to meet the control objective (Dong & Wang, 2009).

Unlike the direct schemes, the indirect adaptive approach uses fuzzy systems to estimate the plant dynamics and then a control law is designed based on these estimates. In indirect adaptive schemes, the possible controller singularity problem usually meets (Shi, Zhang et al., 2011). Also, various algorithms and schemes are developed for the fuzzy adaptive control system. An observer-based indirect adaptive fuzzy neural tracking controller combined with a variable structure scheme and H_∞ control algorithms is developed for nonlinear MIMO systems involving plant uncertainties and external disturbances (Hui Zhang, Yang Shi, et al., (2013)) (Li, Liu et al., 2012). The reliable fuzzy H_∞ controller is designed to guarantee the system's asymptotic Stability. To further overcome the fuzzy approximation error and external disturbances, the adaptive fuzzy controllers are enlarged with a robust compensator, namely a sliding mode controller (SLM), robust adaptive controller or with an H_∞ tracking controller (Nekoukar & Erfanian, 2011).

The rolling cart system with multiple time delayed state uncertainties and external disturbances can be analyzed using the observer-based adaptive tracking control scheme with fuzzy systems and variable structure technique (Yuan, Tan et al., 2014). In the observer design procedure, two prominent advantages are that it does not require the sign of the control gain coefficient to be known and only two parameters need to be adjusted on-line for each subsystem (Liu, Tong et al., 2011). So, the method uses fuzzy differential equations based on the reproducing kernel theory under strongly generalized differentiability. The analytic and approximate solutions are given with series form in terms of their parametric form in the space for the control system (Arqub, Mohammed, et al., 2016; Arqub, Abu et al., 2017; Arqub & Omar, 2017).

In stability analysis of fuzzy control systems, the stabilisation of T-S model using an output feedback controller for both measurable and estimated decision variables cases are considered. In the case of measurable decision variables a T-S observer and T-S controller are designed separately to stabilise globally exponentially the closed loop T-S mode (Chadli, Mohammed et al., 2002) but the main approaches have been based on a single Lyapunov function (Yeh, Chen et al., 2012). These methods basically reduce to the problem of finding a common Lyapunov function for a set of stability conditions (Tong, Li et al., 2013). By using Lyapunov analysis method, it is proven that all the signals in the closed-loop system are guaranteed to be bounded and the system outputs track the reference signals to a bounded compact set (Li, Tong et al., 2010). Since a common Lyapunov function is used for all subsystems, they can be quite conservative in some situations (Zhang, Jiang et al., 2010). Parallel distributed compensation (PDC) control is one of the fuzzy controls that shares the same fuzzy rules and sets as the T-S system. This PDC control-based T-S fuzzy system based on a common Lyapunov function, which often leads to very conservative results. Thus, many investigations have been devoted to less conservative stabilization conditions and many other classes of Lyapunov functions

35 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/article/robust-stabilization-and-control-of-takagi-sugeno-fuzzy-systems-with-parameter-uncertainties-and-disturbances-via-state-feedback-and-output-feedback/253085

Related Content

Introduction to Cloud Computing and Healthcare 5.0: Transforming the Future of Healthcare

Dankan Gowda V., Shashikala S. V., Manu Y. M., Mandeep Kaur and Sudhanshu Kumar Jha (2024). *Federated Learning and AI for Healthcare 5.0* (pp. 26-45).

www.irma-international.org/chapter/introduction-to-cloud-computing-and-healthcare-50/335382

Rethinking "Oil Nationalism": The Case of Anglo Iranian Oil Company (AIOC)

Neveen Abdelrehim (2015). *International Journal of Signs and Semiotic Systems* (pp. 33-49).

www.irma-international.org/article/rethinking-oil-nationalism/142499

A Robot Model of Dynamic Appraisal and Response

Carlos Herrera, Tom Ziemke and Thomas M. McGinnity (2009). *Encyclopedia of Artificial Intelligence* (pp. 1376-1382).

www.irma-international.org/chapter/robot-model-dynamic-appraisal-response/10419

Machine Learning Based Intrusion Detection System for Denial of Service Attack

Ashish Pandey and Neelendra Badal (2021). *Computational Methodologies for Electrical and Electronics Engineers* (pp. 29-47).

www.irma-international.org/chapter/machine-learning-based-intrusion-detection-system-for-denial-of-service-attack/273833

Application of Fuzzy C-Means Clustering and Semantic Ontology in Web Query Session Mining for Intelligent Information Retrieval

Suruchi Chawla (2021). *International Journal of Fuzzy System Applications* (pp. 1-19).

www.irma-international.org/article/application-of-fuzzy-c-means-clustering-and-semantic-ontology-in-web-query-session-mining-for-intelligent-information-retrieval/274883