



# Effect of Nanoparticle and Inclination Angle at Thermal Efficiency in Heatpipes

**Sina Razvarz**

 <https://orcid.org/0000-0003-1549-7307>

*Department of Automatic Control, Centre for Research and Advanced Studies of the National Polytechnic Institute (CINVESTAV-IPN), Mexico City, Mexico*

**Raheleh Jafari**

 <https://orcid.org/0000-0001-7298-2363>

*School of Design, University of Leeds, Leeds, UK*

**Cristóbal Vargas Jarillo**

*Department of Automatic Control, Centre for Research and Advanced Studies of the National Polytechnic Institute (CINVESTAV-IPN), Mexico City, Mexico*

**Alexander Gegov**

 <https://orcid.org/0000-0002-6166-296X>

*School of Computing, University of Portsmouth, UK*

## INTRODUCTION

Recently, the proficiency of the engineering applications have become more notable. Continuous advancement have become essential in order to maintain the technology itself. Technology has improved significantly by accepting novel opinions and approaches for effective application, storage as well as transmission of energy. Nanotechnology is one of the most noteworthy fields which fascinates the researchers because of its superior capability, enabling a considerable advancement in the efficiency of several devices. Over the past few decades remarkable investigations have been carried out in order to implement nanotechnology in heat transfer usages. Nanofluids can be considered as a novel improvement in thermo-fluidics, acquired by stirring nano particles in conventional fluids (Choi, 1998). Investigators are taken nanoparticles of various metals, metal oxides, carbides, nitrides, as well as various kinds of carbon with several base fluids to be mentioned as water, ethylene glycol (EG) as well as engine oils.

Industrial engineering is one of the fields that artificial neural network, fuzzy logic, and nano technology have found an extensive implementation area (Razvarz et al., 2017; Jafari & Yu, 2018 ; Jafari & Razvarz, 2017, 2018, Jafari et al., 2016, 2018a, 2018b, 2019a, 2019b; Jafarian et al., 2012). Nanoscale refers size dimensions between approximately 1 and 100 nm (or more appropriately, 0.2 and 100 nm) because at this scale the properties of materials differ with respect to their physical properties from a larger scale.

The size dimensions of Nanoscale are among nearly 1 and 100 nm (or more suitably, 0.2 and 100 nm), since at this scale the attributes of materials change concerning their physical attributes from a greater scale. Every material which contains one or more dimensions in the nanoscale is stated as nanomaterial (Sekhon, 2014). Nanoparticles contain distinct biological attributes such as tiny size, a great surface-area-to-volume.

DOI: 10.4018/978-1-7998-3479-3.ch087

Nanofluids have been constructed by utilizing two techniques: one step technique and two step technique (Eastaman et al., 2001). The principal aim of these techniques is to provide a homogeneous as well as stable solid-liquid mixture, also avoiding the agglomeration, feasible erosion and clogging etc. In one step technique, the nanoparticles have been constructed and dispersed into the foundation fluid at the same time. Whereas in a two step technique, the nanoparticle has been generated in the first step and dispersed into host fluids in the second step. Investigation reveals that nanofluids with oxide nanoparticles and carbon nanotubes can be produced utilizing two step technique. Two step technique is not appropriate for metallic nanoparticles. Under particular circumstances, nanofluids represent excellent thermo physical features that result in better effect of the thermal usage (Singh & Raykar, 2008).

Currently, so many investigators have suggested mechanisms of increment in heat transfer via nanofluid as the affect of Interface, Brownian motion, Ballistic conveyor of energy carriers as well as thermophoresis. The first attempt in adding nano materials or particles in the liquid was reported by Choi in (Choi et al., 1999; Choi, 1995; Pinto & Fiorelli, 2019) which was named nanofluid in 1995. It is a novel class of heat transfer as well as cooling working fluid. In (Kebllinski et al., 2005) the authors analyzed the consequence of adding nanoparticles to liquid which improved defects of past that the adding of millimeter as well as micro meter scale particles may lead to the sedimentation and pipe block. The heat transfer specifications of nanofluid are discussed in (Lin et al., 2008). The mechanisms that are responsible for the increment in thermal conductivity of nanofluids are investigated in (Chandrasekar et al., 2010; Ren, 2019). Furthermore, several mathematical models for identifying various factors as well as their limitations have been investigated in recent years. In (Murshed et al., 2005; Wang et al., 2017) the authors have been proposed that the nanoparticles shape, size as well as volume fraction are the principal parameters for deciding the thermal conduction of nanofluids. The applications as well as the challenges of nanofluids have been studied in (Saidur et al., 2011).

Heat pipe is considered as a device utilized in conduction the heat from one place to another. They are passive systems which convey heat from a heat origin (evaporator) to a heat sink (condenser) over lengthy intervals through the hidden heat of vaporization of a working fluid. The heat pipe can be theoretically classified into three parts, the evaporator, the adiabatic section, as well as the condenser. A bare heat pipe structure is demonstrated in Figure 1. In procedure, the working fluid attracts the heat from the heat source, then evaporates in the evaporator. The warm vapor straightly runs via the adiabatic part, and then condenses in the condenser. The condensed working fluid in the condenser runs back through capillary construction on the internal wall in the adiabatic part and then attains the evaporator once more. The idea of the heat pipe was initially represented in (Gaugler, 1944; Trefethen; 1962; Rakesh & Bumatraria, 2019), however, was not extensively published up to an independent growth by (Grover et al., 1964) at the Los Alamos Scientific Laboratories. Thermosyphon heat pipe is an empty, closed, and evacuated pipe which contains a working fluid. It is partitioned into three parts: evaporator, adiabatic, and the condenser part. The working fluid attracts the heat in evaporator part, and then gets transformed into the vapor phase that moves to the condenser part because of the pressure variance, declines heat to the cooling media via the condenser part and consequently gets transformed into the liquid phase.

## **BACKGROUND**

The main constituents of a heat pipe are a sealed container, a wick construction, as well as a working fluid. All these components are working simultaneously in order to convey the heat more effectively and evenly. The wick construction is positioned on the internal area of the heat pipe wall, also is saturated

16 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/effect-of-nanoparticle-and-inclination-angle-at-thermal-efficiency-in-heatpipes/260265](http://www.igi-global.com/chapter/effect-of-nanoparticle-and-inclination-angle-at-thermal-efficiency-in-heatpipes/260265)

## Related Content

---

### Optimization of Cyber Defense Exercises Using Balanced Software Development Methodology

Radek Ošlejšekand Tomáš Pitner (2021). *International Journal of Information Technologies and Systems Approach* (pp. 136-155).

[www.irma-international.org/article/optimization-of-cyber-defense-exercises-using-balanced-software-development-methodology/272763](http://www.irma-international.org/article/optimization-of-cyber-defense-exercises-using-balanced-software-development-methodology/272763)

### Financial Risk Intelligent Early Warning System of a Municipal Company Based on Genetic Tabu Algorithm and Big Data Analysis

Hui Liu (2022). *International Journal of Information Technologies and Systems Approach* (pp. 1-14).

[www.irma-international.org/article/financial-risk-intelligent-early-warning-system-of-a-municipal-company-based-on-genetic-tabu-algorithm-and-big-data-analysis/307027](http://www.irma-international.org/article/financial-risk-intelligent-early-warning-system-of-a-municipal-company-based-on-genetic-tabu-algorithm-and-big-data-analysis/307027)

### Causal Mapping: An Historical Overview

V. K. Narayanan (2005). *Causal Mapping for Research in Information Technology* (pp. 1-19).

[www.irma-international.org/chapter/causal-mapping-historical-overview/6512](http://www.irma-international.org/chapter/causal-mapping-historical-overview/6512)

### Mobile Sink with Mobile Agents: Effective Mobility Scheme for Wireless Sensor Network

Rachana Borawake-Sataoand Rajesh Shardanand Prasad (2017). *International Journal of Rough Sets and Data Analysis* (pp. 24-35).

[www.irma-international.org/article/mobile-sink-with-mobile-agents/178160](http://www.irma-international.org/article/mobile-sink-with-mobile-agents/178160)

### Neural Networks and Their Accelerated Evolution From an Economic Analysis Perspective

Stelian Stancu, Constana-Nicoleta Bodea, Oana Mdlna Popescu(Predescu)and Alina Neamu(Idorai) (2018). *Encyclopedia of Information Science and Technology, Fourth Edition* (pp. 6579-6594).

[www.irma-international.org/chapter/neural-networks-and-their-accelerated-evolution-from-an-economic-analysis-perspective/184353](http://www.irma-international.org/chapter/neural-networks-and-their-accelerated-evolution-from-an-economic-analysis-perspective/184353)