



## Chapter 2

# Principles and Applications of Thermal Spray Coatings

**John Henao**

 <https://orcid.org/0000-0002-8954-6039>  
CONACYT-CIATEQ A.C., Mexico

**Astrid L. Giraldo-Betancur**

 <https://orcid.org/0000-0002-5056-7270>  
CONACYT-CINVESTAV, Mexico


**Carlos A. Poblano-Salas**

CIATEQ A.C., Mexico

**Jorge Corona-Castuera**

CIATEQ A.C., Mexico

**Fabio Vargas**

 <https://orcid.org/0000-0003-4484-3950>  
University of Antioquia, Colombia

**Oscar Sotelo-Mazón**

Universidad Autónoma del Estado de Morelos  
(UAEM), Mexico

### ABSTRACT

*The goal of the chapter is to address the fundamental theory of thermal spraying and its modern industrial applications, in particular, those involving flame spray, HVOF, plasma spray, and cold spray processes. During the last 30 years, thousands of manuscripts and various book chapters have been published in the field of thermal spray, displaying the evolution of thermally sprayed coatings in many industrial applications. Thermal spray coatings are currently interesting for different modern applications including prosthesis, thermal barriers, electrochemical catalysis, electrochemical energy conversion devices, biofouling, and self-repairing surfaces. The chapter will explain the fundamental principles of the aforementioned thermal spraying processes and discuss the effect of different controlling parameters on the final properties of the produced coatings. This chapter will also explore current and future industrial applications of thermal spray coatings.*

### LIST OF COMMON ABBREVIATIONS

APS: Atmospheric Plasma Spray

ASI: Adiabatic Shear Instabilities

CAPS: Controlled Atmosphere Plasma Spray

DOI: 10.4018/978-1-7998-4870-7.ch002

CGS: Cold Gas Spray  
dB: Decibels (dBA is noise power measured in dB)  
DC: Direct Current  
D-Gun: Detonation Spray  
HPCS: High Pressure Cold Gas Spray  
HV: Hardness Vickers  
HVOF: High Velocity Air Fuel  
HVOLF: High Velocity Oxygen Liquid Fuel  
HVOF: High Velocity Oxygen Fuel  
HRC: Hardness Rockwell C  
HVSFS: High Velocity Suspension Flame Spray  
LPCS: Low Pressure Cold Gas Spray  
LPPS: Low Pressure Plasma Spray  
PS-PVD: Plasma Spray Physical Vapor Deposition  
SPS: Shrouded Plasma Spray  
TS: Thermal Spray  
TWA: Twin Wire Arc  
VPS: Vacuum Plasma Spray

## **INTRODUCTION TO THERMAL SPRAY**

### **General Background**

Surface modification of materials is a topic that has been intensively studied for the last hundred years to improve, transform, or provide specific functions to a surface originally designed to perform a definite task. Different methods have been employed to modify the surface of materials; for instance, the deleterious effects of corrosion on steels are controlled by applying a layer of a reactive and low melting point metal such as Zn (Marder et al., 2000). A similar protective effect is produced on the surface of iron-based materials when a polymer is deposited on their surface (Ates et al., 2016); however, the pursued application and the specific surface requirements dictate the procedure and more suitable materials for protecting or modifying the surface. Large numbers of materials and processes have been developed for providing surface modification to different substrate materials, from polymers, metals, and ceramics, to electronics, composites, biomaterials, and a myriad of possible combinations in the middle. Thermal spraying (TS) occupies a very specific niche among the technologies developed for providing specific surface features to metallic, ceramic, and composite materials. TS encompasses a group of coating technologies employed for applying metallic and nonmetallic materials on different types of substrates in order to provide them with specific features such as elevated corrosion resistance, biocompatibility, lubrication, high abrasion resistance, electrical and thermal insulation, etc. (Knight et al., 1998). Raw materials employed in such technologies can be in the form of powders, wire, or rods, depending on the selected TS process. All TS processes encompass thermal and kinetic contributions to the overall energy balance between the energy source and the sprayed material (Pawlowski, 2008). Depending on the TS process configuration, thermal and kinetic contributions to that energy balance can be modified; for instance, in high energy processes such as plasma, raw materials receive a larger amount of thermal

38 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

[www.igi-global.com/chapter/principles-and-applications-of-thermal-spray-coatings/262345](http://www.igi-global.com/chapter/principles-and-applications-of-thermal-spray-coatings/262345)

## Related Content

---

### Green Propellants

Gilson da Silva (2018). *Energetic Materials Research, Applications, and New Technologies* (pp. 170-184).  
[www.irma-international.org/chapter/green-propellants/195304](http://www.irma-international.org/chapter/green-propellants/195304)

### Cultural Heritage Career Paths for Materials Scientists and Corrosion Engineers

Stavroula Golfomitou, Myrto Georgakopoulou and Thilo Rehren (2017). *Materials Science and Engineering: Concepts, Methodologies, Tools, and Applications* (pp. 1558-1577).  
[www.irma-international.org/chapter/cultural-heritage-career-paths-for-materials-scientists-and-corrosion-engineers/175752](http://www.irma-international.org/chapter/cultural-heritage-career-paths-for-materials-scientists-and-corrosion-engineers/175752)

### Simulation and Validation of Forming, Milling, Welding and Heat Treatment of an Alloy 718 Component

Joachim Steffenburg-Nordenström and Lars-Erik Svensson (2017). *International Journal of Materials Forming and Machining Processes* (pp. 15-28).  
[www.irma-international.org/article/simulation-and-validation-of-forming-milling-welding-and-heat-treatment-of-an-alloy-718-component/189060](http://www.irma-international.org/article/simulation-and-validation-of-forming-milling-welding-and-heat-treatment-of-an-alloy-718-component/189060)

### Determination of Effective Shear Modulus of Graphite/Epoxy Mixture by an Inverse Method

K. Acharyya, Arun Chattopadhyay and U. S. Dixit (2014). *International Journal of Materials Forming and Machining Processes* (pp. 1-13).  
[www.irma-international.org/article/determination-of-effective-shear-modulus-of-graphiteepoxy-mixture-by-an-inverse-method/106956](http://www.irma-international.org/article/determination-of-effective-shear-modulus-of-graphiteepoxy-mixture-by-an-inverse-method/106956)

### Integration of Legal Aspects in 3D Cadastral Systems

Mohamed Sobaih Aly El-Mekawy, Jesper M. Paasch and Jenny Paulsson (2017). *3D Printing: Breakthroughs in Research and Practice* (pp. 119-144).  
[www.irma-international.org/chapter/integration-of-legal-aspects-in-3d-cadastral-systems/168216](http://www.irma-international.org/chapter/integration-of-legal-aspects-in-3d-cadastral-systems/168216)