Chapter 8 Taxonomy of Computer Network Congestion Control/ Avoidance Methods

Mirza Waseem Hussain Baba Ghulam Shah Badshah University, India

Sanjay Jamwal Baba Ghulam Shah Badshah University, India

Tabasum MirzaBaba Ghulam Shah Badshah University, India

Malik Mubasher Hassan Baba Ghulam Shah Badshah University, India

ABSTRACT

The communication platform in the computing field is increasing at a rapid pace. Technology is constantly budding with the materialization of new technological devices, specifically in the communication industry. The internet is expanding exponentially. Internet-enabled devices are becoming part and parcel of our daily lives. It has turned out to be almost impossible to think about the world without the internet. The internet structures might be reinforced to meet coming prerequisites in mobile communication. Congestion plays a vital role in regulating the flow of data to accelerate the exchange of data in between the wired and wireless devices. In this chapter, the authors try to highlight various network congestion techniques with their limitations proposed from time to time by various researchers. This chapter plays a vital role in highlighting the history of networking congestion detection/ avoidance techniques starting from the early days of networking.

DOI: 10.4018/978-1-5225-9493-2.ch008

Copyright © 2021, IGI Global. Copying or distributing in print or electronic forms without written permission of IGI Global is prohibited.

1. INTRODUCTION to network congestion

Congestion can be defined as the state of the network where total demand for resources is more than availability of the resource. Mathematically it can be defined as: If \sum Total demand > \sum Total available resources, then it is in the state of congestion. In other words, the congestion can be defined as the situation where the total number of packets are more than it can accumulate thus resulting in deterioration of performance. Usually congestion occurs when availability of resources is insufficient to meet the demand of the network. Often increasing the number of resources i.e. larger buffers, reducing processing time, using high speed links does not alienate the problem of congestion (C.-Q. Yang & Reddy, 1995). Although there is no universal accepted definition for network congestion nevertheless one of commonly used definition not in technical perspective but in users perspective is defined as: "A network is said to be congested from the perspective of a user if the service quality noticed by the user decreases because of an increase in network load" (Keshav, 1991).

1.1 Reasons for Network Congestion

Congestion in the network can be caused due to various reasons, which are defined as under:

1.1.1 Inadequate Memory to Store Incoming Packets

Sometime, all of the sudden a large chunk of data arrives simultaneously from several input sources and this data needs to be forwarded through a common output link, then a long queue of packets will be created at the output link. If the size of the queue is small, the packets will be dropped. Adding more buffers also may not help even. If the router has infinite memory the situation may even get worse, for example if there is a long queue of packets, the packets a tail end will take some time to reached the head of queue to be processed but in the meantime, time out for majority packets occurs resulting in useless processing and duplication of packets (Raj Jain, n.d.). Thus, increasing the load needlessly and making the situation worse. It was Nagel who proved that a network with infinite buffer is also susceptible to congestion as a network with normal buffer (Nagle, 1987). The size of the buffer should not be too large as it will create more delay and waste processing time as in Figure 1(a), nor should it be too small resulting in packet loss as shown in Figure 1(b).

33 more pages are available in the full version of this document, which may be purchased using the "Add to Cart"

button on the publisher's webpage: www.igi-

global.com/chapter/taxonomy-of-computer-network-

congestion-controlavoidance-methods/262552

Related Content

Fuzzy Logic Modelling of Nonlinear Metamaterials

N. Yogeesh (2023). *Metamaterial Technology and Intelligent Metasurfaces for Wireless Communication Systems (pp. 230-269).* www.irma-international.org/chapter/fuzzy-logic-modelling-of-nonlinear-metamaterials/328950

The Design and Modeling of 2.4 GHz and 3.5 GHz MMIC LNA

Ching Wen Yip (2012). Advances in Monolithic Microwave Integrated Circuits for Wireless Systems: Modeling and Design Technologies (pp. 157-184). www.irma-international.org/chapter/design-modeling-ghz-ghz-mmic/58491

Detection of PUE Attack in CRN with Reduced Error in Location Estimation Using Novel Bat Algorithm

Aasia Rehmanand Deo Prakash (2017). International Journal of Wireless Networks and Broadband Technologies (pp. 1-25).

www.irma-international.org/article/detection-of-pue-attack-in-crn-with-reduced-error-in-locationestimation-using-novel-bat-algorithm/201494

5G IoT Industry Verticals and Network Requirements

Massimo Condoluci, Maria A. Lema, Toktam Mahmoodiand Mischa Dohler (2021). Research Anthology on Developing and Optimizing 5G Networks and the Impact on Society (pp. 928-949).

www.irma-international.org/chapter/5g-iot-industry-verticals-and-network-requirements/270224

A Binary Search Algorithm to Determine the Minimum Transmission Range for Minimum Connected Dominating Set of a Threshold Size in Ad Hoc Networks

Natarajan Meghanathan (2020). International Journal of Wireless Networks and Broadband Technologies (pp. 1-16).

www.irma-international.org/article/a-binary-search-algorithm-to-determine-the-minimumtransmission-range-for-minimum-connected-dominating-set-of-a-threshold-size-in-ad-hocnetworks/257776