Chapter 1 Fundamental Categories of Artificial Neural Networks

Arunaben Prahladbhai Gurjar

Ganpat University, India

Shitalben Bhagubhai Patel

Ganpat University, India

ABSTRACT

The new era of the world uses artificial intelligence (AI) and machine learning. The combination of AI and machine learning is called artificial neural network (ANN). Artificial neural network can be used as hardware or software-based components. Different topology and learning algorithms are used in artificial neural networks. Artificial neural network works similarly to the functionality of the human nervous system. ANN is working as a nonlinear computing model based on activities performed by human brain such as classification, prediction, decision making, visualization just by considering previous experience. ANN is used to solve complex, hard-to-manage problems by accruing knowledge about the environment. There are different types of artificial neural networks available in machine learning. All types of artificial neural networks work based of mathematical operation and require a set of parameters to get results. This chapter gives overview on the various types of neural networks like feed forward, recurrent, feedback, classification-predication.

CONVOLUTIONAL NEURAL NETWORKS

A CNN architecture consists of different ConvNet stages. For each degree winding of the following comparison module / Sub sampling order module. While the traditional clustering ConvNet modules conceal the average or most of the groups, this grouping uses LP. Ordinance and that, unless it is to become a parameter, as opposed to subtractive. Subtractive is not division, that is, on the average of the value of each of its immediate surroundings; own extended withdrawn(Lawrence,1997). Finally, as is known, also multi-stage the functions that are used in place of the same rank.

DOI: 10.4018/978-1-6684-2408-7.ch001

One-dimensional convolution is an operation between a vector of weight m 2 Rm and vector entries seen as a series of s 2 Rs. The carrier m is the convolution filter. In particular, we think of it as an insertion phrase and yes 2 R is a unique function value associated with the i^{th} word of the phrase. The idea behind the one-dimensional convolution is to take the point product of the vector m with every m-gram in the sentence s another series c:

$$c_j = m | s_j - m + 1; j \tag{1}$$

Equation 1 gives rise to two types of convolutions according to the scope of the J. Lo strait index the type of convolution requires that s³ give me a series c 2 Rs-m + 1 with j going from m one s. The broad type of convolution does not have this requirements for s or m and give a series of c 2 Rs + m-1 where the index j varies from 1 to s +m - 1. Enter out of range values where i <1 where i> s are considered zero. The result of the narrow convolution is a partial sequence of the result of wide convolution (Cireşan,2011). Two types of one dimensional convolution are illustrated in Fig. 1.

Figure 1. Narrow and wide types of CNN m=5



Figure 2. A classic convolutional network

			3	3	2	1	0
3.0	3.0	3.0	0	0	1	3	1
3.0	3.0	3.0	3	1	2	2	3
3.0	2.0	3.0	2	0	0	2	2
			2	0	0	0	1

Why ConvNets Over Feed-Forward Neural Nets?

An image is just a matrix of values in pixels, isn't it? So why not paste the image (for example a description of 3x3 images into a 9x1 vector) and send it to a multi-part Perceptron for processing?

In the case of high quality imagery(Kalchbrenner,2014), the method may show sufficient scale during class imaging, but is low or poorly organized for complex images with pixel dependencies.

ConvNet is able to efficiently capture spatial and model dependencies in the image through the use of appropriate filters. The architecture is more efficient for the data structure due to the reduced number of parameters involved and the overload of the load. In other words, the network can be formed to better understand image stability.

28 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-global.com/chapter/fundamental-categories-of-artificial-neuralnetworks/288948

Related Content

Artificial Neural Network for Solving the Inventory Control Problem in Fuzzy Environments

Mostafijur Rahaman, Sankar Prasad Mondaland Shariful Alam (2021). Artificial Neural Network Applications in Business and Engineering (pp. 126-143).

www.irma-international.org/chapter/artificial-neural-network-for-solving-the-inventory-control-problem-in-fuzzyenvironments/269584

Modeling and Simulation of Alternative Energy Generation Processes using HONN

Salvador Carlos Hernández, Edgar Nelson Sanchez Camperos, Rocío Carrasco Navarro, Joel Kelly Gurubel Tunand José Andrés Bueno García (2013). *Artificial Higher Order Neural Networks for Modeling and Simulation (pp. 162-192).*

www.irma-international.org/chapter/modeling-simulation-alternative-energy-generation/71799

Disease Classification Using ECG Signals Based on R-Peak Analysis With ABC and ANN

Suman Lataand Rakesh Kumar (2022). *Research Anthology on Artificial Neural Network Applications (pp. 933-954).*

www.irma-international.org/chapter/disease-classification-using-ecg-signals-based-on-r-peak-analysis-with-abc-andann/288993

Artificial Higher Order Pipeline Recurrent Neural Networks for Financial Time Series Prediction

Panos Liatsis, Abir Hussainand Efstathios Milonidis (2009). Artificial Higher Order Neural Networks for Economics and Business (pp. 164-189).

www.irma-international.org/chapter/artificial-higher-order-pipeline-recurrent/5282

Use of Eggshell as a Partial Replacement for Sand in Concrete Used in Biomedical Applications

Sebastin S.and Murali Ram Kumar S. M. (2020). *Deep Neural Networks for Multimodal Imaging and Biomedical Applications (pp. 256-264).*

www.irma-international.org/chapter/use-of-eggshell-as-a-partial-replacement-for-sand-in-concrete-used-in-biomedicalapplications/259498