


Chapter 18

Evaluation of a Suitable Material for Soft Actuator Through Experiments and FE Simulations

Elango Natarajan

 <https://orcid.org/0000-0003-1215-0789>
UCSI University, Kuala Lumpur, Malaysia

Muhammad Rusydi Muhammad Razif

Universiti Tun Hussein Onn Malaysia, Parit Raja, Malaysia

AAM Faudzi

Universiti Teknologi Malaysia, Johor Bahru, Malaysia

Palanikumar K.

Sri Sai Ram Institute of Technology, Chennai, India

ABSTRACT

Soft actuators are generally built to achieve extension, contraction, curling, or bending motions needed for robotic or medical applications. It is prepared with a cylindrical tube, braided with fibers that restrict the radial motion and produce the extension, contraction, or bending. The actuation is achieved through the input of compressed air with a different pressure. The stiffness of the materials controls the magnitude of the actuation. In the present study, Silastic-P1 silicone RTV and multi-wall carbon nanotubes (MWCNT) with reinforced silicone are considered for the evaluation. The dumbbell samples are prepared from both materials as per ASTM D412-06a (ISO 37) standard and their corresponding tensile strength, elongation at break, and tensile modulus are measured. The Ogden nonlinear material constants of respective materials are estimated and used further in the finite element analysis of extension, contraction, and bending soft actuators. It is observed that silicone RTV is better in high strain and fast response, whereas, silicone/MWCNT is better at achieving high actuation.

DOI: 10.4018/978-1-6684-3694-3.ch018

INTRODUCTION

The traditional robots exist in the industries are made of metallic parts, motors and fluidic actuators. In contrast, the soft robot uses compliant materials that well suit it for handling soft or fragile materials or unshaped objects. The robot that uses soft material for gripper design is ultimately called as soft robot. It could be applied in medical or industrial applications in order to handle fragile objects like organs, fabrics, papers, vegetables, meat, eggs, etc. The soft actuators are pneumatic actuators that made of polymeric materials. They have been prepared as a key component in soft mechanism in order to directly contact or manipulate the object. Many different kinds of soft actuators have been investigated in the past. The McKibben actuator is the earliest developed pneumatic actuator which used compressed air to expand the rubber tube in the radial directions. It deformed in longitudinal direction when the radial movement of the rubber tube was restricted by knitted fibers H.F. Schulte (1961). The knit angle was the key factor to obtain the extension or contraction motion of the actuator. The rotary type fiber reinforced bending actuator was developed by Noritsugu et al. (2003). Saga (2007) attempted to drive a robot hand with tendon drive with a silicone rubber pneumatic balloon soft actuator. Suzumori et al. (1991) developed a flexible micro actuator that used three fiber-reinforced silicone chambers to achieve bending motion by controlling pressure applied to each cylinder. In most of the actuators Suzumori et al. (1991), Ching-Ping Chou and Hannaford (1996), Smagt et al. (1996), Kawashima (2004) Vanderborght et al. (2006), Hosoda et al. (2008), Wakimoto et al. (2005), Sasaki et al. (2005), Suzumori et al. (2007) in the past, the reinforcement of the rubber tube was used for getting anisotropic elasticity. Suzumori et al. (1994) also attempted to utilize the shape anisotropy instead of fiber reinforcement. He used spoke-shaped rubber components in chambers to restrict the radial motion of the core tube. Ikeuchi et al. (2008) developed a hydraulically operated bellow shaped micro catheter. Wakimoto et al. (2011) developed a rubber actuator using room temperature vulcanized (RTV) silicone rubber for bidirectional curling motion with one air cylinder. Iwata et al. (2011) proved that fiber knitting angle of 23.5° and 66.5° are the best to achieve contraction and extension motions respectively. Ili et al. (2013; 2014) conducted finite element (FE) analysis of three-chamber nylon reinforced soft bending actuator for finger flexion. Agarwal et al. (2016) Ecoflex 00–30, a platinum-catalyzed silicone to prepare the actuator core tube and polyethylene terephthalate (PET) to constraint its motion in the radial direction. They further studied the performance of the actuator through simulations and experiments. Razif et al. (2014) and M. Razif et al. (2014) conducted experiments and simulations on two chambers soft actuator realizing biologically inspired fin for robotic fish. Natividad et al. (2018) developed the pneumatic actuator with fabric inflation modules that are attached to a common flexible but non-inflating plastic spine. They evaluated the static and dynamic performance of their different designs. Ning et al. (2017) developed a single degree of freedom inchworm robot with low cost silicone material and controlled its locomotion by friction hysteresis.

Figure 1 shows components of a bending actuator developed with Silastic-P1 silicone room temperature vulcanization (RTV) rubber. All the above soft actuators attempted in the past used silicone of different grades or silicone RTV to build inner rubber tube of the actuator.

The tensile strength of silicone is generally in the range of 5-10 MPa. The linear actuation of the actuator depends on a few parameters; stiffness and tensile strength of the rubber chamber, fiber knitting angle and tensile strength of the fiber, the shape and the thickness of the actuator. The core tube must exhibit high flexibility and good mechanical strength as well in order to have high performance. On accounting these, Silastic-P1 silicone RTV rubber and multiwall carbon nanotubes (MWCNT) reinforced silicone were considered in this research for the design of inner core rubber chamber. The reason for

13 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/evaluation-of-a-suitable-material-for-soft-actuator-through-experiments-and-fe-simulations/291642

Related Content

Meaning of New Means: Exploring the Economic Impact of Mobile Banking on Rural Bangladesh

Shudipta Sharma, Salauddin Ahmed and Md. Monjur Hossain (2022). *International Journal of Innovation in the Digital Economy* (pp. 1-18).

www.irma-international.org/article/meaning-of-new-means/303617

The Impact of Digital and Organizational Innovation on the Performance of Local SMEs: The Case of SMEs in the Rabat-Salé-Kénitra Region of Morocco

Mohammed Belbachir, Siham El Atmani, Hicham Bahri, Zineb El Atmani, Rachid Zammar and Cheklekbire Malainine (2025). *Sustainable and Intelligent Territorial Marketing and Entrepreneurship* (pp. 315-346).

www.irma-international.org/chapter/the-impact-of-digital-and-organizational-innovation-on-the-performance-of-local-smes/359739

Design of a Home Automation App to Assist Elderly and Limited Mobility People

Bianca Stephanie Guimarães Morais, Álvaro Sobrinho, Helder Oliveira, Lenardo Chaves e Silva and Robson Locatelli Macedo (2022). *Research Anthology on Cross-Disciplinary Designs and Applications of Automation* (pp. 859-876).

www.irma-international.org/chapter/design-of-a-home-automation-app-to-assist-elderly-and-limited-mobility-people/291669

A Fuzzy System for Evaluating Human Resources in Project Management

Oladele Stephen Adeola and Adesina Rafiu Ganiyu (2020). *International Journal of Technology Diffusion* (pp. 66-95).

www.irma-international.org/article/a-fuzzy-system-for-evaluating-human-resources-in-project-management/242992

The Role of Social Media on Young Online Consumer Behavior

Fanni Miháldinecz and Orlando Manuel Martins Marques Lima Rua (2022). *Handbook of Research on Digital Transformation Management and Tools* (pp. 144-168).

www.irma-international.org/chapter/the-role-of-social-media-on-young-online-consumer-behavior/311922