

701 E. Chocolate Avenue, Suite 200, Hershey PA 17033-1240, USA Tel: 717/533-8845; Fax 717/533-8661; URL-http://www.irm-press.com

ITB10712

Chapter VII

Mobility Management in Mobile Computing and Networking Environments

Samuel Pierre, Ecole Polytechnique de Montreal, Canada

Abstract

This chapter analyzes and proposes some mobility management models and schemes by taking into account their capability to reduce search and location update costs in wireless mobile networks. The first model proposed is called the built-in memory model; it is based on the architecture of the IS-41 network and aims at reducing the homelocation-register (HLR) access overhead. The performance of this model was investigated by comparing it with the IS-41 scheme for different call-to-mobility ratios (CMRs). Experimental results indicate that the proposed model is potentially beneficial for large classes of users and can yield substantial reductions in total user-location management costs, particularly for users who have a low CMR. These results also show that the cost reduction obtained on the location update is very significant while the extra costs paid to locate a mobile unit simply amount to the costs of crossing a single pointer between two location areas. The built-in memory model is also compared with the forwarding pointers' scheme. The results show that this model consistently

This chapter appears in the book, Wireless Information Highways, edited by Dimitrios Katsaros, Alexandros Nanopoulos and Yannis Manalopoulos. Copyright © 2005, IRM Press, an imprint of Idea Group Inc. Copyring or distributing in print or electronic forms without written permission of Idea Group Inc. is prohibited.

outperforms the forwarding pointers' strategy. A second location management model to manage mobility in wireless communications systems is also proposed. The results show that significant cost savings can be obtained compared with the IS-41 standard location-management scheme depending on the value of the mobile units' CMR.

Introduction

Mobile communication networks are made possible by the convergence of several different technologies, specifically computer networking protocols, wireless-mobile communication systems, distributed computing, and the Internet. With the rapidly increasing ubiquity of laptop computers, which are primarily used by mobile users to access Internet services such as e-mail and the World Wide Web (WWW), support of Internet services in a mobile environment has become a growing necessity. Mobile Internet providers (IPs) attempt to solve the key problem of developing a mechanism that allows Internet protocol (IP) nodes to change physical locations without changing IP addresses, thereby offering Internet users the so-called "nomadicity." Furthermore, advances in wireless networking technologies and portable information devices have led to a new paradigm of computing called *mobile computing*. According to this concept, users who carry portable devices have access to information services through a shared infrastructure regardless of their physical location or movements. Such a new environment introduces new technical challenges in the area of information access. Traditional techniques to access information are based on the assumptions that the host locations' distributed systems do not change during computation. In a mobile environment, these assumptions are rarely valid or appropriate.

Mobile computing is distinguished from classical, fixed-connection computing due to the following elements: (a) the mobility of nomadic users and the devices they use, and (b) the mobile resource constraints such as limited wireless bandwidth and limited battery life. The mobility of nomadic users implies that the users might connect from different access points through wireless links and might want to stay connected while on the move, despite possible intermittent disconnections. Wireless links are relatively unreliable and currently are two to three times slower than wired networks. Moreover, mobile hosts powered by batteries suffer from limited battery life constraints. These limitations and constraints provide many challenges to address before we consider mobile computing to be fully operational. This remains true despite the recent progress in wireless data communication networks and handheld device technologies.

In next-generation systems supporting mobile environments, mainly due to the huge number of mobile users in conjunction with the small cell size, the influence of mobility on the network performance is strengthened. More particularly, the accuracy of mobility models becomes essential to evaluate system design alternatives and network implementation costs. The device location is unknown a priori and call routing in general implies mobility management procedures. The problems which arise from subscriber mobility are solved in such a way that both a certain degree of mobility and a sufficient quality of the aspired services are achieved.

36 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage: www.igi-

global.com/chapter/mobility-management-mobile-computingnetworking/31449

Related Content

Reality Mining, Location Based Services and E-Business Opportunities: The Case of City Analytics

José Antonio Ariza Montes, Alfonso Carlos Morales Gutiérrez, Emilio Morales Fernándezand Alfredo Romeo (2012). *Wireless Technologies: Concepts, Methodologies, Tools and Applications (pp. 1520-1532).*

www.irma-international.org/chapter/reality-mining-location-based-services/58854

MAC Optimization Based on the Radio Resource Allocation in a 5G eMBB System Simulated in the MmWave Model

Ismail Angri, Abdellah Najidand Mohammed Mahfoudi (2021). *International Journal of Wireless Networks and Broadband Technologies (pp. 32-54).*

www.irma-international.org/article/mac-optimization-based-on-the-radio-resource-allocation-in-a-5g-embb-system-simulated-in-the-mmwave-model/282472

Resource Allocation using Dynamic Fractional Frequency Reuse: A Technique to Reduce Inter Cell Interference at the Cells Edges

Anitha S. Sastryand Akhila S (2017). *International Journal of Wireless Networks and Broadband Technologies (pp. 34-44).*

 $\underline{\text{www.irma-international.org/article/resource-allocation-using-dynamic-fractional-frequency-reuse/198515}$

Perceptual Quality Assessment of Packet-Based Vocal Conversations over Wireless Networks: Methodologies and Applications

Sofiene Jelassi, Habib Youssefand Guy Pujolle (2012). Wireless Technologies: Concepts, Methodologies, Tools and Applications (pp. 273-310).

www.irma-international.org/chapter/perceptual-quality-assessment-packet-based/58793

New Routing Technique to Enhance Energy Efficiency and Maximize Lifetime of the Network in WSNs

Nezha El Idrissi, Abdellah Najidand Hassan El Alami (2020). *International Journal of Wireless Networks and Broadband Technologies (pp. 81-93).*

 $\underline{\text{www.irma-international.org/article/new-routing-technique-to-enhance-energy-efficiency-and-maximize-lifetime-of-the-network-in-wsns/257780}$