



A Method For Narrowband HP FIR Filter Design Using Fewer Multiplications

Gordana Jovanovic-Dolecek, Vlatko Dolecek and Isak Karabegovic
INAOE, Puebla Mexico, University of Sarajevo, Bosnia and Herzegovina,
University of Bihac, Bosnia and Herzegovina, INAOE, Mexico, Tel/Fax: + 222 470517, gordana@inaoep.mx

ABSTRACT

This paper presents a new efficient method for the design of narrowband highpass filters (HP) with fewer multiplications. The method is based on an Interpolated filter (IFIR) structure and the sharpened comb filter (SCF). The novelty of the technique is based on the usage of the SCF filter as an image suppressor in the IFIR structure. The method is useful for narrowband HP filter design.

INTRODUCTION

Finite impulse response (FIR) filters are known to have some very desirable properties such as linear phase, stability, and absence of limit cycle, however their application generally requires more computation. A number of techniques have been proposed to reduce the complexity of FIR filters over the past years. This method belongs to the group of methods which separate the filter transfer function into two or more components having much lower order than the prototype filter (T.Saramaki at al., 1988; Jovanovic-Dolecek and Reyes, 1999; Lian and Lim, 1998 , etc).

We consider narrowband filters. As it is known, one of the most difficult problems in digital filtering is the implementation of narrowband filters. The difficulty lies in the fact that such filters require high-order designs in order to meet the desired frequency response specification. In turn, high order filters require a large amount of computation and so are difficult to implement. In this paper we propose an implementation of a narrowband high-pass filter using Interpolated FIR (IFIR) filters (T. Saramaki at al., 1988) and sharpened comb filter, (Kwentus at al., 1997).

The basic idea behind IFIR filters is to implement a FIR filter as cascade of two FIR filters, $G(z^L)$ and $I(z)$, such that each filter in the cascade has a much lower order than the prototype filter $H(z)$.

The filter $G(z)$, named the shaping filter is a linear-phase lowpass filter. The unwanted images introduced in going from $G(z)$ to $G(z^L)$ are suppressed by the interpolation filter $I(z)$.

In (Jovanovic-Dolecek and Reyes 1999) is proposed to use a comb filter as an interpolation filter. A comb filter has a very narrow passband, wide transition band and large side lobes.

In order to improve the characteristics of the comb filter, in this paper we propose the structure described in the following section.

PROPOSED STRUCTURE

Kwentus at al., 1997, proposed a sharpened comb filter for the multirate applications

$$H_{sh}(z) = 3H_c^2(z) - 2H_c^3(z), \tag{1}$$

where the comb filter $H_c(z)$ is given as

$$H_c(z) = \left(\frac{1 - z^{-L}}{L(1 - z^{-1})} \right)^K = \left(\frac{1}{L} \sum_{n=0}^{L-1} z^{-n} \right)^K \tag{2}$$

and K is called a stage. As it is seen in equation (2), all coefficients are equal to 1 so it is not necessary to apply any multiplication.

The described structure may be used for the design of a lowpass filter.

In order to design a highpass filter, we replace the cutoff frequencies of the highpass filter, ω_p and ω_s , by the corresponding lowpass specifications as follows,

$$\begin{aligned} \omega_p' &= \pi - \omega_p \\ \omega_s' &= \pi - \omega_s \end{aligned} \tag{3}$$

Given the specification (3), a lowpass IFIR sharpened filter can be designed.

For an even interpolation factor L , the unwanted spectrum is at low frequencies and the desired spectrum is at high frequencies. So in order to eliminate the unwanted spectrum, it is only necessary to derive a highpass interpolation filter from its lowpass counterpart. This is done by changing the sign of every other coefficient

$$h_{HP}(n) = (-1)^n h_{LP}(n) \tag{4}$$

Therefore, for an even L , we transform the sharpened filter into a highpass filter using (4).

For an odd interpolation factor L it is necessary transform both the shaping filter $G(z)$ and the sharpened filter $H_{sh}(z)$ into highpass filters.

The method is illustrated in the next example:

Example 1:

We design the highpass filter with the passband frequency $\omega_p = 991$ and the stopband frequency $\omega_s = 98$. Passband ripple is 2 db and the stopband attenuation 60 db.

The prototype HP linear phase filter has an order of $N=458$ and is shown in Figure 1.

We use $L=16$ and $K=2$ in the proposed structure and obtaining a shaping filter whose order is $N_G=33$. The result is shown in Figure 2.

Figure 2 confirms that the passband specification is satisfied.

Figure 1: The prototype filter




Figure 2: The designed filter





Figure 3: Passband specification



CONCLUSION

This paper presents one method for the narrowband highpass filter design with the aim to decrease the number of the multiplications. The method is based on the application of an IFIR structure where the interpolation filter is a sharpened comb filter.

The sharpened comb filter has an advantage because no multipliers and no storage are required for the interpolator coefficients. The overall result is the lower computational complexity of the resulting IFIR structure. The method is especially useful in the design of very narrowband high pass FIR filters and its efficiency increases with the increase of the interpolation factor L .

REFERENCES

- G. Jovanovic-Dolecek and A. Sarmiento Reyes, (1999). "An efficient method for narrowband FIR filter design", *Computacion y Sistemas*, 2, 78-86.
- A. Kwentus, Z. Jiang, and A. Willson, (1997). "Application of filter sharpening to cascaded Integrator-Comb decimation filter", *IEEE Transaction on Signal Processing*, 4, 457-467.
- Y. Lian and Y.C. Lim, (1998), "Structure for narrow and moderate transition band FIR filter design", *Electronic Letters*, 34, 49-51.
- T. Saramaki, Y., Nuevo, and S.K. Mitra, (1988) "Design of computationally efficient interpolated FIR filters", *IEEE Transaction on Circuit and Systems*, 35, 70-78.

0 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/proceeding-paper/method-narrowband-fir-filter-design/31776

Related Content

Mobile Sink with Mobile Agents: Effective Mobility Scheme for Wireless Sensor Network

Rachana Borawake-Satao and Rajesh Shardanand Prasad (2017). *International Journal of Rough Sets and Data Analysis* (pp. 24-35).

www.irma-international.org/article/mobile-sink-with-mobile-agents/178160

Online Prosocial Behaviors

Michelle F. Wright and William Stanley Pendergrass (2018). *Encyclopedia of Information Science and Technology, Fourth Edition* (pp. 7077-7087).

www.irma-international.org/chapter/online-prosocial-behaviors/184404

The Governance of Information Infrastructures

(2012). *Perspectives and Implications for the Development of Information Infrastructures* (pp. 136-155).

www.irma-international.org/chapter/governance-information-infrastructures/66260

Subject Recommended Samples: Snowball Sampling

Pedro Isaias, Sara Pifano and Paula Miranda (2013). *Information Systems Research and Exploring Social Artifacts: Approaches and Methodologies* (pp. 43-57).

www.irma-international.org/chapter/subject-recommended-samples/70709

Comprehensive Survey on Metal Artifact Reduction Methods in Computed Tomography Images

Shrinivas D. Desai and Lingnanagouda Kulkarni (2015). *International Journal of Rough Sets and Data Analysis* (pp. 92-114).

www.irma-international.org/article/comprehensive-survey-on-metal-artifact-reduction-methods-in-computed-tomography-images/133535