Chapter 9 Security Issues on Outlier Detection and Countermeasure for Distributed Hierarchical Wireless Sensor Networks

Yiying Zhang Shenyang Institute of Engineering, China

> Lin He Korea University, South Korea

> > Lei Shu Osaka University, Japan

> > **Takahiro Hara** Osaka University, Japan

> > **Shojiro Nishio** Osaka University, Japan

ABSTRACT

Outliers in wireless sensor networks (WSNs) are sensor nodes that launch attacks by abnormal behaviors and fake message dissemination. However, existing cryptographic techniques have difficulty in detecting these outliers, which makes outlier recognition a critical and challenging issue for reliable and secure data dissemination when outliers exist in WSNs. This chapter is concerned about detection and elimination problems of outlier. To efficiently identify and isolate outliers, we present a novel "Outlier Detection and Countermeasure Scheme" (ODCS), which consists of three mechanisms: (1) An abnormal event observation mechanism (AEOM) for network surveillance; (2) An exceptional message supervision mechanism (EMSM) for distinguishing fake messages by exploiting spatiotemporal correlation and consistency; (3) An abnormal frequency supervision mechanism (AFSM) for the evaluation of node behavior. The chapter also provides a heuristic methodology which does not need the knowledge of normal or malicious sensors in advance. This property makes the ODCS not only to distinguish and deal with various

DOI: 10.4018/978-1-61350-110-8.ch009

dynamic attacks automatically without advance learning but also reduces the requirement of capability for constrained nodes. In our solution, the communication is limited to a local range, such as one-hop or a cluster, which can reduce the communication frequency and circumscribe the session range further. Moreover, the chapter also provides countermeasures for different types of attacks, such as the rerouting scheme and the rekey security scheme, which can separate outliers from normal sensors and enhance the robustness of network, even when some nodes are compromised by adversary. Simulation results indicate that our approach can effectively detect and defend the outlier attack.

INTRODUCTION

Wireless sensor networks (WSNs) can effectively employ different applications by collecting sensory information in unattended and often adversarial environments such as enemy detection in battle fields, or fire monitoring in urban areas (Aggarwal, 2001). Therefore, the security provision of confidentiality and authentication is a critical requirement for many wireless sensor network applications. However, sensor nodes are highly constrained in transmission power, on-board energy, processing capacity and storage, which requires careful resource management. Due to these limited resources and operation in hostile environments, WSNs are subjected to numerous threats and are vulnerable to attacks from inside, e.g., outliers (Akyildiz et al., 2002), (Sheng et al., 2007), (Liu, Cheng, & Chen, 2007), (Zhang et al., 2010), or from outside, e.g., eavesdropping (Bandyopadhyay & Coyle, 2003).

In this chapter, we focus on the outliers. The outliers are severely destructive to the function of WSNs. Since the outliers usually occupy the same network source as normal nodes, they can easily manufacture the fake messages or tamper with the real messages to impact the performance of network. However, the traditional techniques, such as cryptographic encryption, authentication etc., cannot detect and eliminate all attacks.

Although most of previous security works focus on outside attacks and try to establish a credible relationship among sensor nodes in WSN based on the traditional cryptography (Akyildiz et al., 2002), (Bandyopadhyay & Coyle, 2003), (Bellare, Canetti, & Krawczyk, 1996), (Branch et al., 2006), (Breunig et al., 2000), (Chan, Perrig, & Song, 2003), (Chang & Kuo, 2006), (Chen et al., 2002), (David et al., 2004), (Deng, Han, & Mishra, 2005), which cannot support sufficient protection from all attacks, especially outliers from outlier. Thus, it becomes very urgent and challenging to design an outlier detection scheme. In this chapter, we present a novel outlier detection scheme as well as a series of countermeasures.

PROBLEM STATEMENT

Outliers (also called Inside attacker) in WSNs are some sensor nodes controlled by adversary, they do not perform tasks as normal nodes but exhibit different types of abnormal behaviors, e.g., dropping received messages from their neighbors, forwarding messages to enemy, broadcasting redundant messages, and disseminating fake messages (Akyildiz et al., 2002), (Liu, Cheng, & Chen, 2007). The outlier has the same network resource as a normal sensor node, but its behaviors are different. Typically, outliers are compromised and remote-controlled by adversary. Outliers also attack WSNs by tampering with messages transferred in WSNs or generating bogus messages and forwarding them to critical nodes (e.g., aggregation nodes or sink node), which typically reduces network performance in terms of reliability and security because of the following consequences (Bandyopadhyay & Coyle, 2003):

27 more pages are available in the full version of this document, which may be purchased using the "Add to Cart" button on the publisher's webpage:

www.igi-global.com/chapter/security-issues-outlier-detection-

countermeasure/59683

Related Content

Hardware Implementations of Image/Video Watermarking Algorithms

Fayez M. Idris (2010). Advanced Techniques in Multimedia Watermarking: Image, Video and Audio Applications (pp. 425-454).

www.irma-international.org/chapter/hardware-implementations-image-video-watermarking/43481

Information Imperfection as an Inherent Characteristic of Adaptive Hypermedia: Imprecise Models of Users and Interactions

Miguel-Ángel Sicilaand Elena García Barriocanal (2005). *Adaptable and Adaptive Hypermedia Systems* (*pp. 150-168*).

www.irma-international.org/chapter/information-imperfection-inherent-characteristic-adaptive/4183

HaMA: A Handicap-based Architecture for Multimedia Document Adaptation

Asma Saighi, Roose Philippe, Nassira Ghoualmi, Sébastien Laborieand Zakaria Laboudi (2017). International Journal of Multimedia Data Engineering and Management (pp. 55-96). www.irma-international.org/article/hama/182651

Color Image Segmentation: From the View of Projective Clustering

Song Gao, Chengcui Zhangand Wei-Bang Chen (2012). *International Journal of Multimedia Data Engineering and Management (pp. 66-82).* www.irma-international.org/article/color-image-segmentation/72893

Digital Streaming Content: Changing Social Perceptions

Vidya Deshpandeand Nithin Kalorth (2024). *Exploring the Impact of OTT Media on Global Societies (pp. 284-289).*

www.irma-international.org/chapter/digital-streaming-content/340648